

Notes:

-
3. Dimensions given in inches (mm).
- Reinforcement by Door Mfr.
- 3/4 Min. (19) Clearance
- 1/2 (13)
- Common ϕ of Lock and Strike (Edge of Rabbet)
- ϕ Door Edge
- +1/64
9/16^{+0/-0.000} (14.3^{+0/-0})
- #12-24 Machine Screw (2 Places)
- 3/8 (10)
- ϕ Strike
- #6-32 Machine Screw (2 Places) See Note 1
- 1/4 (6)
- 1-3/4 to 2-1/4 (45) to (57)
- 1/2 (13) Door Thickness Typ.
- Inactive Door Dimensions (Strike)
- 11/16 (17.4)
- 5/8^{+0.015/-0.000} (15.8^{+0.4/-0})
- #12-24 Tap (2 Places)
- 8-1/8^{+0.005/-0.000} 206.4^{+0.4/-0}
- #6-32 Mach. Screw (2 Places)
- 1-3/4-2-1/4 Door Thickness (Typ.)
- 5/16 (8)
- Active Door Dimensions (Lock)
- Cutout in Reinforcement 1-1/4 Min. (32)
- 15/64^{+0.005/-0.000} (5.9) ± 2
- 1/2 (13)
- 2-3/4 (70)
- 4-1/2 (114.3)
- Backset 1/2 (13)
- Clearance
- 27/32 (21)
- Reinforcement by Door Mfr.
- 1/2 (13)
- 7-1/4^{+0.005/-0.000} (184.2^{+1/-1})
- 6-1/2 Min (165)
- 8^{+0.015/-0.000} (203.2^{+0.4/-0})
- Front Strip Support by Door Mfr.
- 5/16 (8)

Copyright © 2023, 2024, ASSA ABLOY ACCENTRA™ Access and Egress Hardware Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Access and Egress Hardware Group, Inc. is prohibited.

1-855-557-5078, Ext. 2 www.accentra-assaabloy.com

Sheet: 1 of 1

ACCENTRA
ASSA ABLOY