

Rockwood PDU8500 Panic Device

Frequently Asked Questions

Experience a safer
and more open world

Question: What product line does the PDU8500 Panic Device fall under?

Answer: Rockwood products. Device literature and pricing can be found on rockwoodmfg.com.

Question: Who can purchase the PDU8500 Panic Device?

Answer: Customers who have an open account with Rockwood Manufacturing and have an understanding that they are required to follow installation instructions and videos.

Question: What is required to order a Panic Device

Answer: A completed PDU8500 order form must be filled out, then a door template will be sent back to customer for final approval. Once approved, the order will be entered.

Question: What door types does the PDU8500 work with?

Answer: Metal, storefront and wood doors.

Question: Are there any special requirements for hollow metal frames?

Answer: Yes, specific stop height, stop width, and reinforcements are required. See the PDU8500 order form for details.

Question: Where can I find strike templates?

Answer: Strike templates can be found on rockwoodmfg.com: Library > Product Documentation > Templates > Architectural Panic Devices

Question: What stiles can the PDU8500 device be used on?

Answer: The device will work on medium and wide stiles. Medium stiles are 3-1/2" and less than 5". 5" and greater is considered a wide stile.

Question: What door thicknesses are available?

Answer: The device will work on doors 1-3/8" – 2-1/2" thick.

Question: What is the smallest backset that can be used on the PDU8500?

Answer: The smallest backset is 2-1/4"

Question: What finishes are available?

Answer: The device is stainless steel based. All stainless steel finishes, OptiCoat™ sublimation finishes, stock and custom powder coats are available.

Question: What is the warranty on the device?

Answer: 3-year limited warranty. See ASSA ABLOY Rockwood PDU8500 Series Warranty for full details.

Question: Can the device be modified in the field?

Answer: No. Any field prep will void the warranty.

Question: Does the device meet California Building Code (2019) Sec. 11B-309.4?

Answer: Yes, there is an option that can be chosen when ordering to meet California Building Code (2019) Sec 11B-309.4. This option was specifically designed to be used in the state of California or other areas where a 5lb. activation force is required to meet ADA. For other geographies we recommend using our standard PDU8500.

The ASSA ABLOY Group is the global leader in access solutions. Every day we help people feel safe, secure and experience a more open world.

ROCKWOOD®

ASSA ABLOY

FREQUENTLY ASKED QUESTIONS - CONTINUED

Question: Is the PDU8500 fire rated?

Answer: Yes, when specified (with letter F). UL10C 90-minute rating with hose stream, pairs of hollow metal or wood/composite doors up to 8'x8' only. Three fire bolts (PD18BFB) are provided.

Question: Is dogging standard?

Answer: Yes, the device will come with the dogging feature unless otherwise specified when ordering. This feature may also be added to or removed from the device in the field.

Question: Any special door requirements?

Answer: It is highly recommended for the door to be prepped in a door shop with CNC equipment. Door must be prepped when it is horizontal.

Question: What is the lead time?

Answer: Approximate lead time is 15 working days from the time the order is entered into Rockwood's system. Lead time may change depending on quantity, etc.

Question: Where is the PDU8500 assembled?

Answer: In America's County: Somerset County, Pennsylvania.



Rockwood Manufacturing Company
300 Main St.
Rockwood, PA 15557
www.rockwoodmfg.com
orders.rockwood@assaabloy.com
1 800 458 2424

Rockwood is a brand associated with ASSA ABLOY Accessories and Door Controls Group, Inc. Copyright © 2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited. Printed in the U.S.A.