

How to Order Glass Solutions Panic Device

Experience a safer
and more open world

Part #	Order Qty	Single Or Pair	Finish	Handing	Door Type	Door Height*	Door Width*	Horizontal Crash Bar Height	If-3, Please specify dimension from bottom of door to bottom of mating pull	Rail Profile	Glass Thk.	Cylinder Type	Strike Type	Lcbma	Infill Color	Push Region Engraving	Dogging Option	Bottom Mount Location	Door Marking
PDU8000-3	1	Sgl.	US32D	Swing 3-RHR	P	95.5"	35.75"	37"	10"	SP	1/2"	09	Single Manual	NO	Black	English	Yes	Glass	100A

SAMPLE

PDU8000			10BE	Swing 3-RHR	A	Please refer to NGA MAX guidelines on page 2. (Need Actual Door Dimensions)	Please refer to NGA MAX guidelines on page 2. (Need Actual Door Dimensions)	37"	*Minimum is 1"	LP	1/2"	01	Single Manual	LCBMA	Black (Default)	English	Yes (Default)	Flush (With Door Bottom)	
PDU8000-1			314E	Swing 4-LHR	Top Bottom Patch			42"		Low Profile (Less 3")	9/16"	Mortise Cylinder	Double Manual	NO	Black (Default)	French	No		
PDU8000-2			BPC		BP			Other		SP	5/8"	02	Secure Sgl. Elec. 12VDC	LCBMA	Custom	Spanish			
PDU8000-3			CUSTOM PC		Top Patch Bottom Rail					Standard profile (default)	3/4"	7 Pin SFIC Housing W/CC	Secure Sgl. Elec. 24VDC		Less Paint			Glass	
PDU8000-4			FBPC		P						11/16"	03	Secure Dbl. Elec. 12VDC		White			Rail	
PDU8000-5			RPC		Top Rail Bottom Rail						13/16"	04	Secure Dbl. Ele. 24VDC						
PDU8000-6			US32								Other	Special Order Cylinders	Safe Sgl. Electric 12VDC						
			US32/US32D SPLIT (Pol. Grip)									Customer Sending Cylinder	Safe Sgl. Elec. 24VDC						
			US32D									05	Safe Dbl. Elec. 12VDC						
			US32DMS									Dummy Cylinder	Secure Sgl. Elec. 12VAC						
			US32MS									06	Secure Dbl. Elec. 24VAC						
			WPC									Non Key Function	Safe Sgl. Electric 12VAC						
			WSP									09	Safe Sgl. Electric 24VAC						
			BSP									7 Pin SFIC HSG W/ Yale Core	Safe Dbl. Electric 12VAC						
			315E										Less Strike						

*Required; **Optional

To improve the order process of Glass Solutions Panic Device, please provide and adhere to the following: Fill out the Panic Device Order Form with required information; The sample above displays the customer acknowledgment; and information needed to ease the ordering process.

Infill is not available on split finish US32D/32, US32. The 06 Cylinder option is only available on the PDU8000 and the PDU8000-6.

The ASSA ABLOY Group is the global leader in access solutions. Every day we help people feel safe, secure and experience a more open world.

Mating Pull for Exterior Side:

0-No Mating Pull



1-Full Height L Shape



2-Half Height L Shape



3-Full Height Straight



4-Half Height Straight



5-Short Centered Straight



6-Horizontal Straight



NGA Recommendations for Glass Doors. Guidelines for Interior Swinging Door Sizes

Entrances utilizing non-structural interlayers and/or exterior door applications are dependent on numerous factors impacting the intended design of the entrance. These types of entrances should be reviewed by qualified individuals or manufacturers with engineering capabilities. Fully Tempered and Tempered Laminated Glass.

		R/R (Full Rails)				P/P (Patch Fittings) and/or P/R (Rail Combinations)			
Glass Thickness		10mm (3/8 in.)	12 mm (1/2 in.)	16mm (5/8 in.)	19 mm (3/4 in.)	10mm (3/8 in.)	12 mm (1/2 in.)	16mm (5/8 in.)	19mm (3/4 in.)
Glass Weight		[5 lbs/sf]	[6.4 lbs/sf]	[8.1 lbs/sf]	[9.8 lbs/sf]	[5 lbs/sf]	[6.4 lbs/sf]	[8.1 lbs/sf]	[9.8 lbs/sf]
Concealed Over-head Closer (200lb. max typically)	Width	914 mm (36 in.)	1067 mm (42 in.)	914 mm (36 in.)	914 mm (36 in.)	914 mm (36 in.)	1067 mm (42 in.)	914 mm (36 in.)	914 mm (36 in.)
	Height	2134 mm (84 in.)	2743 mm (108 in.)	2591 mm (102 in.)	2134 mm (84 in.)	2134 mm (84 in.)	2591 mm (102 in.)	2438 mm (96 in.)	2134 mm (84 in.)
	Glass Weight	(105 lbs.)	(202 lbs.)	(207 lbs.)	(206 lbs.)	(105 lbs.)	(191 lbs.)	(195 lbs.)	(206 lbs.)
Floor Closer	Width	914 mm (36 in.)	1219 mm (48 in.)	1219 mm (48 in.)	1219 mm (48 in.)	914 mm (36 in.)	1067 mm (42 in.)	1067 mm (42 in.)	914 mm (36 in.)
	Height	2134 mm (84 in.)	2743 mm (108 in.)	2896 mm (114 in.)	3048 mm (120 in.)	2134 mm (84 in.)	2591 mm (102 in.)	2591 mm (102 in.)	2473 mm (108 in.)
	Glass Weight	(105 lbs.)	(230 lbs.)	(308 lbs.)	(392 lbs.)	(105 lbs.)	(191 lbs.)	(241 lbs.)	(265 lbs.)

ASSA ABLOY Opening Solutions
Glass Solutions
Rockwood, PA
P: 855.594.6989 • F: 844.851.8665
www.assaabloyglass.us
Orders.GlassSolutions@assaabloy.com • TechSupport.GlassSolutions@assaabloy.com

Canada:
ASSA ABLOY Door Security Solutions
160 Four Valley Drive
Vaughan, ON L4K 4T9
P: 800.461.3007
www.assaabloydss.ca