

## Fact Sheet

## Assemblies with Factory Installed Multi-Point Hardware

Experience a safer and more open world

Blast	Hurricane	Tornado	Max. Size Fire Capability	Door Series	Hardware	Leaf Size	Gauge	Core	Other Comments
Х	X	N/A	Steel stiffened only 4'0" x 8'0" single - 3 hour	Multi-Solution Blast and Hurricane Resis- tant Opening	Corbin Russwin - BL6600 Series SARGENT - BL7300 Series	2'8" Min. width 6'8" Min. height 4'0" Max. width 8'0" Max. height	14 min. 12 max.	Steel stiffened 18 gauge stiffeners	Flush only
N/A	X	х	Steel stiffened or honeycomb 4'0" x 8'0" single - 3 hour 8'0" x 8'0" pair - 3 hour	StormPro or 150 PSF Hurricane Resistant Assemblies	Corbin Russwin - FE6600 Series SARGENT - FM7300 Series	2'8" Min. width 6'8" Min. height 4'0" Max. width 8'0" Max. height	14 min.	Steel stiffened 22 gauge stiffeners (18 gauge stiffeners optional) Optional Polystyrene; Polyurethane; Honeycomb	Buy America polyurethane or honeycomb core only 3'0" x 7'0" Min.  Glass limited to visible 10" x 10" size
N/A	N/A	N/A	Steel stiffened only 4'0" x 10'0" single - 3 hour 8'0" x 10'0" pair - 3 hour	Medallion or 747 Door	Corbin Russwin - MP6600 Series SARGENT - 7300 Series	2'0" Min. width 6'8" Min. height 5'0" Max. width 10'0" Max. height	18 min. 16 max.	Steel stiffened 22 gauge stiffeners	Glass allowed

Corbin Russwin and SARGENT concealed vertical rods, top / bottom bolts, and mortise lock body cassettes on this page are only available as factory installed in a Ceco or Curries Door. Doors and frames are ordered through the door brands. Hardware is ordered through the hardware brands. The mortise lock body, levers and trim are shipped directly from Corbin Russwin or SARGENT and must be field installed by a factory trained installer into the corresponding Ceco or Curries door.

IMPORTANT: Do not remove any hardware blocking or filler plates in the door or the frame until the mortise lock is ready to be installed.

CECO DOOR | CORBIN RUSSWIN | CURRIES | SARGENT

**ASSA ABLOY Opening Solutions** 

110 Sargent Drive New Haven, CT 06511 (800) 377-3948