

Acoustical Wood Assemblies

Acoustical Wood Features

- True wood door construction with steel frames
- Up to STC 53
 - Flush wood door configuration
 - 4'0" x 8'0" maximum leaf size
- Up to STC 51
 - Factory installed glazing
 - 4'0" x 8'0" maximum leaf size
- Up to STC 50
 - Flush wood door configuration
 - 4'0" x 10'0" maximum leaf size
- Various wood species, stains and finishes
- Pairs available
- Doors are only 1-3/4" thick
- 20 minute fire ratings
- Integral flush mounted door bottom design
- Adjustable perimeter sound seals, flat unfluted threshold and cam-lift hinges

Applications

- K-12 and College University
- Government and Public Facilities
- Healthcare
- Hospitality
- Offices



True wood acoustical doors and steel frame assemblies from Curries provide third party tested Sound Transmission Class (STC) operable ratings up to STC 53. Face veneers are available in many different species, stains and finishes to meet any project requirement. Wood acoustical doors are only 1-3/4" thick and offer factory installed glazing and fire rated assembly options. Adjustable perimeter sound seals, threshold and cam-lift hinges are provided with every assembly. Perfect for openings designed with the warm look and feel of wood in mind while requiring a high STC performance rating.

1502 12th Street NW | Mason City, IA 50401
Phone: 641-423-1334 | Fax: 641-424-8305
www.curries.com

Experience a safer
and more open world