



NOTES:

1. This template is an addition to the device template. Locate centerlines using horizontal and vertical references on device template.
2. Do not scale drawing.
3. Dimensions are in inches (mm).
4. LHR door shown. Preparation is typical for both door hands.
5. Provide adequate structural support to maintain door integrity during operation.
6. Prepare mounting holes when installing trim.
7. Dimensions given about a centerline are symmetrical.
8. Unspecified radii 1/8" (3) maximum.



626F

NOTE: Lever and knob prefix does not affect door prep.



Section X - X

RESPONSIBILITY
DOOR AND FRAME MANUFACTURERS ARE
RESPONSIBLE FOR PROVIDING ADEQUATE
CONSTRUCTION OR REINFORCEMENTS FOR
PROPER INSTALLATION OF HARDWARE SHOWN.
ALL ARCHITECTURAL BUILDERS HARDWARE MUST
BE INSTALLED ON PROPERLY REINFORCED
DOORS AND FRAMES, REGARDLESS OF TYPE,
MATERIAL, OR METHOD OF CONSTRUCTION.

626F Trim
With 1500(F), 2100(F) or 7100(F) Series
Rim and Vertical Rod Exit Devices
Wood or Composite Door Preparation

1-855-557-5078 Ext. 2

www.accentra-assaabloy.com

Experience a safer
and more open world

Copyright © 2005, 2023, 2024, ASSA ABLOY ACCENTRA™ Access and Egress Hardware Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Access and Egress Hardware Group, Inc. is prohibited.

ACCENTRA
ASSA ABLOY

SUPERSEDES	7400-1626 (12/23)	DO NOT SCALE DRAWING
TEMPLATE NUMBER	7400-1626	SHEET 1 of 1

DATE
05/24