

# Checking a SAFEBOOLT™ Installation

 **SECURITECH**

**ASSA ABLOY**

## SAFEBOOLT™ Series

### Instant Lockdown Mechanical Locks

#### 1. Trigger Action

With the door open

- Press the trigger.  
It should project the bolt and jump back. If not, remove the cover and check the button for any burrs or sticking points.



#### 2. Lever Action Test

With the door open



##### Fast Retract Test

- Press the trigger
- Lower the lever **quickly** until it stops and then let it come back up.

*The deadbolt should retract and stay in.*

*The latch should have gone in and come back out.*

##### Slow Retract Test

- Press the trigger
- Lower the lever **slowly** until it stops and then let it come back up.

*The deadbolt should retract and stay in.*

*The latch should have gone in and come back out.*



##### Notes:

- If the bolt does not stay in, or pops out and 1/2" or stays out, remove the cover and adjust the height of the roller.
- It is normal for the indicator to jump back and forth a little bit as the lever is depressed and returned when the bolt is not projected.



- **Make sure all fasteners are tight**
- **Hand tighten, do not use power tools**

## ⚠ WARNING

This product can expose you to lead which is known to the state of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65warnings.ca.gov](http://www.P65warnings.ca.gov).

## ⚠ NOTE

Parts received may be slightly different from parts shown in this document. Refer to packing list for details on parts and fasteners received..

## ⚠ WARNING

Attention Installer: Improper installation may result in damage to the product and void the factory warranty.

### 3. Key Action

With the door open

#### Unlock Test

- Press the trigger
- Turn the key to retract the bolt. The key should turn easily about 1/4" turn and the bolt should stay in.
- Return the key and remove.

#### Locking Test

Turn the key in the opposite direction to throw the bolt.

Return the key and remove.



 **SECURITECH**

**ASSA ABLOY**

### 4. Strike Alignment

With the door closed

- Press the trigger
- Check the bolt projection into the strike



#### Inswing

- If the bolt rubs against the strike cover, remove the bottom part of the opening cover.



#### Outswing

- If the bolt rubs or does not fully project, check the strike location and remove any debris within the opening.

- Wipe the lock down with a soft clean cloth to remove any dust or debris left during installation.

**Questions? Call Securitech Tech Support 718.392.9000**

 **SECURITECH**  
**ASSA ABLOY**

54-60 46th Street  
Maspeth, NY 11378  
718-392-9000

INS-00119-Rev: A 10/24

1-800-622-5625 • [www.securitech.com](http://www.securitech.com)

Copyright © 2018, 2024, Securitech®. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Access and Egress Hardware Group, Inc. is prohibited.