

Rockwood SMU9000

Single Motion Device

Storefront/Hollow-Metal/Wood Door

Experience a safer
and more open world

Complete this form and email to: orders.rockwood@assaabloy.com / or fax to: 800-922-9212

Customer Information

Company Name: _____ Date: _____
 Account #: _____ Phone/Fax: _____ / _____
 Email: _____ PO #: _____ Line #: _____

Door Markings: _____



Quantity of Swing Pair(s): _____

Quantity of Singles: Swing 3 (RHR): _____ 4 (LHR) Single(s): _____


Door Type: ☐ Storefront ☐ Wood ☐ Hollow-MetalDoor Thickness: ☐ 1 3/4" ☐ 2 1/4" ☐ Other: _____ (min: 1 3/8" max: 3 1/2")

Frame Type: ☐ Aluminum - Removable Stop ☐ Wood - Removable Stop ☐ Hollow-Metal - Removable Stop
☐ Aluminum - Permanent Stop ☐ Wood - Permanent Stop ☐ Hollow-Metal - Permanent Stop

Stile: ☐ Medium Stile (3 7/16" - less than 5") Backset is 2 1/4"
☐ Wide Stile (choose backset) (5" or greater) Backset: ☐ 2 1/4" ☐ 4 1/8"
☐ Wood/Hollow-Metal Backset:
 Single Application is 5 1/8"
 Double Application is 4 1/8"

**Specify Handing**

(check both for pairs):

☐ 4 (LHR) ☐ 3 (RHR)**Hollow Metal Frame Requirements:**

Stop Height: 5/8"
 This will shift the top of the panic device down on the door when compared to an aluminium frame.

Stop Width: Minimum of 3" wide.

Reinforcement: Minimum 12 gauge closer reinforcement along the stop width in the area that the strike will be attached.

Actual Door Size: W: _____ H: _____

Note: Actual Door Size dimensions need to be actual door leaf size not a general opening size. Door gaps should NOT be included in these dimensions above.

Distance Between Bottom of Push Region to Bottom of Door: ☐ 34" ☐ 39" ☐ Other: _____Meets California Building Code (2019) Sec.11B-309.4¹: ☐ Yes ☐ No (default)**Finish Options²** (for both Single Motion Device and Mating Pull):

☐ US32/629 ☐ US32D/630 ☐ US32D316 ☐ US32316 ☐ US32DMS ☐ US32D/US32 (Push) ☐ 314E
☐ BSP ☐ FBPC ☐ WSP ☐ 4E ☐ 10BE ☐ Stock Powder Coats (specify): _____

Engraved "PUSH" Area Finish Options:

☐ Black Paint ☐ White Paint ☐ Less Paint (32 and powder coat only) ☐ Custom Color (specify): _____

¹This product was specifically designed to be used in the state of California or other areas where a 5lb. activation force is required to meet ADA.²Powder Coat options may not be tested to BHMA finish standards.

The ASSA ABLOY Group is the global leader in access solutions. Every day we help people feel safe, secure and experience a more open world.

Mating Pull for Exterior Side:

- ☐ 0-No Mating Pull



- ☐ 3-Full Height Straight

Bottom of Ext Pull:

- ☐ Full Height
☐ _____" up from bottom of door*



- ☐ 4-Half Height Straight



- ☐ 5-Short Centered Straight

Exterior Pull Length:

- ☐ Standard (19 1/4")
☐ Custom Length: _____"
(minimum is 19 1/4")



☐ **Custom RM Mating pull option** (provide RM part number): _____

*Minimum of 10" clearance from the floor on the mating pull side to prevent interference with wheelchairs and other mobility devices.

Cylinder Options:

- ☐ 01 – Mortise Cylinder
☐ 02 – 7-pin SFIC Housing w/Plastic Core
☐ †03 – Special Order (keyed alike)
☐ 04 – Customer Sending Cylinder to Factory – Length of Cylinder: _____
☐ 05 – Dummy Cylinder Housing
☐ 06 – Non-Keyed Function⁴ (only available on No Mating Pull)
☐ 09 – 7-pin SFIC w/ACCENTRA Core (standard)
☐ **10 – Customer Swapping in Field

**Cylinder rings will be provided for cylinder lengths up to 1⁵/₈". If cylinder length is greater than 1⁵/₈", please contact factory.

Dogging Feature: ☐ Yes (standard) ☐ No ☐ Security

Strike Options (Check all that apply. See website for strike templates):

- ☐ Manual ☐ 1600 Electric ☐ Strike Purchased Separately
☐ 9100 Electric
☐ 9200 Electric

- ☐ LM – Lock Monitor (optional on 1600)
☐ LMS – Latch Strike Monitoring (optional on 9100/9200)
☐ ***Medium Stile (optional on Manual and 9200)

***Select Medium Stile Strike for 2 1/4" backset.

Strike Finish Options: ☐ US32/629 ☐ US32D/630 ☐ US32D316 ☐ US32316 ☐ US32DMS ☐ 314E
☐ BSP ☐ FBPC ☐ WSP ☐ 4E ☐ 10BE ☐ Stock Powder Coats (specify): _____

Your signature indicates the information contained on this order form is accurate and ready to be manufactured.

(customer signature)

(date)

NOTE: Top door gap range is 1/8" - 1/4".

NOTE: Device is not to be used with coordinator.

NOTE: This device is not fire-rated.

Consult local building codes for ADA compliance. Industry standards recommend cylinder fall in between 34" and 48".

⁴Only available on No Mating Pull options.

[†]03 Cylinder option add on charge will apply. 4 week minimum lead time.

Rockwood Manufacturing Company
300 Main St.
Rockwood, PA 15557
www.rockwoodmfg.com
1 800 458 2424

Rockwood is a brand associated with ASSA ABLOY Accessories and Door Controls Group, Inc.

Copyright © 2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited. Printed in the U.S.A.