

Rockwood SMU9000

Single Motion Device

Glass Door

Experience a safer
and more open world

Complete this form and email to: orders.rockwood@assaabloy.com / or fax to: 800-922-9212.

Customer Information

Company Name: _____ Date: _____


Account #: _____ Phone/Fax: _____ / _____

Email: _____ PO #: _____ Line #: _____

*Please provide US customary fractional numbers only.


Quote #: _____ **Total Devices:** _____ ☐ Single ☐ Pair **Door Markings:** _____

Glass Thickness: ☐ 1/2" ☐ 3/4" ☐ Other: _____

Door Type: ☐ A  ☐ BP  ☐ P  ☐ H 

Specify Handing
(check both for pairs):

☐ 4 (LHR) ☐ 3 (RHR)



Description of Top Rail: ☐ Standard Profile ☐ Low Profile (less than 3" tall)
Rail Thickness: _____ (if not supplied by ASSA ABLOY)

Description of Bottom Rail: ☐ Standard Profile ☐ Low Profile (less than 3" tall)
Rail Thickness: _____ (if not supplied by ASSA ABLOY)

Actual Door Size¹: W: _____ H: _____

Distance Between Bottom of Push Region to Bottom of Door:

☐ 34" ☐ 39" ☐ Other: _____

Meets California Building Code (2019) Sec. 11B-304.9²: ☐ Yes ☐ No (default)

Finish Options³ (For both Single Motion and Mating Pull):

☐ US32/629 ☐ US32D/630 ☐ US32316 ☐ US32D316 ☐ US32MS ☐ US32D/US32 (Push) ☐ BSP
☐ WSP ☐ 314E ☐ 4E ☐ 10BE ☐ Stock Powder Coats (specify): _____

Engraved "PUSH" Area Finish Options:

☐ Black Paint ☐ White Paint
☐ Less Paint (32 and powder coat only) ☐ Custom Color (specify): _____

¹Top door gap must be no less than 3/16".

²This product was specifically designed to be used in the state of California or other areas where a 5 lb. activation force is required to meet ADA.

³Powder Coat options may not be tested to BHMA finish standards.

The ASSA ABLOY Group is the global leader in access solutions. Every day we help people feel safe, secure and experience a more open world.

Mating Pull for Exterior Side:

- ☐ 0-No Mating Pull



- ☐ 3-Full Height Straight

Bottom of Ext Pull:

- ☐ Full Height
☐ _____" up from bottom of door*



- ☐ 4-Half Height Straight



- ☐ 5-Short Centered Straight



Exterior Pull Length:

- ☐ Standard (19 1/4")
☐ Custom Length: _____" (minimum is 19 1/4")

☐ **Custom RM Mating pull option** (provide RM part number): _____

*Minimum of 10" clearance from the floor on the mating pull side to prevent interference with wheelchairs and other mobility devices.

Cylinder Options:

- ☐ 01 – Mortise Cylinder
- ☐ 02 – 7-pin SFIC Housing w/Plastic Core
- ☐ '03 – Special Order (keyed alike)
- ☐ 04 – Customer Sending Cylinder to Factory – Length of Cylinder: _____
- ☐ 05 – Dummy Cylinder Housing
- ☐ 06 – Non-Keyed Function⁴ (Blank Escutcheon Plate provided)
- ☐ 09 – 7 pin SFIC w/ACCENTRA Core (standard)
- ☐ **10 – Customer Swapping in Field

**Cylinder rings will be provided for cylinder lengths up to 1⁵/₈". If cylinder length is greater than 1⁵/₈", please contact factory.

Dogging Feature: ☐ Yes (standard) ☐ No ☐ Security

Strike Options (Check all that apply. See website for strike templates):

- ☐ Manual ☐ 1600 Electric ☐ Strike Purchased Separately
- ☐ 9100 Electric
- ☐ 9200 Electric
- ☐ LM – Lock Monitor (optional on 1600)
- ☐ LMS – Latch Strike Monitoring (optional on 9100/9200)

Strike Finish Options:

- ☐ US32/629 ☐ US32D/630 ☐ US32D316 ☐ US32316 ☐ US32MS ☐ BSP
- ☐ WSP ☐ 314E ☐ 4E ☐ 10BE ☐ Stock Powder Coats (specify): _____

Your signature indicates the information contained on this order form is accurate and ready to be manufactured.

(customer signature)

(date)

Consult local building codes for ADA compliance. Industry standards recommend cylinder fall in between 34" and 48".

⁴Only available on No Mating Pull options.

¹03 Cylinder option add on charge will apply. 4 week minimum lead time.