

Rockwood PDU8500F

Series Fire Rated Panic

Architectural Safety Exit Device

Experience a safer
and more open world

Complete this form and email to: orders.rockwood@assaabloy.com / or fax to: 800-922-9212

Customer Information

Company Name: _____ Date: _____
 Account #: _____ Phone/Fax: _____ / _____
 Email: _____ PO #: _____ Line #: _____

Door Markings: _____

Quantity of Swing Pair(s): _____ Note: Fire certification only on pairs of doors.

Door Type: ☐ Hollow-Metal ☐ Wood/Composite

Door Thickness: ☐ 1 3/4"

Frame Type: ☐ Hollow-Metal - Permanent Stop ☐ Wood/Composite - Permanent Stop

Stile: ☐ Hollow-Metal / Wood/Composite Backset:
 Double Application is 4 1/8"

Hollow Metal Frame Requirements:

Stop Height: 5/8" - This will shift the top of the panic device down on the door when compared to an aluminium frame.

Stop Width: Minimum of 3" wide.

Reinforcement: Minimum 12 gauge closer reinforcement along the stop width in the area that the strike will be attached.



Actual Door Size: W: _____ H: _____

Note: Actual/Net Door Size dimensions need to be actual/net door leaf size not a general opening size. Door gaps should NOT be included in these dimensions above. Max door size is double door opening 8'0" x 8'0".

Distance Between Centerline of Crash Bar to Bottom of Door: ☐ 37" ☐ 42" ☐ Other: _____

Meets California Building Code (2019) Sec.11B-309.4²: ☐ Yes ☐ No (default)

Finish Options¹ (For both Panic Device and Mating Pull):

☐ US32/629 ☐ US32D/630 ☐ US32D316 ☐ US32316 ☐ US32DMS
☐ US32D/US32 (Push) ☐ 314E ☐ BSP ☐ FBPC
☐ WSP ☐ 4E ☐ 10BE ☐ Stock Powder Coats (specify): _____

Engraved "PUSH" Area Finish Options:



☐ Black Paint ☐ White Paint ☐ Less Paint (32 and powder coat only) ☐ Custom Color (specify): _____

¹Powder Coat options may not be tested to BHMA finish standards.

²This product was specifically designed to be used in the state of California or other areas where a 5lb. activation force is required to meet ADA.
 For other geographies, we recommend using our standard PDU8500.

The ASSA ABLOY Group is the global leader in access solutions. Every day we help people feel safe, secure and experience a more open world.

Mating Pull for Exterior Side:

- 0-No Mating Pull 
- 1-Full Height L Shape 
- 2-Half Height L Shape 
- 3-Full Height Straight
Bottom of Ext Pull:
○ Full Height
○ _____" up from bottom of door* 
- 4-Half Height Straight 
- 5-Short Centered Straight
Exterior Pull Length:
○ Standard (19 1/4")
○ Custom Length _____" (Minimum is 19 1/4") 
- 5-Extended**
Exterior Pull Length: _____"
_____ " from top of door to top of pull 
- 6-Horizontal Straight 

**5 - Extended, the mating pull will extend below the crash bar - requires additional bottom post.

- ☐ **Custom RM Mating Pull Option** (provide RM part number): _____
Custom RM Mating Pull must be completely stainless steel based.

*Minimum of 10" clearance from the floor on the mating pull side to prevent interference with wheelchairs and other mobility devices.

Cylinder Options:

- 01 - Mortise Cylinder
- 02 - 7-pin SFIC housing w/plastic core
- 03 - Special Order (keyed alike)
- 04 - Customer Sending Cylinder to Factory
- 05 - Dummy Cylinder Housing
- 06 - Non-Keyed Function
- Length of Cylinder: _____
- 09 - 7 pin SFIC w/ACCENTRA Core (standard)
- (Only available on No Mating Pull and Horizontal Straight Mating Pull options. Blank Escutcheon Plate provided)
- *10 - Customer Swapping in Field

*Cylinder rings will be provided for cylinder lengths up to 1 5/8". If cylinder length is greater than 1 5/8", please contact factory.

Dogging Feature: Dogging not allowed on fire rated panic

Strike Options (Check all that apply. See website for strike templates):

- Manual
- 1600 Electric
- LM - Lock Monitor (Optional on 1600)

WARNING: Be advised that use of unauthorized non-ASSA ABLOY products or parts such as strikes in conjunction with this product and/or installation outside UL10C guidelines will void the warranty and any manufacturer owned liability, as well as decertify to UL305 and ANSI156.3 compliance.

- Strike Finish Options:**
- US32/629
 - US32D/630
 - US32D316
 - US32316
 - US32DMS
 - 314E
 - BSP
 - FBPC
 - WSP
 - 4E
 - 10BE
 - Stock Powder Coats (specify): _____

Your signature indicates the information contained on this order form is accurate and ready to be manufactured.

(customer signature)

(date)

NOTE: Top door gap range is 1/8" - 1/4".

NOTE: Device is not to be used with coordinator.

Rockwood Manufacturing Company
300 Main St.
Rockwood, PA 15557
www.rockwoodmfg.com
1 800 458 2424

Rockwood is a brand associated with ASSA ABLOY Accessories and Door Controls Group, Inc.
Copyright © 2020-2026, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited. Printed in the U.S.A.