



Features:

- . European AC input (200-240VAC).
- . Built-in active PFC function.
- . IP20.
- . Suitable for dry environment.
- . Protections: Short circuit / Over temperature / Over voltage.
- . Adopt plastic case and internal glue potting.
- . Built-in lightning protection device, can meet the difference mode 1kV.
- . Comply with the world lighting equipment safety standards.
- . 5 years warranty.



Description:

SNP250 series is an indoor constant voltage LED driver with an input voltage range of 180-264Vac, whose efficiency is up to 94%, it's working in the temperature range of - 20 ° C to + 45° C under free air convection. It has a high power factor, ultra-low total harmonic distortion, low standby power consumption, lightning protection and other comprehensive protection functions, which not only greatly improves the reliability of the product, but also guarantees the product life cycle. This series is designed for LED lighting and is used in indoor lighting applications. They are suitable for a wide range of applications in almost all kinds of environments where LED luminaires can be installed. The product designed completely in accordance with world's lighting equipment safety regulations to ensure the safety of both user and luminaire system during installation.

Model:

Model	Output voltage	Output current	Max. Output power	Output voltage precision	Total harmonic distortion (Typ.)	Power factor (Typ.)	Efficiency (Typ.)
SNP250-12VL-1	12V	0-18A	216W	±5%	13%	0.97	93%
SNP250-24VL-1	24V	0-10.4A	250W	±5%	13%	0.97	94%

Remark: All the parameters are measured at 230VAC input, full load and 25 °C of ambient temperature if they are not specially mentioned.


Input:

Parameter	Min. value	Typical value	Max. value	Note
Rated input voltage	200 Vac		240Vac	Derating curve is shown in figure
Input voltage	180Vac		264Vac	
Input frequency	47Hz		63Hz	
Max. Input current			1.4A	
Input inrush current			90A	230Vac/50Hz, Cold Start
Power factor	0.95	0.97		230Vac, Full Load
Total harmonic input		13%	15%	230Vac, Full Load
Leakage current			0.7mA	230Vac/50Hz, Full Load
Stand-by power consumption		0.4W	0.5W	230Vac/50Hz, No Load

Output:

Parameter	SNP250-12VL-1	SNP250-24VL-1	Note
Output voltage	12VDC	24VDC	
Rated output current	18A	10.4A	
Output current	0-18A	0-10.4A	
Rated output power	216W	250W	
Rated output efficiency	93%	94%	230Vac
Output voltage precision	±5%		
Output voltage ripple (PK-PK)	±3%		Full load (Test under 20M bandwidth)
Output current ripple (PK-PK)	---		Full load (Test under 20M bandwidth)
Rise time	100mS		230Vac
Startup time	300mS		230Vac
Line regulation	±1%		full load
Load regulation	±1%		

Characteristic Curve:



Protection:

Parameter		Conditions	Note
Protection	Over load	1.1-1.6 times rated load	Auto-recovery after overload removed.
	Short circuit	Short circuit power \leq 0.5W	Hiccup mode, auto-recovery after short circuit removed.
	Over voltage	1.5 times of rated output voltage	Turn off the input voltage and recover after restart.
	Over temperature	110 °C	Turn off the input voltage, the temperature can be restored after return to normal.

Environment Requirement:

Parameter	Min.	Typ.	Max.	Note
Working temp.	-20 °C	25 °C	+45 °C	See Fig.1
Storage temp.	-40 °C	25 °C	+85 °C	
Working humidity	10%RH		90%RH	
Storage humidity	5%RH		95%RH	
IP grade			IP20	
Cooling mode	Natural cooling			

Safety&EMC standard:

Certificate	Safety standards	Certification	Note
UL/CUL	---		
TUV	EN61347-1:2015 EN 61347-2-13:2014+A1 EN62493:2015	√	
SAA	AS/NZS 61347.2.13		
CCC	---		
CE	EN 61347-2-13:2014 +A1 EN61347-1:2015	√	

Indoor LED Power Supply

Safety test		Qualification	Note
Dielectric compressive strength	Input to output	3750Vac/5mA Max/60s	Reinforced insulation, no breakdown, no flashover
	Primary to ground	---	Basic insulation, no breakdown, no flashover
	Secondary to ground	---	Functional insulation, no breakdown, no flashover
Insulation resistance	Input to output	≥10MΩ	Test voltage : 500Vdc
Grounding resistance		---	25A/1min
Leakage current		≤0.75mA	264Vac
EMI/EMS item		Standard/Level	Data
Conduction CE		EN55015	
Radiation RE		EN55015	
Harmonics		EN IEC 61000-3-2	Class C

Others:

Parameters	Condition	note
Lifetime	30,000 hours	230Vac, full load, case Temp. 75°C
MTBF	200,000 hours	230Vac, full load, environment Temp. 25°C (MIL-HDBK-217F)
TC	90°C	
Warranty	5 years	
Weight	g	
Dimensions	195mm * 67.1mm * 31.2mm	L x W x H

Indoor LED Power Supply

Mechanical Specification (Unit : mm)

