

**Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))
SOLUWAX**

Regulation (EU) n. 2020/878

Safety Data Sheet date: 18/10/2023, version 9

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Trade name: SOLUWAX
SDS code: P43074
UFI: C0D5-J4XJ-P04W-TWE7

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use:

Cleaner

Industrial uses

Uses advised against:

No uses advised against are identified.

1.3. Details of the supplier of the safety data sheet**Manufacturers:**

Socomore SASU

Zone Industrielle du Prat - CS 23707 - 56037 VANNES CEDEX - France

Tel : +33 (0)2 97 43 76 83 - Fax : +33 (0)2 97 54 50 26

Socomore Ireland Ltd. - Meenane, Watergrasshill, Co. Cork, Ireland - Tel +353 21 4889922 / Fax +353 21 4889923 / ireland@socomore.com

Distributors:

Socomore SASU

Zone Industrielle du Prat - CS 23707 - 56037 VANNES CEDEX - France

Tel : +33 (0)2 97 43 76 83 - Fax : +33 (0)2 97 54 50 26

Socomore Ireland Ltd. - Meenane, Watergrasshill, Co. Cork, Ireland - Tel +353 21 4889922 / Fax +353 21 4889923 / ireland@socomore.com

Competent person responsible for the safety data sheet:

techdirsocomore@socomore.com

1.4. Emergency telephone number

France : ORFILA (INRS) +33 (0)1 45 42 59 59

International : CHEMTEL +1-813-248-0585.

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****EC regulation criteria 1272/2008 (CLP)**

⚠ Danger, Skin Corr. 1A, Causes severe skin burns and eye damage.

⚠ Danger, Eye Dam. 1, Causes serious eye damage.

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Hazard pictograms:

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

SOLUWAX



Danger

Hazard statements:

H314 Causes severe skin burns and eye damage.

Precautionary statements:

P280 Wear protective gloves/clothing and eye/face protection.

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor/...

P501 Dispose of contents/container in accordance with applicable regulations.

Special Provisions:

None

Contains

ISOTRIDECANOL, ETHOXYLATED (2-5 OE)

ISOTRIDECANOL ETHOXYLATED (5-20 OE)

Decyl D-glucoside

C8 Alkyl glucoside

Special provisions according to Annex XVII of REACH and subsequent amendments:

None

2.3. Other hazards

No PBT, vPvB or endocrine disruptor substances present in concentration $\geq 0.1\%$

SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:

stta	Name	Ident. Number	Classification
$\geq 5\%$ - $< 7\%$	ISOTRIDECANOL, ETHOXYLATED (2-5 OE)	CAS: 69011-36-5 EC: 500-241-6 REACH No.: 01- 2119976362 -32	◊ 3.1/4/Oral Acute Tox. 4 H302 ◊ 3.3/1 Eye Dam. 1 H318 4.1/C3 Aquatic Chronic 3 H412
$\geq 3\%$ - $< 5\%$	ISOTRIDECANOL ETHOXYLATED (5-20)	CAS: 69011-36-5	◊ 3.1/4/Oral Acute Tox. 4 H302

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

SOLUWAX

	OE)	EC: 500-241-6 REACH No.: 01-2119976362-32	⚠ 3.3/1 Eye Dam. 1 H318 Acute Toxicity Estimate: ATE - Oral 555,56 mg/kg bw
>= 1% - < 3%	SILICIC ACID, POTASSIUM SALT	CAS: 1312-76-1 EC: 215-199-1 REACH No.: 01-2119456888-17	⚠ 3.2/2 Skin Irrit. 2 H315 ⚠ 3.8/3 STOT SE 3 H335 ⚠ 3.3/2 Eye Irrit. 2 H319
>= 1% - < 3%	Decyl D-glucoside	CAS: 54549-25-6 EC: 259-218-1 REACH No.: 01-2119489418-23	⚠ 3.2/2 Skin Irrit. 2 H315 ⚠ 3.3/1 Eye Dam. 1 H318
>= 1% - < 3%	C8 Alkyl glucoside	EC: 414-420-0 REACH No.: 01-0000016147-72	⚠ 3.3/1 Eye Dam. 1 H318
>= 1% - < 3%	POTASSIUM 3,5,5- TRIMETHYLHEXANOATE	CAS: 93918-10-6 EC: 299-890-3 REACH No.: Exempted----	⚠ 3.3/2 Eye Irrit. 2 H319 ⚠ 3.2/2 Skin Irrit. 2 H315
>= 1% - < 3%	potassium hydroxide; caustic potash	Index number: 019-002-00-8 CAS: 1310-58-3 EC: 215-181-3 REACH No.: 01-2119487136-33	⚠ 2.16/1 Met. Corr. 1 H290 ⚠ 3.2/1A Skin Corr. 1A H314 ⚠ 3.1/4/Oral Acute Tox. 4 H302 Specific Concentration Limits: C >= 5%: Skin Corr. 1A H314 2% <= C < 5%: Skin Corr. 1B H314 0,5% <= C < 2%: Skin Irrit. 2 H315 0,5% <= C < 2%: Eye Irrit. 2 H319

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

OBTAIN IMMEDIATE MEDICAL ATTENTION.

Remove contaminated clothing immediately and dispose of safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

**Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))
SOLUWAX**

Protect uninjured eye.

In case of Ingestion:

Do NOT induce vomiting.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

None

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

No particular treatment.

SECTION 5: Firefighting measures**5.1. Extinguishing media**

Suitable extinguishing media:

Water.

Carbon dioxide (CO₂).

Extinguishing media which must not be used for safety reasons:

None in particular.

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

5.3. Advice for firefighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Wear personal protection equipment.

Remove persons to safety.

See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

6.3. Methods and material for containment and cleaning up

Wash with plenty of water.

6.4. Reference to other sections

See also section 8 and 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Avoid contact with skin and eyes, inhalation of vapours and mists.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

SOLUWAX

the containers.

See also section 8 for recommended protective equipment.

Advice on general occupational hygiene:

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

7.2. Conditions for safe storage, including any incompatibilities

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

7.3. Specific end use(s)

None in particular

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values

SILICIC ACID, POTASSIUM SALT - CAS: 1312-76-1

- OEL Type: TWA - STEL: 2 mg/m³ - Notes: 15 min

potassium hydroxide; caustic potash - CAS: 1310-58-3

- OEL Type: Ontario - STEL: 2 mg/m³ - Notes: Canada

- OEL Type: British Columbia - STEL: 2 mg/m³ - Notes: Canada

- OEL Type: Alberta - STEL: 2 mg/m³ - Notes: Canada

- OEL Type: Québec - STEL: 2 mg/m³ - Notes: Canada

- OEL Type: ACGIH - STEL: Ceiling 2 mg/m³ - Notes: URT, eye, and skin irr

- OEL Type: National - STEL: 2 mg/m³ - Notes: France

- OEL Type: National - STEL: 2 mg/m³ - Notes: Spain

DNEL Exposure Limit Values

SILICIC ACID, POTASSIUM SALT - CAS: 1312-76-1

Worker Professional: 5.61 mg/m³ - Consumer: 1.38 mg/m³ - Exposure: Human Inhalation

- Frequency: Long Term, systemic effects

Worker Professional: 1.49 mg/kg b.w./day - Consumer: 0.74 mg/kg b.w./day - Exposure:

Human Dermal - Frequency: Long Term, local effects

Consumer: 0.74 mg/kg - Exposure: Human Oral

Decyl D-glucoside - CAS: 54549-25-6

Worker Industry: 420 mg/m³ - Consumer: 124 mg/m³ - Exposure: Human Inhalation -

Frequency: Long Term, systemic effects

Worker Industry: 595000 mg/kg b.w./day - Consumer: 357000 mg/kg b.w./day - Exposure:

Human Dermal - Frequency: Long Term, systemic effects

Consumer: 35.7 mg/cm² - Exposure: Human Oral - Frequency: Long Term, systemic effects

potassium hydroxide; caustic potash - CAS: 1310-58-3

Worker Industry: 1 mg/m³ - Consumer: 1 mg/m³ - Exposure: Human Inhalation -

Frequency: Long Term (repeated)

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

SOLUWAX

PNEC Exposure Limit Values

SILICIC ACID, POTASSIUM SALT - CAS: 1312-76-1

Target: Fresh Water - Value: 7.5 mg/l

Target: Marine water - Value: 1 mg/l

Target: Microorganisms in sewage treatments - Value: 348 mg/l

Target: PNEC intermittent - Value: 7.5 mg/l

Decyl D-glucoside - CAS: 54549-25-6

Target: Fresh Water - Value: 0.175 mg/l

Target: Marine water - Value: 0.018 mg/l

Target: Freshwater sediments - Value: 1.516 mg/kg dw

Target: Marine water sediments - Value: 0.065 mg/kg dw

Target: Sewage treatment plant - Value: 5000 mg/l

Target: Soil - Value: 0.654 mg/kg dw

Biological Exposure Index

N.A.

8.2. Exposure controls

See below, example of PPE to use.

Eye protection:

Safety goggles (EN 166)

Face protection shield. (EN 166)

Use closed fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Boots (NF EN13832-3)

Protection for hands:

Suitable gloves type: NF EN374

NR (natural rubber, natural latex).

PVC (polyvinyl chloride).

Butyl rubber (isobutylene-isoprene copolymer)

NBR (nitrile rubber).

PVA (Polyvinyl alcohol).

Respiratory protection:

Not needed for normal use.

Thermal Hazards:

None

Environmental exposure controls:

None

Appropriate engineering controls:

None

Other conditions affecting workers exposure:

None

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Method:	Notes
Physical state:	Liquid	--	--
Colour:	Light yellow	--	--

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))
SOLUWAX

Odour:	N.A.	--	--
Melting point/freezing point:	Not Relevant	--	--
Boiling point or initial boiling point and boiling range:	100 ?C	--	--
Flammability:	N.A.	--	--
Lower and upper explosion limit:	N.A.	--	--
Flash point (°C):	N.A.	--	--
Auto-ignition temperature:	N.A.	--	--
Decomposition temperature:	N.A.	--	--
pH:	12.6	--	--
Kinematic viscosity:	N.A.	--	--
Solubility in water:	N.A.	--	--
Solubility in oil:	N.A.	--	--
Partition coefficient n-octanol/water (log value):	N.A.	--	--
Vapour pressure:	N.A.	--	--
Density and/or relative density:	1.07	--	--
Relative vapour density:	N.A.	--	--
Particle characteristics:			
Particle size:	N.A.	--	--

9.2. Other information

No other relevant information

Volatile Organic compounds - VOCs = 0 %

Volatile Organic compounds - VOCs = 0 g/l

N.A. = not available

**Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))
SOLUWAX****SECTION 10: Stability and reactivity****10.1. Reactivity**

Stable under normal conditions

10.2. Chemical stability

Stable under normal conditions

10.3. Possibility of hazardous reactions

None

10.4. Conditions to avoid

Stable under normal conditions.

10.5. Incompatible materials

None in particular.

10.6. Hazardous decomposition products

None.

SECTION 11: Toxicological information**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**

Toxicological information of the product:

SOLUWAX

Acute toxicity:

ATEmix - Oral 5208,48 mg/kg bw

Toxicological information of the main substances found in the product:

ISOTRIDECANOL, ETHOXYLATED (2-5 OE) - CAS: 69011-36-5

Acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 300 mg/kg

Test: LD50 - Route: Oral - Species: Rat < 2000 mg/kg - Source: OECD 423

Test: LD50 - Route: Skin - Species: Rat > 2000 mg/kg - Source: OECD 402

Carcinogenicity:

Test: NOAEL > 250 mg/kg bw/day

Reproductive toxicity:

Test: NOAEL > 250 mg/kg bw/day

STOT-repeated exposure:

Route: Oral - Species: Rat = 50 mg/kg bw/day - Duration: 2 years

ISOTRIDECANOL ETHOXYLATED (5-20 OE) - CAS: 69011-36-5

Acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 300 mg/kg - Source: OECD 423

ATE - Oral 555,56 mg/kg bw

Test: LD50 - Route: Oral - Species: Rat <= 2000 mg/kg - Source: OECD 423

ATE - Oral 555,56 mg/kg bw

Test: LD50 - Route: Skin - Species: Rat > 2000 mg/kg - Source: OECD 402

ATE - Oral 555,56 mg/kg bw

Reproductive toxicity:

Test: NOAEL - Route: Oral - Species: Rat > 250 mg/kg bw/day

Test: NOAEL - Route: Oral - Species: Rat > 50 mg/kg bw/day

STOT-repeated exposure:

Test: NOAEL - Route: Oral - Species: Rat = 50 mg/kg

**Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))
SOLUWAX**

SILICIC ACID, POTASSIUM SALT - CAS: 1312-76-1

Acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 2000 mg/kg

Skin corrosion/irritation:

Test: LD50 - Route: Skin - Species: Rat > 5000 mg/kg

Respiratory or skin sensitisation:

Test: LC50 - Route: Inhalation - Species: Rat > 2.06 g/m³

STOT-repeated exposure:

Test: NOAEL - Route: Oral - Species: Rat = 159 mg/kg bw/day

Decyl D-glucoside - CAS: 54549-25-6

Acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 5000 mg/kg - Source: OECD, 401

C8 Alkyl glucoside

Acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 2000 mg/kg - Source: Directive 67/548/CEE, Annexe V, B.1.

Test: LD50 - Route: Oral - Species: Rat ≤ 5000 mg/kg - Source: Directive 67/548/CEE, Annexe V, B.1.

Test: LD50 - Route: Skin - Species: Rat > 5000 mg/kg - Source: Directive 67/548/CEE, Annexe V, B.3.

potassium hydroxide; caustic potash - CAS: 1310-58-3

Acute toxicity:

Test: LD50 - Route: Oral - Species: Rat = 273 mg/kg

If not differently specified, the information required in Regulation (EU)2020/878 listed below must be considered as N.A.:

Acute toxicity;

Skin corrosion/irritation;

Serious eye damage/irritation;

Respiratory or skin sensitisation;

Germ cell mutagenicity;

Carcinogenicity;

Reproductive toxicity;

STOT-single exposure;

STOT-repeated exposure;

Aspiration hazard.

11.2. Information on other hazards

Endocrine disrupting properties:

No endocrine disruptor substances present in concentration ≥ 0.1%

Other toxicological information:

ISOTRIDEKANOL, ETHOXYLATED (2-5 OE)

Eye irritation:

Severe eye damage

-

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))
SOLUWAX

ISOTRIDECANOL ETHOXYLATED (5-20 OE)

Eye contact:

Severe eye damage

-

SILICIC ACID, POTASSIUM SALT

Irritating to eyes and skin.

-

Decyl D-glucoside

Skin corrosion/skin irritation:

Irritating to skin.

Eye damage / eye irritation:

Risk of serious eye damage

-

C8 Alkyl glucoside

Eye damage / eye irritation:

Risk of serious eye damage

-

potassium hydroxide; caustic potash

Harmful if swallowed

Corrosive, causes severe burns

Risk of serious eye damage

Irritating to skin.

Irritating to respiratory tracts

SECTION 12: Ecological information**12.1. Toxicity**

Adopt good working practices, so that the product is not released into the environment.

ISOTRIDECANOL, ETHOXYLATED (2-5 OE) - CAS: 69011-36-5

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish > 1 mg/l - Duration h: 96 - Notes: Leuciscus idus (Fish test acute, static)

Endpoint: LC50 - Species: Fish < 10 mg/l - Duration h: 96 - Notes: Leuciscus idus (Fish test acute, static)

Endpoint: EC50 - Species: Daphnia > 1 mg/l - Duration h: 48 - Notes: Daphnia magna (Daphnia test acute)

Endpoint: EC50 - Species: Daphnia < 10 mg/l - Duration h: 48 - Notes: Daphnia magna (Daphnia test acute)

Endpoint: EC50 - Species: Aquatic plants > 1 mg/l - Duration h: 72 - Notes: Scenedesmus sp. (DIN 38412 Part 9)

Endpoint: EC50 - Species: Aquatic plants < 10 mg/l - Duration h: 72 - Notes: Scenedesmus sp.

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

SOLUWAX

(DIN 38412 Part 9)

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Daphnia = 0.37 mg/l - Duration h: 504 - Notes: DAPHNIA MAGNA

c) Bacteria toxicity:

Endpoint: EC50 - Species: bacteria = 140 mg/l

d) Terrestrial toxicity:

Endpoint: NOEC = 10 mg/kg - Notes: Lepidium sativum

ISOTRIDECANOL ETHOXYLATED (5-20 OE) - CAS: 69011-36-5

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Algae > 1 mg/l - Duration h: 72 - Notes: Desmodesmus subspicatus

Endpoint: EC50 - Species: Daphnia > 1 mg/l - Duration h: 48 - Notes: Daphnia magna

Endpoint: LC50 - Species: Fish > 1 mg/l - Duration h: 96 - Notes: Cyprinus carpio

Endpoint: EC10 - Species: Daphnia = 2.6 mg/l - Duration h: 504 - Notes: Daphnia magna

Endpoint: EC10 - Species: Algae > 1 mg/l - Duration h: 72 - Notes: Desmodesmus subspicatus

c) Bacteria toxicity:

Endpoint: EC50 - Species: bacteria = 140 mg/l

f) Effects in sewage plants:

Endpoint: NOEC = 220 mg/kg

SILICIC ACID, POTASSIUM SALT - CAS: 1312-76-1

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish > 146 mg/l - Duration h: 48 - Notes: Leuciscus idus

Endpoint: EC50 - Species: Daphnia > 146 mg/l - Duration h: 24 - Notes: Daphnia magna

Decyl D-glucoside - CAS: 54549-25-6

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish > 1 mg/l - Duration h: 96 - Notes: Danio rerio / OECD, 203

Endpoint: LC50 - Species: Fish <= 10 mg/l - Duration h: 96 - Notes: Danio rerio / OECD, 203

Endpoint: EC50 - Species: Aquatic invertebrates > 1 mg/l - Duration h: 48 - Notes: Daphnia magna / OECD, 202

Endpoint: EC50 - Species: Aquatic invertebrates <= 10 mg/l - Duration h: 48 - Notes: Daphnia magna / OECD, 202

Endpoint: EC50 - Species: Algae > 1 mg/l - Duration h: 72 - Notes: Skeletonema costatum / ISO 10253

Endpoint: EC50 - Species: Algae <= 10 mg/l - Duration h: 72 - Notes: Skeletonema costatum / ISO 10253

Endpoint: NOEC - Species: Algae > 1 mg/l - Duration h: 72 - Notes: Skeletonema costatum / ISO 10253

Endpoint: NOEC - Species: Algae <= 10 mg/l - Duration h: 72 - Notes: Skeletonema costatum / ISO 10253

Endpoint: NOEC - Species: Aquatic invertebrates > 1 mg/l - Duration h: 72 - Notes: Daphnia magna / OECD, 202

Endpoint: NOEC - Species: Aquatic invertebrates <= 10 mg/l - Duration h: 72 - Notes: Daphnia magna / OECD, 202

C8 Alkyl glucoside

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish > 310 mg/l - Duration h: 96 - Notes: Oncorhynchus mykiss

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

SOLUWAX

Endpoint: EC50 - Species: Aquatic invertebrates > 100 mg/l - Duration h: 48 - Notes: Daphnia magna

Endpoint: EC50 - Species: Algae > 100 mg/l - Duration h: 72 - Notes: Selenastrum capricornutum potassium hydroxide; caustic potash - CAS: 1310-58-3

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Daphnia = 270 mg/l - Duration h: 24

Endpoint: LC50 - Species: Fish = 44 mg/l - Duration h: 24 - Notes: Gambusia affinis, Poescilidae

12.2. Persistence and degradability

ISOTRIDEKANOL, ETHOXYLATED (2-5 OE) - CAS: 69011-36-5

Biodegradability: Readily biodegradable - Test: OECD 301B - Duration: 28 days - %: > 60 - Notes: Aerobic

Biodegradability: Biodegradable - Test: OECD 311 - Duration: 60 days - %: > 60 - Notes: Anaerobic

ISOTRIDEKANOL ETHOXYLATED (5-20 OE) - CAS: 69011-36-5

Biodegradability: Readily biodegradable - Test: OECD 301B - Duration: 28 days - %: >60% - Notes: aerobic

Biodegradability: Readily biodegradable - Test: OECD 310 - Duration: 60 days - %: >60% - Notes: anaerobic

Biodegradability: Chemical Oxygen Demand (COD) - Notes: 2100 mg/g

Decyl D-glucoside - CAS: 54549-25-6

Biodegradability: Readily biodegradable - Test: OECD 301D

C8 Alkyl glucoside

Biodegradability: Readily biodegradable - Test: OECD 301D

12.3. Bioaccumulative potential

ISOTRIDEKANOL, ETHOXYLATED (2-5 OE) - CAS: 69011-36-5

Low bioconcentration potential

12.4. Mobility in soil

ISOTRIDEKANOL, ETHOXYLATED (2-5 OE) - CAS: 69011-36-5

High adsorption on soils

Log Koc > 5000 - Notes: QSAR

ISOTRIDEKANOL ETHOXYLATED (5-20 OE) - CAS: 69011-36-5

Log Koc > 5000

High adsorption on soils

12.5. Results of PBT and vPvB assessment

vPvB Substances: None - PBT Substances: None

12.6. Endocrine disrupting properties

No endocrine disruptor substances present in concentration $\geq 0.1\%$

12.7. Other adverse effects

No harmful effects expected.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

Codes of wastes (Décision 2001/573/EC, Directive 2006/12/EEC, Directive 94/31/EEC on hazardous waste):

06 02 99 wastes not otherwise specified

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))
SOLUWAX

SECTION 14: Transport information



14.1. UN number or ID number

ADR-UN Number: 1760
 IATA-UN Number: 1760
 IMDG-UN Number: 1760

14.2. UN proper shipping name

ADR-Shipping Name: CORROSIVE LIQUID, N.O.S. (POTASSIUM HYDROXIDE)
 IATA-Shipping Name: CORROSIVE LIQUID, N.O.S. (POTASSIUM HYDROXIDE)
 IMDG-Shipping Name: CORROSIVE LIQUID, N.O.S. (POTASSIUM HYDROXIDE)

14.3. Transport hazard class(es)

ADR-Class: 8
 ADR - Hazard identification number: 80
 IATA-Class: 8
 IATA-Label: 8
 IMDG-Class: 8

14.4. Packing group

ADR-Packing Group: II
 IATA-Packing group: II
 IMDG-Packing group: II

14.5. Environmental hazards

ADR-Environmental Pollutant: No
 IMDG-Marine pollutant: No
 IMDG-EmS: F-A , S-B

14.6. Special precautions for user

ADR-Subsidiary hazards: -
 ADR-S.P.: 274
 ADR-Transport category (Tunnel restriction code): 2 (E)
 IATA-Passenger Aircraft: 851
 IATA-Subsidiary hazards: -
 IATA-Cargo Aircraft: 855
 IATA-S.P.: A3 A803
 IATA-ERG: 8L
 IMDG-Subsidiary hazards: -
 IMDG-Stowage and handling: Category B SW2
 IMDG-Segregation: -
 Q.L.: 1L
 Q.E.: E2

14.7. Maritime transport in bulk according to IMO instruments

N.A.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))
SOLUWAX**

Dir. 98/24/EC (Risks related to chemical agents at work)
Dir. 2000/39/EC (Occupational exposure limit values)
Regulation (EC) n. 1907/2006 (REACH)
Regulation (EC) n. 1272/2008 (CLP)
Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013
Regulation (EU) n. 286/2011 (ATP 2 CLP)
Regulation (EU) n. 618/2012 (ATP 3 CLP)
Regulation (EU) n. 487/2013 (ATP 4 CLP)
Regulation (EU) n. 944/2013 (ATP 5 CLP)
Regulation (EU) n. 605/2014 (ATP 6 CLP)
Regulation (EU) n. 2015/1221 (ATP 7 CLP)
Regulation (EU) n. 2016/918 (ATP 8 CLP)
Regulation (EU) n. 2016/1179 (ATP 9 CLP)
Regulation (EU) n. 2017/776 (ATP 10 CLP)
Regulation (EU) n. 2018/669 (ATP 11 CLP)
Regulation (EU) n. 2018/1480 (ATP 13 CLP)
Regulation (EU) n. 2019/521 (ATP 12 CLP)
Regulation (EU) n. 2020/217 (ATP 14 CLP)
Regulation (EU) n. 2020/1182 (ATP 15 CLP)
Regulation (EU) n. 2021/643 (ATP 16 CLP)
Regulation (EU) n. 2021/849 (ATP 17 CLP)
Regulation (EU) n. 2022/692 (ATP 18 CLP)

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product:

Restriction 3

Restrictions related to the substances contained:

Restriction 75

Listed or in compliance with the following international inventories:

N.A.

Labelling of detergents (EC Regulations 648/2004 and 907/2006):

SOLUWAX

anionic surface active agents < 5%

non-ionic surface active agents >= 15% - < 30%

Labelling of biocides (Regulations 1896/2000, 1687/2002, 2032/2003, 1048/2005, 1849/2006, 1451/2007 and Directive 98/8/EC):

N.A.

N.A.

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

SOLUWAX

Where applicable, refer to the following regulatory provisions :

Directive 2003/105/CE ('Activities linked to risks of serious accidents') and subsequent amendments.

1999/13/EC (VOC directive)

Dir. 2004/42/EC (VOC directive)

Provisions related to directive EU 2012/18 (Seveso III):

Seveso III category according to Annex 1, part 1

None

15.2. Chemical safety assessment

No

SECTION 16: Other information

N.A.: Not Applicable or Not Available

Full text of phrases referred to in Section 3:

H302 Harmful if swallowed.

H318 Causes serious eye damage.

H412 Harmful to aquatic life with long lasting effects.

H315 Causes skin irritation.

H335 May cause respiratory irritation.

H319 Causes serious eye irritation.

H290 May be corrosive to metals.

H314 Causes severe skin burns and eye damage.

Hazard class and hazard category	Code	Description
Met. Corr. 1	2.16/1	Substance or mixture corrosive to metals, Category 1
Acute Tox. 4	3.1/4/Oral	Acute toxicity (oral), Category 4
Skin Corr. 1A	3.2/1A	Skin corrosion, Category 1A
Skin Corr. 1B	3.2/1B	Skin corrosion, Category 1B
Skin Irrit. 2	3.2/2	Skin irritation, Category 2
Eye Dam. 1	3.3/1	Serious eye damage, Category 1
Eye Irrit. 2	3.3/2	Eye irritation, Category 2

Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))

SOLUWAX

STOT SE 3	3.8/3	Specific target organ toxicity - single exposure, Category 3
Aquatic Chronic 3	4.1/C3	Chronic (long term) aquatic hazard, category 3

This safety data sheet has been completely updated in compliance to Regulation 2020/878. Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Classification according to Regulation (EC) Nr. 1272/2008	Classification procedure
Skin Corr. 1A, H314	Calculation method
Eye Dam. 1, H318	Calculation method

This document was prepared by a competent person who has received appropriate training.
Main bibliographic sources:

- ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities
- SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold
- CCNL - Appendix 1
- Insert further consulted bibliography

Important confidentiality : this document contains confidential information that is proprietary to SOCOMORE. Subject to legal provisions determining otherwise, the distribution, republication or re-transmission of this document, in full or in part, must be limited to clearly identified individuals, either because they use the product, or to provide HSE information. Any communication of this document outside of this framework without our written consent is strictly forbidden.

SOCOMORE strongly advises every recipient of this safety data sheet to read it carefully and to consult experts in the field if necessary or appropriate, in order to understand the information it contains, notably the possible dangers associated with this product. The users must ensure the conformity and completeness of this information with regards to their specific use of the product.

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. It is the responsibility of the purchaser/user to ensure that their activities conform with current legislation in force.

The information is considered correct, but it is not exhaustive and it shall be used only as a guide which is based on the current knowledge of the substance or mixture and it is applicable to the safety precautions appropriate for the product.

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

**Safety Data Sheet (Regulation (EC) n. 1907/2006 (REACH))
SOLUWAX**

ATE:	Acute Toxicity Estimate
ATEmix:	Acute toxicity Estimate (Mixtures)
CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GefStoffVO:	Ordinance on Hazardous Substances, Germany.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
LTE:	Long-term exposure.
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STE:	Short-term exposure.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
STOT SE:	May cause drowsiness or dizziness
TLV:	Threshold Limiting Value.
TWA:	Time-weighted average
TWATLV:	Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).
WGK:	German Water Hazard Class.