Safety Data Sheet date: 26/1/2021, version 1

1. Identification

GHS Product Identifier

Mixture identification:

Trade name: SYNCLAIR A2 GEL

SDS code: P40460

Recommended use of the chemical and restrictions on use

Recommended use:

Cleaner

Industrial uses

Restrictions on use:

No uses advised against are identified.

Supplier's details

Manufacturers:

Socomore SASU

Zone Industrielle du Prat - CS 23707 - 56037 VANNES CEDEX - France

Tel: +33 (0)2 97 43 76 83 - Fax: +33 (0)2 97 54 50 26

Socomore Ireland Ltd. - Meenane, Watergrasshill, Co. Cork, Ireland - Tel +353 21 4889922 / Fax +353 21 4889923 / ireland@socomore.com

Distributors:

Surface Prep New Zealand Ltd, 301/6-8 Heather Street Parnell, Auckland 1052, NEW

ZEALAND, PH 021 455595 / john@sea2sky.co.nz

Competent person responsible for the safety data sheet:

techdirsocomore@socomore.com

Emergency phone number:

New Zealand emergency phone number: 0800 764 766 (0800 POISON)

2. Identification des dangers

Classification complies with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS Ed.7) and is consistent with ERMA New Zealand Approval number (HSNO) which is reported in Section 15.

Warning, Skin Irrit. 3, Causes mild skin irritation.

Warning, Eye Irrit. 2A, Causes serious eye irritation.

GHS label elements, including precautionary statements

Hazard pictograms:



Warning

Hazard statements:

H316 Causes mild skin irritation.

H319 Causes serious eye irritation.

Precautionary statements:

P264 Wash hands thoroughly after handling.

P280 Wear protective gloves and eye/face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P332+P313 If skin irritation occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

Special Provisions:

None

Other hazards which do not result in a classification

No other hazards

3. Composition/information on ingredients

Substances

N.A.

Mixtures

Hazardous components within the meaning of GHS and related classification:

Qty	Name	Ident. Number		Classification
>= 1% - < 3%	ISOTRIDECANOL, ETHOXYLATED (2-5 OE)	CAS: EC: REACH No.:	69011-36-5 500-241-6 01- 2119976362 -32	 \$\psi_3.2/2\$ Skin Irrit. 2 H315 \$\psi_3.3/1\$ Eye Dam. 1 H318 4.1/C3 Aquatic Chronic 3 H412
>= 0.5% - < 1%	2-AMINOETHANOL	CAS: EC:	141-43-5 205-483-3	2.6/4 Flam. Liq. 4 H227

4. First-aid measures

Description of necessary first-aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap.

Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediately and dispose of safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an opthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do not induce vomiting. Obtain a medical examination.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

Most important symptoms/effects, acute and delayed

None

Indication of immediate medical attention and special treatment needed, if necessary

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

No particular treatment.

5. Fire-fighting measures

Suitable extinguishing media

Water.

Carbon dioxide (CO2).

Unsuitable extinguishing media

None in particular.

Special hazards arising from the chemical

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

Hazardous combustion products:

None

Explosive properties: N.A.
Oxidizing properties: N.A.

Special protective actions for fire-fighters

Use suitable breathing apparatus.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove persons to safety.

See protective measures under point 7 and 8.

Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

Methods and material for containment and cleaning up

Wash with plenty of water.

7. Handling and storage

Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

See also section 8 for recommended protective equipment.

Advice on general occupational hygiene:

Contamined clothing should be changed before entering eating areas.

Do not eat or drink while working.

Conditions for safe storage, including any incompatibilities

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

8. Exposure controls/personal protection

Control parameters

2-AMINOETHANOL - CAS: 141-43-5

- OEL Type: National TWA(8h): 0.5 mg/m3 Notes: Germany- DFG, EU, Y, Sh, H, 11
- OEL Type: National TWA(8h): 2.5 mg/m3, 1 ppm STEL: 7.6 mg/m3, 3 ppm Notes: France VLEC TMP N° 49, 49 Bis
- OEL Type: EU TWA(8h): 2.5 mg/m3, 1 ppm STEL: 7.6 mg/m3, 3 ppm Notes: Skin
- OEL Type: ACGIH TWA(8h): 3 ppm STEL: 6 ppm Notes: Eye and skin irr
- OEL Type: National TWA(8h): 2.5 mg/m3, 0.98 ppm STEL: 7.6 mg/m3, 3 ppm -

Notes: Netherland

- OEL Type: National - TWA(8h): 2.5 mg/m3, 1 ppm - STEL: 7.6 mg/m3, 3 ppm - Notes: Belgium

- OEL Type: National - TWA(8h): 2.5 mg/m3, 1 ppm - STEL: 7.6 mg/m3, 3 ppm - Notes: UK

DNEL Exposure Limit Values

2-AMINOETHANOL - CAS: 141-43-5

Worker Industry: 1 mg/kg - Consumer: 0.24 mg/kg - Exposure: Human Dermal -

Frequency: Long Term, systemic effects

Worker Industry: 3.3 mg/m3 - Consumer: 2 mg/m3 - Exposure: Human Inhalation -

Frequency: Long Term, local effects

Consumer: 3.75 mg/kg - Exposure: Human Oral - Frequency: Long Term, local effects

PNEC Exposure Limit Values

2-AMINOETHANOL - CAS: 141-43-5

Target: Fresh Water - Value: 0.085 mg/l Target: Marine water - Value: 0.0085 mg/l

Target: Freshwater sediments - Value: 0.425 mg/l Target: Marine water sediments - Value: 0.0425 mg/l

Target: Microorganisms in sewage treatments - Value: 100 mg/l

Target: Soil (agricultural) - Value: 0.035 mg/kg Target: PNEC intermittent - Value: 0.025 mg/l

Appropriate engineering controls:

None

Individual protection measures, such as personal protective equipment (PPE) Eye protection:

Safety goggles (EN 166)

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

NR (natural rubber, natural latex).

NBR (nitrile rubber).

PVC (polyvinyl chloride).

PVA (Polyvinyl alcohol).

Butyl rubber (isobutylene-isoprene copolymer)

Respiratory protection:

Not needed for normal use.

Thermal Hazards:

None

9. Physical and chemical properties

Properties	Value	Method:	Notes
Appearance and colour:	Hazy colourless gel		
Odour:	N.A.		
pH:	11.4		

Kinematic viscosity	N.A.					
Melting point / freezing point:	Not Relevant					
Initial boiling point and boiling range:	100 °C					
Flammability	N.A.					
Flash point (°C):	N.A.					
Upper/lower flammability or explosive limits:	N.A.					
Vapour pressure:	17.5					
Vapour density:	0.675					
Relative density:	1.01					
Solubility in water:	N.A.					
Solubility in oil:	N.A.					
Partition coefficient (n-octanol/water):	N.A.					
Auto-ignition temperature:	573°C/1000°F					
Decomposition temperature:	N.A.					
Particle characteristics:						
Particle size (average and range)	N.A.					

10. Stability Toxicological information

Reactivity

Stable under normal conditions

Chemical stability

Stable under normal conditions

Possibility of hazardous reactions

None

Conditions to avoid

Stable under normal conditions.

Incompatible materials

None in particular.

Hazardous decomposition products

None.

11. Toxicological information

Information on toxicological effects Toxicological information of the product:

N.A

Toxicological information of the main substances found in the product:

ISOTRIDECANOL, ETHOXYLATED (2-5 OE) - CAS: 69011-36-5

Acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 2000 mg/kg Test: LD50 - Route: Skin - Species: Rabbit > 2000 mg/kg

Carcinogenicity:

Test: NOAEL > 250 MGKGBWDAY

Reproductive toxicity:

Test: NOAEL > 250 MGKGBWDAY

STOT-repeated exposure:

Route: Oral - Species: Rat = 50 MGKGBWDAY - Duration: 2 years

2-AMINOETHANOL - CAS: 141-43-5

Acute toxicity:

Test: LD50 - Route: Oral - Species: Rat = 1089 mg/kg
Test: LD50 - Route: Skin - Species: Rabbit > 1000 mg/kg
Test: LC50 - Route: Inhalation Dust > 1 mg/l - Duration: 4h

Reproductive toxicity:

Test: NOAEL - Species: Rat = 225 MGKGBWDAY - Notes: development Test: NOAEL - Species: Rat = 300 MGKGBWDAY - Notes: fertility

STOT-single exposure:

Test: C - Route: Inhalation Dust > 5 mg/l - Duration: 4h

STOT-repeated exposure:

Test: NOAEL - Route: Oral - Species: Rat = 300 mg/kg/d - Duration: > 75 days - Source: OECD 416, Experimental value - Notes: Effect: Body weight, weight of organs, consumption food

Test: NOAEC - Route: Inhalation - Species: Rat = 10 mg/m3 - Duration: 4 weeks (daily, 5 days/week) - Source: OECD 412, Experimental value - Notes: Effect: Lesions to the larynx, trachea and lungs

Test: NOEC - Route: Inhalation - Species: Rabbit = 150 mg/m3 - Duration: 4 weeks (daily, 5 days/week) - Source: OECD 412, Experiemental value - Notes: No adverse systemic effects

If not differently specified, the information listed below must be considered as non applicable:

Acute toxicity;

Skin corrosion/irritation;

Serious eye damage/irritation;

Respiratory or skin sensitisation;

Germ cell mutagenicity;

Carcinogenicity;

Reproductive toxicity;

STOT-single exposure;

STOT-repeated exposure;

Aspiration hazard.

12. Ecological information

Toxicity

Adopt good working practices, so that the product is not released into the environment.

ISOTRIDECANOL, ETHOXYLATED (2-5 OE) - CAS: 69011-36-5

b) Aquatic chronic toxicity:

Endpoint: LC50 - Species: Fish > 10 mg/l - Duration h: 96 - Notes: Leuciscus idus

Endpoint: EC50 - Species: Daphnia > 10 mg/l - Duration h: 48 - Notes: DAPHNIA MAGNA

Endpoint: NOEC - Species: Daphnia = 0.37 mg/l - Duration h: 504 - Notes: DAPHNIA

MAGNA

c) Bacteria toxicity:

Endpoint: EC50 - Species: bacteria = 140 mg/l

d) Terrestrial toxicity:

Endpoint: NOEC = 10 mg/kg - Notes: Lepidium sativum

e) Plant toxicity:

Endpoint: EC50 - Species: Algae > 10 mg/l - Duration h: 72

2-AMINOETHANOL - CAS: 141-43-5

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 349 mg/l - Duration h: 96 - Notes: Cyprinus carpio

Endpoint: NOEC - Species: Fish = 1.2 mg/l - Duration h: 720 - Notes: Oryzias latipes

Endpoint: EC50 - Species: Daphnia = 65 mg/l - Duration h: 48

Endpoint: NOEC - Species: Daphnia = 0.85 mg/l - Duration h: 504

Endpoint: NOEC - Species: Algae = 1 mg/l - Duration h: 72 - Notes: Pseudokirchneriella

subcapitata

Endpoint: EC50 - Species: Algae = 2.5 mg/l - Duration h: 72 - Notes: Pseudokirchneriella

subcapitata

c) Bacteria toxicity:

Endpoint: EC50 - Species: bacteria > 1000 mg/l

Persistence and degradability

ISOTRIDECANOL, ETHOXYLATED (2-5 OE) - CAS: 69011-36-5

Biodegradability: Readily biodegradable - Test: OECD 301B - Duration: 28 days - %: > 60 -

Notes: Aerobic

Biodegradability: Biodegradable - Test: OECD 311 - Duration: 60 days - %: > 60 - Notes:

Anaerobic

2-AMINOETHANOL - CAS: 141-43-5

Biodegradability: Biodegradability rate - Duration: 21 days - %: > 90

Bioaccumulative potential

ISOTRIDECANOL, ETHOXYLATED (2-5 OE) - CAS: 69011-36-5

Low bioconcentration potential 2-AMINOETHANOL - CAS: 141-43-5

Log Pow -1.91

Mobility in soil

ISOTRIDECANOL, ETHOXYLATED (2-5 OE) - CAS: 69011-36-5

High adsorption on soils

Log Koc > 5000 - Notes: QSAR

2-AMINOETHANOL - CAS: 141-43-5

Log Koc 1.17

Other adverse effects

No harmful effects expected.

13. Disposal considerations

Disposal methods:

Disposal should be in accordance with applicable regional, national and local laws and regulations. Please consult Technical Data Sheet for details.

14. Transport information

UN number

Not classified as dangerous in the meaning of transport regulations.

UN proper shipping name

N.A.

Transport hazard class(es)

N.A.

Packing group, if applicable

N.A.

Environmental hazards

ADR-Environmental Pollutant: No IMDG-Marine pollutant: No

Special precautions for user

N.A.

Transport in bulk according to IMO instruments

N.A.

15. Regulatory information

P40460/1

Safety, health and environmental regulations specific for the product in question.

This Safety Data Sheet has been prepared according to the Globally Harmonized System of Classification and Labelling of Chemicals (GHS), Seventh revised edition.

International Inventories:

The substances are listed or exempted from registration in the following international inventories:

HSNO Group Standard Approval: HSR002530

16. Other information

This document was prepared by a competent person who has received appropriate training. Classification complies with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS Ed.7) and is consistent with ERMA New Zealand Approval number (HSNO) which is reported in Section 15.

Full text of phrases referred to in Section 3:

H315 Causes skin irritation.

H318 Causes serious eye damage.

H412 Harmful to aquatic life with long lasting effects.

H227 Combustible liquid.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H401 Toxic to aquatic life.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre,

Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - $\mbox{\sc Van}$

Nostrand Reinold

CCNL - Appendix 1

Insert further consulted bibliography

Important confidentiality: this document contains confidential information that is proprietary to SOCOMORE. Subject to legal provisions determining otherwise, the distribution, republication or re-transmission of this document, in full or in part, must be limited to clearly identified individuals, either because they use the product, or to provide HSE information. Any communication of this document outside of this framework without our written consent is strictly forbidden.

SOCOMORE strongly advises every recipient of this safety data sheet to read it carefully and to consult experts in the field if necessary or appropriate, in order to understand the information it contains, notably the possible dangers associated with this product. The users must ensure the conformity and completeness of this information with regards to their specific use of the product.

The information contained herein is based on our state of knowledge at the above-specified date. It

refers solely to the product indicated and constitutes no guarantee of particular quality. It is the responsibility of the purchaser/user to ensure that their activities conform with current legislation in force.

ADR: European Agreement concerning the International Carriage of

Dangerous Goods by Road.

ATE: Acute Toxicity Estimate

ATEmix: Acute toxicity Estimate (Mixtures)

CAS: Chemical Abstracts Service (division of the American Chemical Society).

CLP: Classification, Labeling, Packaging.

DNEL: Derived No Effect Level.

EINECS: European Inventory of Existing Commercial Chemical Substances.

GefStoffVO: Ordinance on Hazardous Substances, Germany.

GHS: Globally Harmonized System of Classification and Labeling of

Chemicals.

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport

Association" (IATA).

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization"

(ICAO).

IMDG: International Maritime Code for Dangerous Goods.INCI: International Nomenclature of Cosmetic Ingredients.

KSt: Explosion coefficient.

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

PNEC: Predicted No Effect Concentration.

RID: Regulation Concerning the International Transport of Dangerous Goods

by Rail.

STEL: Short Term Exposure limit.

STOT: Specific Target Organ Toxicity.

TLV: Threshold Limiting Value.

TWA: Time-weighted average

WGK: German Water Hazard Class.