

Safety Data Sheet

DIESTONE DLS

Safety Data Sheet date: 7/19/2022, version 4

1. IDENTIFICATION

Product identifier

Mixture identification:
Trade name: DIESTONE DLS
Other means of identification:
SDS code: P28280-NA

Recommended use of the chemical and restrictions on use

Recommended use:
Solvent
Cleaner
Industrial uses
Restrictions on use:
No uses advised against are identified.

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Manufacturers:

Dysol Inc. - 5475 E. State Highway 114, Rhome Texas, 76078 / Phone: 1-817-335-1826 /
csr-na@socomore.com/ Fax Number: 817-335-2405

Distributors:

Dysol Inc. - 5475 E. State Highway 114, Rhome Texas, 76078 / Phone: 1-817-335-1826 /
csr-na@socomore.com/ Fax Number: 817-335-2405
Socomore Canada Limited - Unit 204, 6741 Cariboo Road, Burnaby V3N 4A3, British
Columbia, Canada / Email: csr-ca@socomore.com / Phone: +1 604 420 7707 / Fax: +1 604
420 7701

Competent person responsible for the safety data sheet:

techdirsocomore@socomore.com


Emergency phone number:

CHEMTEL: +1-813-248-0585 (International); 1-800-255-3924 (USA); CANUTEC:
1-613-996-6666 (CANADA)
Socomore Canada Limited - +1-604-420-7707 (Monday-Friday; 7:30 am - 5:00 pm)

2. HAZARD(S) IDENTIFICATION

Classification of the chemical

 Warning, Flam. Liq. 3, Flammable liquid and vapour.

 Warning, STOT SE 3, May cause drowsiness or dizziness.

Aquatic Chronic 3, Harmful to aquatic life with long lasting effects.

Label elements

Hazard pictograms:



Warning

Hazard statements:

Safety Data Sheet

DIESTONE DLS

H226 Flammable liquid and vapour.
 H336 May cause drowsiness or dizziness.
 H412 Harmful to aquatic life with long lasting effects.

Precautionary statements:

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
 P240 Ground/bond container and receiving equipment.
 P241 Use explosion-proof electrical/ventilating/lighting/equipment.
 P242 Use only non-sparking tools.
 P243 Take precautionary measures against static discharge.
 P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
 P271 Use only outdoors or in a well-ventilated area.
 P273 Avoid release to the environment.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.
 P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P312 Call a POISON CENTER/doctor/... if you feel unwell.
 P370+P378 In case of fire: Use ... to extinguish.
 P403+P233 Store in a well-ventilated place. Keep container tightly closed.
 P403+P235 Store in a well-ventilated place. Keep cool.
 P405 Store locked up.
 P501 Dispose of contents/container in accordance with applicable regulations.

Special Provisions:

None

Hazards not otherwise classified identified during the classification process:

None

Ingredient(s) with unknown acute toxicity:

None.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances

N.A.

Mixtures

Hazardous components within the meaning of 29 CFR 1910.1200 and related classification:

>= 70% - < 80% 1-methoxy-2-propanol; monopropylene glycol methyl ether

REACH No.: 01-2119457435-35, Index number: 603-064-00-3, CAS: 107-98-2, EC: 203-539-1



B.6/3 Flam. Liq. 3 H226



A.8/3 STOT SE 3 H336

>= 15% - < 20% 2-methoxy-1-methylethyl acetate

REACH No.: 01-2119475791-29, Index number: 607-195-00-7, CAS: 108-65-6, EC: 203-603-9



B.6/3 Flam. Liq. 3 H226

>= 7% - < 10% HYDROTREATED HEAVY PETROLEUM NAPHTA


CAS: 64742-48-9




B.6/3 Flam. Liq. 3 H226

Safety Data Sheet

DIESTONE DLS

 US-HAE/C2 Aquatic Chronic 2 H411

 A.10/1 Asp. Tox. 1 H304

4. FIRST-AID MEASURES

Description of necessary measures

In case of skin contact:

Immediately take off all contaminated clothing.
Remove contaminated clothing immediately and dispose of safely.

In case of eyes contact:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

In case of Ingestion:

Do not induce vomiting. Obtain a medical examination.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

Most important symptoms/effects, acute and delayed

None

Indication of immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

No particular treatment.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media:

In case of fire: Use ... to extinguish.

Unsuitable extinguishing media

None in particular.

Specific hazards arising from the chemical

Do not inhale explosion and combustion gases.
Burning produces heavy smoke.

Hazardous combustion products:

None

Explosive properties: Not Relevant

Oxidizing properties: Not Relevant

Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus .
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Move undamaged containers from immediate hazard area if it can be done safely.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment, and emergency procedures

Wear personal protection equipment.
Remove all sources of ignition.
Remove persons to safety.
See protective measures under point 7 and 8.

Methods and materials for containment and cleaning up

Wash with plenty of water.

Safety Data Sheet

DIESTONE DLS

7. HANDLING AND STORAGE

Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.
Do not use on extensive surface areas in premises where there are occupants.
Don't use empty container before they have been cleaned.
Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.
See also section 8 for recommended protective equipment.
Advice on general occupational hygiene:
Contaminated clothing should be changed before entering eating areas.
Do not eat or drink while working.

Conditions for safe storage, including any incompatibilities

Always keep in a well ventilated place.
Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.
Avoid accumulating electrostatic charge.
Keep away from food, drink and feed.
Incompatible materials:
None in particular.
Instructions as regards storage premises:
Cool and adequately ventilated.
Safety electric system.
Storage temperature:
Store at ambient temperature.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

- 1-methoxy-2-propanol; monopropylene glycol methyl ether - CAS: 107-98-2
- OEL Type: National - TWA(8h): 188 mg/m³, 50 ppm - STEL: 375 mg/m³, 100 ppm -
Notes: France VLEC - INRS TMP N°84
- OEL Type: National - TWA: 370 mg/m³, 100 ppm - Notes: Germany
- OEL Type: National - TWA: 180 mg/m³ - STEL: 360 mg/m³ - Notes: Poland
- OEL Type: EU - TWA(8h): 375 mg/m³, 100 ppm - STEL: 563 mg/m³, 150 ppm -
Notes: Skin
- OEL Type: ACGIH - TWA(8h): 50 ppm - STEL: 100 ppm - Notes: A4 - Eye and URT
irr
- OEL Type: National - TWA: 187 mg/m³, 50 ppm - STEL(Mow): 187 mg/m³, 50 ppm -
Notes: Osterreich
- OEL Type: National - TWA(8h): 375 mg/m³, 100 ppm - STEL(15'): 560 mg/m³, 150
ppm - Notes: United Kingdom - Skin
- 2-methoxy-1-methylethyl acetate - CAS: 108-65-6
- OEL Type: ACGIH - TWA(8h): 150 ppm - STEL: 100 ppm
- OEL Type: National - TWA(8h): 275 mg/m³, 50 ppm - STEL: 550 mg/m³, 100 ppm -
Behaviour: Binding - Notes: France VLEPC
- OEL Type: National - TWA(8h): 270 mg/m³, 50 ppm - Notes: GERMANY
- OEL Type: National - TWA(8h): 274 mg/m³, 50 ppm - STEL: 548 mg/m³, 100 ppm -
Notes: UK (WELs)
- OEL Type: National - TWA: 260 mg/m³ - STEL: 520 mg/m³ - Notes: POLAND
- OEL Type: EU - TWA(8h): 275 mg/m³, 50 ppm - STEL: 550 mg/m³, 100 ppm -
Notes: Skin
- OEL Type: AIHA
- TWA: 50 ppm
- OEL Type: National - TWA: 275 mg/m³, 50 ppm - STEL(5 min (Mow)): 550 mg/m³,
100 ppm - Notes: Osterreich

Safety Data Sheet

DIESTONE DLS

DNEL Exposure Limit Values

- 1-methoxy-2-propanol; monopropylene glycol methyl ether - CAS: 107-98-2
Worker Industry: 369 mg/m³ - Consumer: 43.9 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
Worker Industry: 50.6 mg/kg b.w./day - Consumer: 18.1 mg/kg b.w./day - Exposure: Human Dermal - Frequency: Long Term, systemic effects
Consumer: 3.3 mg/kg b.w./day - Exposure: Human Oral - Frequency: Long Term, systemic effects
Worker Industry: 553.5 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term (acute)
- 2-methoxy-1-methylethyl acetate - CAS: 108-65-6
Worker Industry: 796 mg/kg b.w./day - Consumer: 320 mg/kg b.w./day - Exposure: Human Dermal - Frequency: Long Term, systemic effects
Worker Industry: 275 mg/m³ - Consumer: 33 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
Consumer: 36 mg/kg b.w./day - Exposure: Human Oral - Frequency: Long Term, systemic effects
Worker Industry: 550 mg/m³ - Consumer: 33 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, local effects

PNEC Exposure Limit Values

- 1-methoxy-2-propanol; monopropylene glycol methyl ether - CAS: 107-98-2
Target: Fresh Water - Value: 10 mg/l
Target: Freshwater sediments - Value: 41.6 mg/kg
Target: Marine water sediments - Value: 4.17 mg/kg
Target: Soil (agricultural) - Value: 2.47 mg/kg
Target: Microorganisms in sewage treatments - Value: 100 mg/l
Target: Marine water - Value: 1 mg/l
Target: Water (intermittent discharge) - Value: 100 mg/l
- 2-methoxy-1-methylethyl acetate - CAS: 108-65-6
Target: Fresh Water - Value: 0.635 mg/l
Target: Marine water - Value: 0.0635 mg/l
Target: Microorganisms in sewage treatments - Value: 100 mg/l
Target: Freshwater sediments - Value: 3.29 mg/kg dw
Target: Marine water sediments - Value: 0.329 mg/kg dw
Target: Soil - Value: 0.29 mg/kg
Target: PNEC intermittent - Value: 6.35 mg/l

Appropriate engineering controls:

None

Individual protection measures

Eye protection:

Safety goggles (EN 166)

Protection for skin:

Chemical protection clothing.

Protection for hands:

PVA (Polyvinyl alcohol).

Butyl rubber (isobutylene-isoprene copolymer)

Respiratory protection:

Use adequate protective respiratory equipment.

Mask with filter "A1" , brown colour (NF EN14387)

Thermal Hazards:

None

9. PHYSICAL AND CHEMICAL PROPERTIES

Safety Data Sheet

DIESTONE DLS

Properties	Value	Method:	Notes
Physical state:	Liquid	--	--
Colour:		--	--
Odour:	N.A.	--	--
Odour threshold:	N.A.	--	--
pH:	Not Relevant	--	--
Melting point / freezing point:	Not Relevant	--	--
Initial boiling point and boiling range:	117C	--	--
Flash Point (F):	86 F	--	--
Flash point (C):	30 C	--	--
Evaporation rate:	0.6	--	--
Solid/gas flammability:	N.A.	--	--
Upper/lower flammability or explosive limits:	7.6	--	--
Vapour pressure:	Not Relevant	--	--
Vapour density:	3.4	--	--
Relative density:	0.9	--	--
Solubility in water:	N.A.	--	--
Solubility in oil:	N.A.	--	--
Partition coefficient (n-octanol/water):	<1	--	--
Auto-ignition temperature:	276 C	--	--
Decomposition temperature:	N.A.	--	--
Viscosity:	N.A.	--	--
Explosive properties:	Not Relevant	--	--
Oxidizing properties:	Not Relevant	--	--

9.2. Other information

Properties	Value	Method:	Notes
Miscibility:	N.A.	--	--
Fat Solubility:	N.A.	--	--
Conductivity:	N.A.	--	--
Substance Groups relevant properties	N.A.	--	--

10. STABILITY AND REACTIVITY

Reactivity

It may generate dangerous reactions (See subsections below)

Chemical stability

It may generate dangerous reactions (See subsections below)

Possibility of hazardous reactions

None

Conditions to avoid

Avoid accumulating electrostatic charge.

Incompatible materials

Avoid contact with combustible materials. The product could catch fire.

Hazardous decomposition products

None.

Safety Data Sheet

DIESTONE DLS

11. TOXICOLOGICAL INFORMATION

Information on toxicological effects

Toxicological information of the product:

N.A.

Toxicological information of the main substances found in the product:

1-methoxy-2-propanol; monopropylene glycol methyl ether - CAS: 107-98-2

Acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 2000 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit > 2000 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat > 5 mg/l - Duration: 4h

2-methoxy-1-methylethyl acetate - CAS: 108-65-6

Acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 5000 mg/kg - Source: OECD 401

Test: LD50 - Route: Skin - Species: Rat > 2000 mg/kg - Source: OECD 402

Test: LC50 - Route: Inhalation - Species: Rat > 10.8 mg/l

Test: LC50 - Route: Skin - Species: Rabbit > 5000 mg/kg - Source: OECD 402

Test: LC0 - Route: Inhalation Vapour - Species: Rabbit = 23.5 mg/l - Source: OECD 403

HYDROTREATED HEAVY PETROLEUM NAPHTA - CAS: 64742-48-9

Acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 5000 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit > 5000 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat > 4951 mg/m³

Substance(s) listed on the NTP report on Carcinogens:

None.

Substance(s) listed on the IARC Monographs:

None.

Substance(s) listed as OSHA Carcinogen(s):

None.

Substance(s) listed as NIOSH Carcinogen(s):

None.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Adopt good working practices, so that the product is not released into the environment.

1-methoxy-2-propanol; monopropylene glycol methyl ether - CAS: 107-98-2

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish > 1000 mg/l - Duration h: 96 - Notes: Leuciscus idus, LC/EC/IC50

Endpoint: LC50 - Species: Daphnia > 1000 mg/l - Duration h: 48 - Notes: LC/EC/IC50

Endpoint: LC50 - Species: Algae > 1000 mg/l - Notes: LC/EC/IC50

Endpoint: LC50 - Species: Fish < 4600 mg/l - Duration h: 96 - Notes: Leuciscus idus

2-methoxy-1-methylethyl acetate - CAS: 108-65-6

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Aquatic plants > 1000 mg/l - Duration h: 72 - Notes:

Selenastrum capricornutum, OECD 201

Endpoint: LC50 - Species: Fish = 134 mg/l - Duration h: 96 - Notes: Oncorhynchus mykiss, OECD 203

Endpoint: EC50 - Species: Invertebrates > 500 mg/l - Duration h: 48 - Notes: Daphnia magna

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Fish = 47.5 mg/l - Duration h: 336 - Notes: Oryzias latipes, OECD 204

Safety Data Sheet
DIESTONE DLS

Endpoint: NOEC - Species: Invertebrates > 100 mg/l - Duration h: 504 - Notes: Daphnia magna, OECD 202

HYDROTREATED HEAVY PETROLEUM NAPHTA - CAS: 64742-48-9

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish > 1000 mg/l - Duration h: 96 - Notes: Oncorhynchus mykiss

Endpoint: EC50 - Species: Algae > 1000 mg/l - Duration h: 72 - Notes: Pseudokirchnerella subcapitata

Persistence and degradability

1-methoxy-2-propanol; monopropylene glycol methyl ether - CAS: 107-98-2

Biodegradability: Readily biodegradable

2-methoxy-1-methylethyl acetate - CAS: 108-65-6

Biodegradability: Biological oxygen demand (BOD) - Test: OECD 301F - Duration: 28 days - %: 83% - Notes: ISO 9408; 92/69/CEE, C.4-D

Bioaccumulative potential

1-methoxy-2-propanol; monopropylene glycol methyl ether - CAS: 107-98-2

Log Pow 0.37

Mobility in soil

N.A.

Other adverse effects

No harmful effects expected.

13. DISPOSAL CONSIDERATIONS

Waste treatment and disposal methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

14. TRANSPORT INFORMATION



UN number

ADR-UN Number: 1993

DOT number: UN1993

IATA-UN Number: 1993

IMDG-UN Number: 1993

UN proper shipping name

ADR-Shipping Name: FLAMMABLE LIQUID, N.O.S. (1-methoxy-2-propanol; monopropylene glycol methyl ether, 2-methoxy-1-methylethyl acetate)

DOT-Shipping Name: Flammable liquids, n.o.s.(1-methoxy-2-propanol; monopropylene glycol methyl ether, 2-methoxy-1-methylethyl acetate)

IATA-Shipping Name: FLAMMABLE LIQUID, N.O.S. (1-methoxy-2-propanol; monopropylene glycol methyl ether, 2-methoxy-1-methylethyl acetate)

IMDG-Shipping Name: FLAMMABLE LIQUID, N.O.S. (1-methoxy-2-propanol; monopropylene glycol methyl ether, 2-methoxy-1-methylethyl acetate)

Transport hazard class(es)

ADR-Class: 3

DOT Hazard Class: 3

Safety Data Sheet

DIESTONE DLS

ADR - Hazard identification number:	30
IATA-Class:	3
IATA-Label:	3
IMDG-Class:	3
Packing group	
ADR-Packing Group:	III
DOT Packing group:	III
IATA-Packing group:	III
IMDG-Packing group:	III
Environmental hazards	
ADR-Environmental Pollutant:	No
IMDG-Marine pollutant:	No
Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code)	
N.A.	
Special precautions	
DOT Special provisions:	B1, B52, IB3, T4, TP1, TP29
DOT Labels:	3
ADR-Subsidiary hazards:	-
ADR-S.P.:	274 601
ADR-Transport category (Tunnel restriction code):	3 (D/E)
IATA-Passenger Aircraft:	355
IATA-Subsidiary hazards:	-
IATA-Cargo Aircraft:	366
IATA-S.P.:	A3
IATA-ERG:	3L
IMDG-EmS:	F-E , S-E
IMDG-Subsidiary hazards:	-
IMDG-Stowage and handling:	Category A
IMDG-Segregation:	-
Q.L.:	5L
Q.E.:	E1

15. REGULATORY INFORMATION

USA - Federal regulations

TSCA - Toxic Substances Control Act

TSCA inventory: all the components are listed on the TSCA inventory or are not required to be listed on the TSCA.

TSCA sections for substances listed in section 3:

1-methoxy-2-propanol; monopropylene glycol methyl ether is listed in TSCA Section 8d HSDR, Section 8b

2-methoxy-1-methylethyl acetate is listed in TSCA Section 8d HSDR, Section 8b, Section 8a - PAIR

HYDROTREATED HEAVY PETROLEUM NAPHTHA is listed in TSCA Section 8b.

SARA - Superfund Amendments and Reauthorization Act

Section 302 Extremely Hazardous Substances: no substances listed.

Section 304 Hazardous substances: no substances listed.

Section 313 Toxic chemical list: no substances listed.

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act

No substances listed.

CAA - Clean Air Act

CAA listed substances:

1-methoxy-2-propanol; monopropylene glycol methyl ether is listed in CAA Section 112(b) - HON.

Safety Data Sheet

DIESTONE DLS

CWA - Clean Water Act
CWA listed substances:
None.

USA - State specific regulations

California Proposition 65
Substance(s) listed under California Proposition 65:
None.

Massachusetts Right to know
Substance(s) listed under Massachusetts Right to know:
1-methoxy-2-propanol; monopropylene glycol methyl ether.

New Jersey Right to know
Substance(s) listed under New Jersey Right to know:
1-methoxy-2-propanol; monopropylene glycol methyl ether.

Pennsylvania Right to know
Substance(s) listed under Pennsylvania Right to know:
1-methoxy-2-propanol; monopropylene glycol methyl ether.

The following substance(s) in this product has/have an identification by CAS number either in countries not affected by the REACH regulation or in regulations not yet updated to reflect the new naming convention for hydrocarbon solvents:
HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS (CAS: 64742-48-9)

16. OTHER INFORMATION

Full text of phrases referred to in Section 3:
H226 Flammable liquid and vapour.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.
H304 May be fatal if swallowed and enters airways.

Safety Data Sheet date: 7/19/2022, version 4

Disclaimer:

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. The information relates only to the specific material and may not be valid for such material used in combination with any other material or in any process.

This Safety Data Sheet cancels and replaces any preceding release.

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

ATE: Acute Toxicity Estimate

ATEmix: Acute toxicity Estimate (Mixtures)

CAS: Chemical Abstracts Service (division of the American Chemical Society).

CLP: Classification, Labeling, Packaging.

DNEL: Derived No Effect Level.

EINECS: European Inventory of Existing Commercial Chemical Substances.

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

HMIS: Hazardous Materials Identification System

IARC: International Agency for Research on Cancer

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport

Safety Data Sheet

DIESTONE DLS

ICAO:	Association" (IATA). International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
NFPA:	National Fire Protection Association
NIOSH:	National Institute for Occupational Safety and Health
NTP:	National Toxicology Program
OSHA:	Occupational Safety and Health Administration
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWA:	Time-weighted average