

Safety Data Sheet
DIESTONE HFP - P28283-NA

Safety Data Sheet dated 9/17/2018, version 3

1. IDENTIFICATION

Product identifier

Mixture identification:

Trade name: DIESTONE HFP

Other means of identification:

SDS code: P28283-NA

Recommended use of the chemical and restrictions on use

Recommended use:

Solvent

Cleaner

Industrial uses

Professional uses

Restrictions on use:

No uses advised against are identified.

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Company:

Dysol Inc. - 791 Westport Parkway - Fort Worth, TX 76177 / Phone: 1-817-335-1826 /
csr-na@socomore.com/ Fax Number: 817-335-2405Distributor: SOCOMORE S.A.S. - Zone Industrielle du Prat - CS 23707 - 56037 VANNES
CEDEX - France - Tel : +33 (0)2 97 43 76 83 - Fax : +33 (0)2 97 54 20 26Distributor: Socomore Ltd - 5, Coe Avenue - Loughborough - Leicestershire - LE11 4SE - UK
- Tel: +44 1509 262040 - Fax: +44 1509 262046Distributor: Socomore Iberia - Calle Diputacio, 260 - 08007 Barcelona - Espana - Tel: +34 917
693 962 - Fax: +34 902 908 966Distributor: MagChem Inc. 1271, rue Ampere, suite 101, Boucherville, QC, J4B 5Z5 Canada -
Tel: 1-450 641 8500 - Fax: 1-450 655 1717Distributor: Socomore GmbH - c/o MAZARS GmbH - Theodor-Stern-Kai 1 - 60596 Frankfurt
am Main - Deutschland - Tel: +49 (0)89 20 70 28 83 - Fax: +49 (0) 89 88 91 98 16Distributor: Socomore Trading Shanghai - 355 East Kang Qiao Road - Kang Qiao Industrial
Zone - Pudong - 201315 Shanghai - Tel: 862158131133 - Fax: 862158131933Dystrybutor : SOCOMORE SPzoo - Ul. Piekna 18, 00-549 Warszawa Polska - Tel : +48 608
454 114 - Fax : +48 (22) 621 61 09

Competent person responsible for the safety data sheet:

techdirsocomore@socomore.com

Emergency phone number

CHEMTEL: 1-800-255-3924 (USA) / CANUTEC: 1-613-996-6666 (CANADA)

2. HAZARD(S) IDENTIFICATION

Classification of the chemical



Warning, Flam. Liq. 3, Flammable liquid and vapour.



Danger, Asp. Tox. 1, May be fatal if swallowed and enters airways.

Label elements

Hazard pictograms:



Danger

Safety Data Sheet**DIESTONE HFP - P28283-NA**

Hazard statements:

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

Precautionary statements:

P210 Keep away from heat - No smoking.

P233 Keep container tightly closed.

P240 Ground container and receiving equipment.

P241 Use explosion-proof electrical equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P280 Wear protective gloves and eye/face protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water/shower.

P331 Do NOT induce vomiting.

P370+P378 In case of fire, use a CO2 fire extinguisher to extinguish.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/container in accordance with applicable regulations.

Special Provisions:

None

Hazards not otherwise classified identified during the classification process:

None

Ingredient(s) with unknown acute toxicity:

None.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances

N.A.

Mixtures

Hazardous components within the meaning of 29 CFR 1910.1200 and related classification:

>= 20% - < 25% 2-methoxy-1-methylethyl acetate

REACH No.: 01-2119475791-29, Index number: 607-195-00-7, CAS: 108-65-6, EC:
203-603-9

B.6/3 Flam. Liq. 3 H226

>= 1% - < 3% XYLENE

REACH No.: 01-2119488216-32, Index number: 601-022-00-9, CAS: 1330-20-7, EC:
215-535-7

B.6/3 Flam. Liq. 3 H226



A.2/2 Skin Irrit. 2 H315



A.1/4/Dermal Acute Tox. 4 H312



A.1/4/Inhal Acute Tox. 4 H332

Safety Data Sheet

DIESTONE HFP - P28283-NA

4. FIRST-AID MEASURES

Description of necessary measures

In case of skin contact:

Immediately take off all contaminated clothing.

Remove contaminated clothing immediately and dispose off safely.

In case of eyes contact:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

In case of Ingestion:

Do NOT induce vomiting.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

Most important symptoms/effects, acute and delayed

None

Indication of immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

No particular treatment.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media:

In case of fire, use a CO2 fire extinguisher to extinguish.

Unsuitable extinguishing media:

None in particular.

Specific hazards arising from the chemical

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

Hazardous combustion products:

None

Explosive properties: Not Relevant

Oxidizing properties: Not Relevant

Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment, and emergency procedures

Wear personal protection equipment.

Remove all sources of ignition.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Provide adequate ventilation.

Remove persons to safety.

Use appropriate respiratory protection.

See protective measures under point 7 and 8.

Methods and materials for containment and cleaning up

Wash with plenty of water.

7. HANDLING AND STORAGE

Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Do not use on extensive surface areas in premises where there are occupants.

Don't use empty container before they have been cleaned.

Safety Data Sheet

DIESTONE HFP - P28283-NA

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

Conditions for safe storage, including any incompatibilities

Always keep in a well ventilated place.

Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.

Avoid accumulating electrostatic charge.

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

Safety electric system.

Storage temperature:

Store at ambient temperature.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

2-methoxy-1-methylethyl acetate - CAS: 108-65-6

- OEL Type: ACGIH - TWA(8h): 150 ppm - STEL: 100 ppm

- OEL Type: National - TWA(8h): 275 mg/m³, 50 ppm - STEL: 550 mg/m³, 100 ppm -

Notes: France VLEC

- OEL Type: National - TWA(8h): 270 mg/m³, 50 ppm - Notes: GERMANY

- OEL Type: National - TWA(8h): 274 mg/m³, 50 ppm - STEL: 548 mg/m³, 100 ppm -

Notes: UK (WELs)

- OEL Type: National - TWA: 260 mg/m³ - STEL: 520 mg/m³ - Notes: POLAND

- OEL Type: EU - TWA(8h): 275 mg/m³, 50 ppm - STEL: 550 mg/m³, 100 ppm -

Notes: Skin

- OEL Type: AIHA

- TWA: 50 ppm

XYLENE - CAS: 1330-20-7

- OEL Type: National - TWA(8h): 440 mg/m³ - Notes: Germany - DFG, H

- OEL Type: National - TWA(8h): 221 mg/m³, 50 ppm - STEL: 442 mg/m³, 100 ppm -

Notes: France VLEC - TMP N? 4Bis, 84

- OEL Type: National - TWA(8h): 220 mg/m³, 50 ppm - STEL: 441 mg/m³, 100 ppm -

Notes: UK (WELs)

- OEL Type: EU - TWA(8h): 221 mg/m³, 50 ppm - STEL: 442 mg/m³, 100 ppm -

Notes: Skin

- OEL Type: ACGIH - TWA(8h): 100 ppm - STEL: 150 ppm - Notes: A4, BEI - URT

and eye irr, CNS impair

DNEL Exposure Limit Values

2-methoxy-1-methylethyl acetate - CAS: 108-65-6

Worker Industry: 153.5 mg/kg bw/day - Consumer: 54.8 mg/kg bw/day - Exposure:

Human Dermal - Frequency: Long Term, systemic effects

Worker Industry: 275 mg/m³ - Consumer: 33 mg/m³ - Exposure: Human Inhalation -

Frequency: Long Term, systemic effects

Consumer: 1.67 mg/kg bw/day - Exposure: Human Oral - Frequency: Long Term, systemic effects

Safety Data Sheet

DIESTONE HFP - P28283-NA

PNEC Exposure Limit Values

- 2-methoxy-1-methylethyl acetate - CAS: 108-65-6
 Target: Fresh Water - Value: 0.635 mg/l
 Target: Marine water - Value: 0.0635 mg/l
 Target: Microorganisms in sewage treatments - Value: 100 mg/l
 Target: Freshwater sediments - Value: 3.29 mg/kg
 Target: Marine water sediments - Value: 0.329 mg/kg
 Target: Soil (agricultural) - Value: 0.29 mg/kg
 Target: PNEC intermittent - Value: 6.35 mg/l
- XYLENE - CAS: 1330-20-7
 Target: Fresh Water - Value: 0.327 mg/l
 Target: Marine water - Value: 0.327 mg/l
 Target: Microorganisms in sewage treatments - Value: 6.58 mg/l
 Target: Freshwater sediments - Value: 12.46 mg/kg dw
 Target: Marine water sediments - Value: 12.46 mg/kg dw
 Target: Soil (agricultural) - Value: 2.31 mg/kg dw
 Target: PNEC intermittent - Value: 0.327 mg/l

Biological Exposure Index

- XYLENE - CAS: 1330-20-7
 Value: 1.5 g/g - medium: Urinary creatinine - Biological Indicator: Methyl hippuric acid in urine - Sampling Period: End of turn - Remark: ACGIH BEL (2009)
 Value: 1.5 mg/g - medium: Urinary creatinine - Biological Indicator: Methyl hippuric acid in urine - Sampling Period: Before turn - Remark: FR IBE (1997)

Appropriate engineering controls:

None

Individual protection measures

Eye protection:

Safety goggles (EN 166)

Protection for skin:

Chemical protection clothing.

Protection for hands:

Suitable gloves type: NF EN374

NBR (nitrile rubber).

PVA (Polyvinyl alcohol).

Respiratory protection:

Use adequate protective respiratory equipment.

Mask with filter "A1" , brown colour (NF EN14387)

Thermal Hazards:

None

9. PHYSICAL AND CHEMICAL PROPERTIES

Properties	Value	Method:	Notes
Appearance and colour:	Clear Colourless liquid	--	--
Odour:	N.A.	--	--
Odour threshold:	N.A.	--	--
pH:	Not Relevant	--	--
Melting point / freezing point:	Not Relevant	--	--
Initial boiling point and boiling range:	163 172 188° C / 327 342 371 °F	--	--

Safety Data Sheet

DIESTONE HFP - P28283-NA

Flash Point (°F):	108°F	--	--
Flash point (°C):	42°C	--	--
Evaporation rate:	0.143	--	--
Solid/gas flammability:	Not Relevant	--	--
Upper/lower flammability or explosive limits:	1.1	--	--
Vapour pressure:	1,3 mmHg (20°C)	--	--
Vapour density:	4.8	--	--
Relative density:	0.86	--	--
Solubility in water:	N.A.	--	--
Solubility in oil:	N.A.	--	--
Partition coefficient (n-octanol/water):	Not Relevant	--	--
Auto-ignition temperature:	276 °C/530°F	--	--
Decomposition temperature:	N.A.	--	--
Viscosity:	< 7 mm ² /s (40°C)	--	--
Explosive properties:	Not Relevant	--	--
Oxidizing properties:	Not Relevant	--	--

9.2. Other information

Properties	Value	Method:	Notes
Miscibility:	N.A.	--	--
Fat Solubility:	N.A.	--	--
Conductivity:	N.A.	--	--
Substance Groups relevant properties	N.A.	--	--

10. STABILITY AND REACTIVITY

Reactivity

It may generate dangerous reactions (See subsections below)

Chemical stability

It may generate dangerous reactions (See subsections below)

Possibility of hazardous reactions

None

Conditions to avoid

Avoid accumulating electrostatic charge.

Incompatible materials

Avoid contact with combustible materials. The product could catch fire.

Hazardous decomposition products

None.

11. TOXICOLOGICAL INFORMATION

Information on toxicological effects

Toxicological information of the product:

N.A.

Safety Data Sheet**DIESTONE HFP - P28283-NA**

Toxicological information of the main substances found in the product:

2-methoxy-1-methylethyl acetate - CAS: 108-65-6

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 5000 mg/kg

Test: LD50 - Route: Skin - Species: Rat > 2000 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat > 10.8 mg/l

Test: LC50 - Route: Skin - Species: Rabbit > 5000 mg/kg

XYLENE - CAS: 1330-20-7

a) acute toxicity:

Test: LC50 - Route: Inhalation Vapour - Species: Rat = 6700 ppm - Duration: 4h

Test: LD50 - Route: Skin - Species: Rabbit > 4200 mg/kg

Test: LD50 - Route: Oral - Species: Rat = 3523 mg/kg

Substance(s) listed on the NTP report on Carcinogens:

None.

Substance(s) listed on the IARC Monographs:

XYLENE - Group 3.

Substance(s) listed as OSHA Carcinogen(s):

None.

Substance(s) listed as NIOSH Carcinogen(s):

None.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Adopt good working practices, so that the product is not released into the environment.

2-methoxy-1-methylethyl acetate - CAS: 108-65-6

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Algae > 1000 mg/l

Endpoint: LC50 - Species: Fish = 134 mg/l

Endpoint: EC50 - Species: Daphnia = 408 mg/l

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Fish = 47.5 mg/l - Duration h: 336 - Notes: Oryzias latipes

Endpoint: NOEC - Species: Daphnia > 100 mg/l - Duration h: 504

XYLENE - CAS: 1330-20-7

a) Aquatic acute toxicity:

Endpoint: NOEC - Species: Daphnia = 1.17 mg/l - Duration h: 168 - Notes: Daphnia - Ceriodaphnia dubia

Endpoint: EC50 - Species: Algae = 4.36 mg/l - Duration h: 73

Endpoint: EC50 - Species: Daphnia = 90 mg/l - Duration h: 48 - Notes: Cypris subglobosa, intoxication

Species: Daphnia = 1 mg/l - Duration h: 24 - Notes: IC50

Endpoint: LC50 - Species: Fish = 2.6 mg/l - Duration h: 96

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Fish > 1.3 mg/l - Duration h: 1344

Persistence and degradability

N.A.

Bioaccumulative potential

XYLENE - CAS: 1330-20-7

Low bioconcentration potential - Test: N.A. N.A. - Duration: N.A. - Notes: N.A.

Log Pow - Test: N.A. 3.12 - Duration: N.A. - Notes: N.A.

BCF - Test: N.A. 8.1 - 25.9 - Duration: N.A. - Notes: N.A.

Mobility in soil

N.A.

Safety Data Sheet

DIESTONE HFP - P28283-NA

Other adverse effects
No harmful effects expected.

13. DISPOSAL CONSIDERATIONS

Waste treatment and disposal methods
Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

14. TRANSPORT INFORMATION



UN number
 ADR-UN Number: 1993
 DOT number: UN1993
 IATA-UN Number: 1993
 IMDG-UN Number: 1993

UN proper shipping name
 ADR-Shipping Name: FLAMMABLE LIQUID, N.O.S. (HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS, 2-methoxy-1-methylethyl acetate)
 DOT-Shipping Name: FLAMMABLE LIQUID, N.O.S. (HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS, 2-methoxy-1-methylethyl acetate)
 IATA-Shipping Name: FLAMMABLE LIQUID, N.O.S. (HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS, 2-methoxy-1-methylethyl acetate)
 IMDG-Shipping Name: FLAMMABLE LIQUID, N.O.S. (HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS, 2-methoxy-1-methylethyl acetate)

Transport hazard class(es)
 ADR-Class: 3
 DOT Hazard Class: 3
 ADR - Hazard identification number: 30
 IATA-Class: 3
 IATA-Label: 3
 IMDG-Class: 3

Packing group
 ADR-Packing Group: III
 DOT Packing group: III
 IATA-Packing group: III
 IMDG-Packing group: III

Environmental hazards
 ADR-Environmental Pollutant: No
 IMDG-Marine pollutant: No

Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code)
 N.A.

Safety Data Sheet

DIESTONE HFP - P28283-NA

Special precautions

DOT Special provisions:	B1, B52, IB3, T4, TP1, TP29
DOT Labels:	3
ADR-Subsidiary risks:	-
ADR-S.P.:	274 601 640E
ADR-Transport category (Tunnel restriction code): (D/E)	
IATA-Passenger Aircraft:	355
IATA-Subsidiary risks:	-
IATA-Cargo Aircraft:	366
IATA-S.P.:	A3
IATA-ERG:	3L
IMDG-EmS:	F-E , S-E
IMDG-Subsidiary risks:	-
IMDG-Stowage and handling:	Category A
IMDG-Segregation:	-
Q.L.: 5L	
Q.E.: E1	

15. REGULATORY INFORMATION

USA - Federal regulations

TSCA - Toxic Substances Control Act

TSCA inventory: all the components are listed on the TSCA inventory.

TSCA listed substances:

2-methoxy-1-methylethyl acetate is listed in TSCA Section 8a - PAIR, Section 8b, Section 8d HSDR

XYLENE is listed in TSCA Section 8b.

SARA - Superfund Amendments and Reauthorization Act

Section 302 - Extremely Hazardous Substances: no substances listed.

Section 304 - Hazardous substances: XYLENE.

Section 313 - Toxic chemical list: XYLENE.

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act

Substance(s) listed under CERCLA: XYLENE - Reportable quantity: 100 pounds.

Reportable quantity for mixture: 4000 pounds.

CAA - Clean Air Act

CAA listed substances:

XYLENE is listed in CAA Section 111, Section 112(b) - HAP, Section 112(b) - HON.

CWA - Clean Water Act

CWA listed substances:

XYLENE is listed in CWA Section 304, Section 311.

USA - State specific regulations

California Proposition 65

Substance(s) listed under California Proposition 65:

None.

Massachusetts Right to know

Substance(s) listed under Massachusetts Right to know:

XYLENE.

New Jersey Right to know

Substance(s) listed under New Jersey Right to know:

XYLENE.

Pennsylvania Right to know

Substance(s) listed under Pennsylvania Right to know:

XYLENE.

Safety Data Sheet

DIESTONE HFP - P28283-NA

The following substance(s) in this product has/have an identification by CAS number either in countries not affected by the REACH regulation or in regulations not yet updated to reflect the new naming convention for hydrocarbon solvents:
 HYDROCARBONS, C9, AROMATICS. (CAS: 64742-95-6)
 HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, <2%
 AROMATICS (CAS: 64742-48-9)

16. OTHER INFORMATION

Full text of phrases referred to in Section 3:

- H226 Flammable liquid and vapour.
- H315 Causes skin irritation.
- H312 Harmful in contact with skin.
- H332 Harmful if inhaled.

Safety Data Sheet dated 9/17/2018, version 3

Disclaimer:

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. The information relates only to the specific material and may not be valid for such material used in combination with any other material or in any process.

This Safety Data Sheet cancels and replaces any preceding release.

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
HMIS:	Hazardous Materials Identification System
IARC:	International Agency for Research on Cancer
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
NFPA:	National Fire Protection Association
NIOSH:	National Institute for Occupational Safety and Health
NTP:	National Toxicology Program
OSHA:	Occupational Safety and Health Administration
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.

Safety Data Sheet
DIESTONE HFP - P28283-NA

TWA: Time-weighted average