

SAFETY DATA SHEET

DILUANT DL 206 ANHYDRE

Version 1.6 Revision Date: 02/17/2020 SDS Number: 102000004254 Date of last issue: 07/02/2019
Date of first issue: 06/03/2017

SECTION 1. IDENTIFICATION

1.1 Product identifier

Trade name : DILUANT DL 206 ANHYDRE

Identification of the article : 070431005R

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Thinner

1.3 Relevant Parties

Supplier

Company : Dysol, Inc. dba Socomore
Address : 791 Westport Parkway
Fort Worth, TX 76177 USA
Telephone : 1-817-335-1826
Email : techsupport-na@socomore.com
Website : www.socomore.com / store.socomore.com

Manufacturer

Company : MÄDER AERO
Address : Rue Jean Baptiste Réveillon 2
FR – 61300 L'AIGLE
Telephone : +33320127950
Email : products-safety.mader-france@mader-group.com

1.4 Emergency telephone number

Emergency telephone number : CHEMTEL: +1-813-248-0585 (International); 1-800-255-3924 (USA)

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

Flammable liquids : Category 2
Skin irritation : Category 2
Eye irritation : Category 2A
Reproductive toxicity : Category 2
Specific target organ toxicity - single exposure : Category 3 (Respiratory system, Central nervous system)
Specific target organ toxicity - repeated exposure : Category 2
Aspiration hazard : Category 1

SAFETY DATA SHEET

DILUANT DL 206 ANHYDRE

Version	Revision Date:	SDS Number:	Date of last issue: 07/02/2019
1.6	02/17/2020	102000004254	Date of first issue: 06/03/2017

GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H225 Highly flammable liquid and vapour.
 H304 May be fatal if swallowed and enters airways.
 H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H335 May cause respiratory irritation.
 H336 May cause drowsiness or dizziness.
 H361d Suspected of damaging the unborn child.
 H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements :

Prevention:

P201 Obtain special instructions before use.
 P202 Do not handle until all safety precautions have been read and understood.
 P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
 P233 Keep container tightly closed.
 P240 Ground/bond container and receiving equipment.
 P241 Use explosion-proof electrical/ ventilating/ lighting equipment.
 P242 Use only non-sparking tools.
 P243 Take precautionary measures against static discharge.
 P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
 P264 Wash skin thoroughly after handling.
 P271 Use only outdoors or in a well-ventilated area.
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
 P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
 P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P308 + P313 IF exposed or concerned: Get medical advice/ attention.
 P331 Do NOT induce vomiting.
 P332 + P313 If skin irritation occurs: Get medical advice/ attention.

SAFETY DATA SHEET

DILUANT DL 206 ANHYDRE

Version 1.6 Revision Date: 02/17/2020 SDS Number: 102000004254 Date of last issue: 07/02/2019
 Date of first issue: 06/03/2017

P337 + P313 If eye irritation persists: Get medical advice/ attention.
 P362 Take off contaminated clothing and wash before reuse.
 P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
 P403 + P235 Store in a well-ventilated place. Keep cool.
 P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : Thinner

Components

Chemical name	CAS-No.	Concentration (% w/w)
Toluene	108-88-3	>= 30 - < 50
Methyl isobutyl ketone	108-10-1	>= 30 - < 50
Butyl acetate	123-86-4	>= 20 - < 30
2-Propanol, 1-methoxy-, acetate	108-65-6	>= 1 - < 5

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.
 Show this safety data sheet to the doctor in attendance.
 Symptoms of poisoning may appear several hours later.
 Do not leave the victim unattended.

If inhaled : Consult a physician after significant exposure.
 If unconscious, place in recovery position and seek medical advice.

In case of skin contact : If skin irritation persists, call a physician.
 If on skin, rinse well with water.
 If on clothes, remove clothes.

In case of eye contact : Immediately flush eye(s) with plenty of water.
 Remove contact lenses.
 Protect unharmed eye.
 Keep eye wide open while rinsing.
 If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.
 Do NOT induce vomiting.
 Do not give milk or alcoholic beverages.
 Never give anything by mouth to an unconscious person.

SAFETY DATA SHEET

DILUANT DL 206 ANHYDRE

Version	Revision Date:	SDS Number:	Date of last issue: 07/02/2019
1.6	02/17/2020	102000004254	Date of first issue: 06/03/2017

Most important symptoms and effects, both acute and delayed	:	<p>If symptoms persist, call a physician. Take victim immediately to hospital. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation. May cause drowsiness or dizziness. Suspected of damaging the unborn child. May cause damage to organs through prolonged or repeated exposure.</p>
Notes to physician	:	No information available.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	:	<p>Alcohol-resistant foam Carbon dioxide (CO₂) Dry chemical</p>
Unsuitable extinguishing media	:	High volume water jet
Specific hazards during fire-fighting	:	Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	:	No hazardous combustion products are known
Further information	:	<p>Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.</p>
Special protective equipment for firefighters	:	Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	:	<p>Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.</p>
Environmental precautions	:	<p>Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.</p>
Methods and materials for containment and cleaning up	:	Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SAFETY DATA SHEET

DILUANT DL 206 ANHYDRE

Version	Revision Date:	SDS Number:	Date of last issue: 07/02/2019
1.6	02/17/2020	102000004254	Date of first issue: 06/03/2017

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.
- Advice on safe handling : Avoid formation of aerosol. Do not breathe vapours/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage stability : No decomposition if stored and applied as directed.

SAFETY DATA SHEET

DILUANT DL 206 ANHYDRE

Version 1.6 Revision Date: 02/17/2020 SDS Number: 102000004254 Date of last issue: 07/02/2019
 Date of first issue: 06/03/2017

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis		
Toluene	108-88-3	TWA	20 ppm	ACGIH		
		TWA	100 ppm 375 mg/m ³	NIOSH REL		
		ST	150 ppm 560 mg/m ³	NIOSH REL		
		TWA	200 ppm	OSHA Z-2		
		CEIL	300 ppm	OSHA Z-2		
		Peak	500 ppm (10 minutes)	OSHA Z-2		
		TWA	100 ppm 375 mg/m ³	OSHA P0		
		STEL	150 ppm 560 mg/m ³	OSHA P0		
		Methyl isobutyl ketone	108-10-1	TWA	20 ppm	ACGIH
STEL	75 ppm			ACGIH		
TWA	50 ppm 205 mg/m ³			NIOSH REL		
ST	75 ppm 300 mg/m ³			NIOSH REL		
TWA	100 ppm 410 mg/m ³			OSHA Z-1		
TWA	50 ppm 205 mg/m ³			OSHA P0		
STEL	75 ppm 300 mg/m ³			OSHA P0		
Butyl acetate	123-86-4			TWA	150 ppm 710 mg/m ³	NIOSH REL
				ST	200 ppm 950 mg/m ³	NIOSH REL
		TWA	150 ppm 710 mg/m ³	OSHA Z-1		
		TWA	150 ppm 710 mg/m ³	OSHA P0		
		STEL	200 ppm 950 mg/m ³	OSHA P0		
		TWA	50 ppm	ACGIH		
		STEL	150 ppm	ACGIH		
		2-Propanol, 1-methoxy-, acetate	108-65-6	TWA	50 ppm	US WEEL

SAFETY DATA SHEET

DILUANT DL 206 ANHYDRE

Version 1.6 Revision Date: 02/17/2020 SDS Number: 102000004254 Date of last issue: 07/02/2019
 Date of first issue: 06/03/2017

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
Toluene	108-88-3	Toluene	In blood	Prior to last shift of work-week	0.02 mg/l	ACGIH BEI
		Toluene	Urine	End of shift (As soon as possible after exposure ceases)	0.03 mg/l	ACGIH BEI
Methyl isobutyl ketone	108-10-1	methyl isobutyl ketone	Urine	End of shift (As soon as possible after exposure ceases)	1 mg/l	ACGIH BEI

Personal protective equipment

- Respiratory protection : In the case of vapour formation use a respirator with an approved filter.
- Hand protection
- Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.
- Eye protection : Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.
- Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Hygiene measures : When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : liquid
- Colour : colourless
- Odour : solvent-like
- Odour Threshold : No data available
- pH : Not applicable

SAFETY DATA SHEET

DILUANT DL 206 ANHYDRE

Version 1.6	Revision Date: 02/17/2020	SDS Number: 102000004254	Date of last issue: 07/02/2019 Date of first issue: 06/03/2017
----------------	------------------------------	-----------------------------	---

Melting point/range	:	Not applicable
Boiling point/boiling range	:	> 97 °F / > 36 °C
Flash point	:	ca. 39 °F / 4 °C
Evaporation rate	:	No data available
Self-ignition	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapour pressure	:	< 1,000 hPa (122 °F / 50 °C)
Relative vapour density	:	No data available
Density	:	ca. 0.85 g/cm ³ (73 °F / 23 °C)
Solubility(ies)		
Water solubility	:	immiscible
Partition coefficient: n-octanol/water	:	No data available
Auto-ignition temperature	:	No data available
Decomposition temperature	:	Not applicable
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	< 20.4 mm ² /s (104 °F / 40 °C)
Explosive properties	:	No data available
Oxidizing properties	:	No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No decomposition if stored and applied as directed.
Chemical stability	:	No decomposition if stored and applied as directed.
Possibility of hazardous reactions	:	No dangerous reaction known under conditions of normal use. No decomposition if stored and applied as directed. Vapours may form explosive mixture with air.
Conditions to avoid	:	Heat, flames and sparks.
Incompatible materials	:	Strong oxidizing agents Strong oxidizing agents

SAFETY DATA SHEET

DILUANT DL 206 ANHYDRE

Version 1.6	Revision Date: 02/17/2020	SDS Number: 102000004254	Date of last issue: 07/02/2019 Date of first issue: 06/03/2017
----------------	------------------------------	-----------------------------	---

NTP No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Suspected of damaging the unborn child.

STOT - single exposure

May cause respiratory irritation.
May cause drowsiness or dizziness.

STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.
Concentrations substantially above the TLV value may cause narcotic effects.
Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances
Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : No data available

SAFETY DATA SHEET

DILUANT DL 206 ANHYDRE

Version	Revision Date:	SDS Number:	Date of last issue: 07/02/2019
1.6	02/17/2020	102000004254	Date of first issue: 06/03/2017

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

- | | | |
|------------------------|---|--|
| Waste from residues | : | Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company. |
| Contaminated packaging | : | Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum. |

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

- | | | |
|----------------------|---|------------------------|
| UN number | : | UN 1263 |
| Proper shipping name | : | PAINT RELATED MATERIAL |
| Class | : | 3 |
| Packing group | : | II |
| Labels | : | 3 |

IATA-DGR

- | | | |
|--------------------------------------|---|------------------------|
| UN/ID No. | : | UN 1263 |
| Proper shipping name | : | PAINT RELATED MATERIAL |
| Class | : | 3 |
| Packing group | : | II |
| Labels | : | Flammable Liquids |
| Packing instruction (cargo aircraft) | : | 364 |

IMDG-Code

- | | | |
|----------------------|---|------------------------|
| UN number | : | UN 1263 |
| Proper shipping name | : | PAINT RELATED MATERIAL |
| Class | : | 3 |
| Packing group | : | II |
| Labels | : | 3 |
| EmS Code | : | F-E, <u>S-E</u> |
| Marine pollutant | : | no |

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

49 CFR

- | | | |
|----------------------|---|------------------------|
| UN/ID/NA number | : | UN 1263 |
| Proper shipping name | : | PAINT RELATED MATERIAL |
| Class | : | 3 |
| Packing group | : | II |
| Labels | : | FLAMMABLE LIQUID |
| ERG Code | : | 128 |
| Marine pollutant | : | no |

SAFETY DATA SHEET

DILUANT DL 206 ANHYDRE

Version 1.6 Revision Date: 02/17/2020 SDS Number: 102000004254 Date of last issue: 07/02/2019
Date of first issue: 06/03/2017

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Toluene	108-88-3	1,000	2,857
Toluene	108-88-3	100	100 (F005)
Methyl isobutyl ketone	108-10-1	100	100 (F003)

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)
Skin corrosion or irritation
Serious eye damage or eye irritation
Reproductive toxicity
Specific target organ toxicity (single or repeated exposure)
Aspiration hazard

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

Toluene	108-88-3	>= 30 - < 50 %
Methyl isobutyl ketone	108-10-1	>= 30 - < 50 %

Clean Air Act

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 112 (40 CFR 61):

Toluene	108-88-3	>= 30 - < 50 %
Methyl isobutyl ketone	108-10-1	>= 30 - < 50 %

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489):

Toluene	108-88-3	>= 30 - < 50 %
Methyl isobutyl ketone	108-10-1	>= 30 - < 50 %
Butyl acetate	123-86-4	>= 20 - < 30 %

SAFETY DATA SHEET

DILUANT DL 206 ANHYDRE

Version	Revision Date:	SDS Number:	Date of last issue: 07/02/2019
1.6	02/17/2020	102000004254	Date of first issue: 06/03/2017

Clean Water Act

The following Hazardous Substances are listed under the U.S. CleanWater Act, Section 311, Table 116.4A:

Toluene	108-88-3	>= 30 - < 50 %
Butyl acetate	123-86-4	>= 20 - < 30 %

The following Hazardous Chemicals are listed under the U.S. CleanWater Act, Section 311, Table 117.3:

Toluene	108-88-3	>= 30 - < 50 %
Butyl acetate	123-86-4	>= 20 - < 30 %

This product contains the following toxic pollutants listed under the U.S. Clean Water Act Section 307

Toluene	108-88-3	>= 30 - < 50 %
---------	----------	----------------

US State Regulations

Massachusetts Right To Know

Toluene	108-88-3
Methyl isobutyl ketone	108-10-1
Butyl acetate	123-86-4
2-Propanol, 1-methoxy-, acetate	108-65-6

Pennsylvania Right To Know

Toluene	108-88-3
Methyl isobutyl ketone	108-10-1
Butyl acetate	123-86-4
2-Propanol, 1-methoxy-, acetate	108-65-6

Maine Chemicals of High Concern

Toluene	108-88-3
---------	----------

The following chemicals are listed as Maine Chemicals of High Concern:

Maine Chemicals of High Concern

Toluene	108-88-3
---------	----------

Vermont Chemicals of High Concern

Toluene	108-88-3
---------	----------

Washington Chemicals of High Concern

Toluene	108-88-3
---------	----------

California Prop. 65

WARNING: This product can expose you to chemicals including Methyl isobutyl ketone, which is/are known to the State of California to cause cancer, and Toluene, Methyl isobutyl ketone, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

California List of Hazardous Substances

Toluene	108-88-3
Methyl isobutyl ketone	108-10-1
Butyl acetate	123-86-4

California Permissible Exposure Limits for Chemical Contaminants

Toluene	108-88-3
Methyl isobutyl ketone	108-10-1
Butyl acetate	123-86-4
2-Propanol, 1-methoxy-, acetate	108-65-6

SAFETY DATA SHEET

DILUANT DL 206 ANHYDRE

Version 1.6 Revision Date: 02/17/2020 SDS Number: 102000004254 Date of last issue: 07/02/2019
Date of first issue: 06/03/2017

The components of this product are reported in the following inventories:

TSCA : On the inventory, or in compliance with the inventory
DSL : All components of this product are on the Canadian DSL

TSCA list


No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



HMIS® IV:

HEALTH	*	3
FLAMMABILITY		4
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)
NIOSH REL : USA. NIOSH Recommended Exposure Limits
OSHA P0 : USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA Z-2 : USA. Occupational Exposure Limits (OSHA) - Table Z-2
US WEEL : USA. Workplace Environmental Exposure Levels (WEEL)
ACGIH / TWA : 8-hour, time-weighted average
ACGIH / STEL : Short-term exposure limit
NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST : STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday

SAFETY DATA SHEET

DILUANT DL 206 ANHYDRE

Version	Revision Date:	SDS Number:	Date of last issue: 07/02/2019
1.6	02/17/2020	102000004254	Date of first issue: 06/03/2017

OSHA P0 / TWA	:	8-hour time weighted average
OSHA P0 / STEL	:	Short-term exposure limit
OSHA Z-1 / TWA	:	8-hour time weighted average
OSHA Z-2 / TWA	:	8-hour time weighted average
OSHA Z-2 / CEIL	:	Acceptable ceiling concentration
OSHA Z-2 / Peak	:	Acceptable maximum peak above the acceptable ceiling concentration for an 8-hr shift
US WEEL / TWA	:	8-hr TWA

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 02/17/2020

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN