

## SAFETY DATA SHEET

### PRIAM PCE 211 PARTIE B

Version            Revision Date:            SDS Number:            Date of last issue: 02/08/2019  
1.7                02/13/2020                102000004072            Date of first issue: 06/03/2017

---

#### SECTION 1. IDENTIFICATION

##### 1.1 Product identifier

Trade name                                : PRIAM PCE 211 PARTIE B

Identification of the article            : 045880105R

##### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mix-            : Hardener  
ture

##### 1.3 Relevant Parties

###### Supplier

Company                                : Dysol, Inc. dba Socomore  
Address                                 : 791 Westport Parkway  
Fort Worth, TX 76177 USA  
Telephone                               : 1-817-335-1826  
Email                                     : techsupport-na@socomore.com  
Website                                 : www.socomore.com / store.socomore.com

###### Manufacturer

Company                                : MÄDER AERO  
Address                                 : Rue Jean Baptiste Réveillon 2  
FR – 61300 L'AIGLE  
Telephone                               : +33320127950  
Email                                     : products-safety.mader-france@mader-group.com

##### 1.4 Emergency telephone number

Emergency telephone                 : CHEMTEL: +1-813-248-0585 (International); 1-800-255-3924 (USA)  
number

---

#### SECTION 2. HAZARDS IDENTIFICATION

##### GHS classification in accordance with 29 CFR 1910.1200

Flammable liquids                     : Category 3  
Skin irritation                         : Category 2  
Serious eye damage                   : Category 1  
Specific target organ toxicity       : Category 3 (Respiratory system)  
- single exposure  
Specific target organ toxicity       : Category 2  
- repeated exposure

## SAFETY DATA SHEET

### PRIAM PCE 211 PARTIE B

Version	Revision Date:	SDS Number:	Date of last issue: 02/08/2019
1.7	02/13/2020	102000004072	Date of first issue: 06/03/2017

#### GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H226 Flammable liquid and vapour.  
H315 Causes skin irritation.  
H318 Causes serious eye damage.  
H335 May cause respiratory irritation.  
H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements :

**Prevention:**

P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.  
P233 Keep container tightly closed.  
P240 Ground/bond container and receiving equipment.  
P241 Use explosion-proof electrical/ ventilating/ lighting equipment.  
P242 Use only non-sparking tools.  
P243 Take precautionary measures against static discharge.  
P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.  
P264 Wash skin thoroughly after handling.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves/ eye protection/ face protection.

**Response:**

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.  
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.  
P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.  
P314 Get medical advice/ attention if you feel unwell.  
P332 + P313 If skin irritation occurs: Get medical advice/ attention.  
P362 Take off contaminated clothing and wash before reuse.  
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

**Storage:**

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.  
P403 + P235 Store in a well-ventilated place. Keep cool.  
P405 Store locked up.

# SAFETY DATA SHEET

## PRIAM PCE 211 PARTIE B

Version 1.7      Revision Date: 02/13/2020      SDS Number: 102000004072      Date of last issue: 02/08/2019  
 Date of first issue: 06/03/2017

**Disposal:**

P501 Dispose of contents/ container to an approved waste disposal plant.

**Other hazards**

None known.

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : Hardener

**Components**

Chemical name	CAS-No.	Concentration (% w/w)
Xylene	1330-20-7	>= 30 - < 50
1-Butanol	71-36-3	>= 10 - < 20
Ethylbenzene	100-41-4	>= 1 - < 5

Actual concentration is withheld as a trade secret

### SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.  
 Show this safety data sheet to the doctor in attendance.  
 Do not leave the victim unattended.

If inhaled : Consult a physician after significant exposure.  
 If unconscious, place in recovery position and seek medical advice.

In case of skin contact : If skin irritation persists, call a physician.  
 If on skin, rinse well with water.  
 If on clothes, remove clothes.

In case of eye contact : Immediately flush eye(s) with plenty of water.  
 Remove contact lenses.  
 Protect unharmed eye.  
 Keep eye wide open while rinsing.  
 If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.  
 Do not give milk or alcoholic beverages.  
 Never give anything by mouth to an unconscious person.  
 If symptoms persist, call a physician.  
 Take victim immediately to hospital.

Most important symptoms and effects, both acute and delayed : Causes skin irritation.  
 Causes serious eye damage.  
 May cause respiratory irritation.  
 May cause damage to organs through prolonged or repeated exposure.

Notes to physician : No information available.

### SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Alcohol-resistant foam  
 Carbon dioxide (CO<sub>2</sub>)  
 Dry chemical

## SAFETY DATA SHEET

### PRIAM PCE 211 PARTIE B

Version	Revision Date:	SDS Number:	Date of last issue: 02/08/2019
1.7	02/13/2020	102000004072	Date of first issue: 06/03/2017

- 
- |   |   |   |
|---|---|---|
| Unsuitable extinguishing media                | : | High volume water jet   |
| Specific hazards during fire-fighting         | : | Do not allow run-off from fire fighting to enter drains or water courses.   |
| Hazardous combustion products                 | : | No hazardous combustion products are known  |
| Further information                           | : | Collect contaminated fire extinguishing water separately. This must not be discharged into drains.<br>Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.<br>For safety reasons in case of fire, cans should be stored separately in closed containments.<br>Use a water spray to cool fully closed containers. |
| Special protective equipment for firefighters | : | In the event of fire, wear self-contained breathing apparatus.  |

---

#### SECTION 6. ACCIDENTAL RELEASE MEASURES

- |   |   |   |
|---|---|---|
| Personal precautions, protective equipment and emergency procedures | : | Use personal protective equipment.<br>Ensure adequate ventilation.<br>Remove all sources of ignition.<br>Evacuate personnel to safe areas.<br>Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. |
| Environmental precautions   | : | Prevent product from entering drains.<br>Prevent further leakage or spillage if safe to do so.<br>If the product contaminates rivers and lakes or drains inform respective authorities.   |
| Methods and materials for containment and cleaning up               | : | Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).                     |

---

#### SECTION 7. HANDLING AND STORAGE

- |   |   |  |
|---|---|--|
| Advice on protection against fire and explosion | : | Do not spray on a naked flame or any incandescent material.<br>Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).<br>Keep away from open flames, hot surfaces and sources of ignition.                                     |
| Advice on safe handling                         | : | Avoid formation of aerosol.<br>Do not breathe vapours/dust.<br>Avoid exposure - obtain special instructions before use.<br>Avoid contact with skin and eyes.<br>For personal protection see section 8.<br>Smoking, eating and drinking should be prohibited in the application area. |

**SAFETY DATA SHEET**
**PRIAM PCE 211 PARTIE B**

Version	Revision Date:	SDS Number:	Date of last issue:
1.7	02/13/2020	102000004072	02/08/2019
			Date of first issue: 06/03/2017

- Take precautionary measures against static discharges.  
 Provide sufficient air exchange and/or exhaust in work rooms.  
 Open drum carefully as content may be under pressure.  
 Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : No smoking.  
 Keep container tightly closed in a dry and well-ventilated place.  
 Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
 Observe label precautions.  
 Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage conditions : To protect from humid air, and water
- Further information on storage stability : No decomposition if stored and applied as directed.

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**
**Components with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Xylene	1330-20-7	TWA	100 ppm 435 mg/m <sup>3</sup>	OSHA Z-1
		TWA	100 ppm	ACGIH
		STEL	150 ppm	ACGIH
		STEL	150 ppm 655 mg/m <sup>3</sup>	OSHA P0
		TWA	100 ppm 435 mg/m <sup>3</sup>	OSHA P0
1-Butanol	71-36-3	TWA	20 ppm	ACGIH
		C	50 ppm 150 mg/m <sup>3</sup>	NIOSH REL
		TWA	100 ppm 300 mg/m <sup>3</sup>	OSHA Z-1
		C	50 ppm 150 mg/m <sup>3</sup>	OSHA P0
Ethylbenzene	100-41-4	TWA	20 ppm	ACGIH
		TWA	100 ppm 435 mg/m <sup>3</sup>	NIOSH REL
		ST	125 ppm 545 mg/m <sup>3</sup>	NIOSH REL
		TWA	100 ppm 435 mg/m <sup>3</sup>	OSHA Z-1
		TWA	100 ppm 435 mg/m <sup>3</sup>	OSHA P0
		STEL	125 ppm 545 mg/m <sup>3</sup>	OSHA P0

# SAFETY DATA SHEET

## PRIAM PCE 211 PARTIE B

Version 1.7      Revision Date: 02/13/2020      SDS Number: 102000004072      Date of last issue: 02/08/2019  
 Date of first issue: 06/03/2017

### Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
Xylene	1330-20-7	Methylhippuric acids	Urine	End of shift (As soon as possible after exposure ceases)	1.5 g/g creatinine	ACGIH BEI

### Personal protective equipment

- Respiratory protection : In the case of vapour formation use a respirator with an approved filter.
- Hand protection
- Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.
- Eye protection : Eye wash bottle with pure water  
Tightly fitting safety goggles  
Wear face-shield and protective suit for abnormal processing problems.
- Skin and body protection : Impervious clothing  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Hygiene measures : When using do not eat or drink.  
When using do not smoke.  
Wash hands before breaks and at the end of workday.

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : liquid
- Colour : colourless
- Odour : solvent-like
- pH : Not applicable
- Melting point/freezing point : No data available
- Boiling point/boiling range : > 97 °F / > 36 °C
- Flash point : ca. 73 °F / 23 °C
- Evaporation rate : No data available
- Self-ignition : No data available
- Upper explosion limit / Upper flammability limit : No data available

## SAFETY DATA SHEET

### PRIAM PCE 211 PARTIE B

Version	Revision Date:	SDS Number:	Date of last issue: 02/08/2019
1.7	02/13/2020	102000004072	Date of first issue: 06/03/2017

---

Lower explosion limit / Lower flammability limit	:	No data available
Vapour pressure	:	< 1,000 hPa (122 °F / 50 °C)
Relative vapour density	:	No data available
Density	:	ca. 0.92 g/cm <sup>3</sup> (73 °F / 23 °C)
Solubility(ies)		
Water solubility	:	immiscible
Partition coefficient: n-octanol/water	:	No data available
Auto-ignition temperature	:	No data available
Decomposition temperature	:	Not applicable
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	> 20.6 mm <sup>2</sup> /s (104 °F / 40 °C)
Explosive properties	:	No data available
Oxidizing properties	:	No data available

---

#### SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No decomposition if stored and applied as directed.
Chemical stability	:	No decomposition if stored and applied as directed.
Possibility of hazardous reactions	:	No dangerous reaction known under conditions of normal use. No decomposition if stored and applied as directed. Vapours may form explosive mixture with air.
Conditions to avoid	:	Heat, flames and sparks.
Incompatible materials	:	Strong oxidizing agents Strong oxidizing agents
Hazardous decomposition products	:	Stable under recommended storage conditions.

---

#### SECTION 11. TOXICOLOGICAL INFORMATION

##### Acute toxicity

Not classified based on available information.

##### **Product:**

Acute oral toxicity	:	Acute toxicity estimate: 4,386 mg/kg Method: Calculation method
Acute inhalation toxicity	:	Acute toxicity estimate: 27.11 mg/l Exposure time: 4 h Test atmosphere: vapour

## SAFETY DATA SHEET

### PRIAM PCE 211 PARTIE B

Version 1.7	Revision Date: 02/13/2020	SDS Number: 102000004072	Date of last issue: 02/08/2019 Date of first issue: 06/03/2017
----------------	------------------------------	-----------------------------	---

---

Method: Calculation method  
Assessment: The substance/mixture is not toxic on inhalation as defined by dangerous goods regulations.

Acute toxicity estimate: 21.68 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: 2,285 mg/kg  
Method: Calculation method

#### **Skin corrosion/irritation**

Causes skin irritation.

#### **Product:**

Remarks : May cause skin irritation in susceptible persons.

#### **Serious eye damage/eye irritation**

Causes serious eye damage.

#### **Product:**

Remarks : May cause irreversible eye damage.

#### **Respiratory or skin sensitisation**

##### **Skin sensitisation**

Not classified based on available information.

##### **Respiratory sensitisation**

Not classified based on available information.

##### **Germ cell mutagenicity**

Not classified based on available information.

##### **Carcinogenicity**

Not classified based on available information.

<b>IARC</b>	Group 2B: Possibly carcinogenic to humans Ethylbenzene	100-41-4
-------------	---	----------

**OSHA** No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

**NTP** No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

##### **Reproductive toxicity**

Not classified based on available information.

##### **STOT - single exposure**

May cause respiratory irritation.



## SAFETY DATA SHEET

### PRIAM PCE 211 PARTIE B

Version	Revision Date:	SDS Number:	Date of last issue: 02/08/2019
1.7	02/13/2020	102000004072	Date of first issue: 06/03/2017

---

#### **STOT - repeated exposure**

May cause damage to organs through prolonged or repeated exposure.

#### **Aspiration toxicity**

Not classified based on available information.

#### **Further information**

#### **Product:**

Remarks : Solvents may degrease the skin.

---

## SECTION 12. ECOLOGICAL INFORMATION

#### **Ecotoxicity**

No data available

#### **Persistence and degradability**

No data available

#### **Bioaccumulative potential**

No data available

#### **Mobility in soil**

No data available

#### **Other adverse effects**

#### **Product:**

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances  
Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Harmful to aquatic life with long lasting effects.

---

## SECTION 13. DISPOSAL CONSIDERATIONS

#### **Disposal methods**

Waste from residues : The product should not be allowed to enter drains, water courses or the soil.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

---

## SAFETY DATA SHEET

### PRIAM PCE 211 PARTIE B

Version	Revision Date:	SDS Number:	Date of last issue:
1.7	02/13/2020	102000004072	02/08/2019
			Date of first issue: 06/03/2017

---

#### SECTION 14. TRANSPORT INFORMATION

##### International Regulations

###### UNRTDG

UN number	:	UN 1263
Proper shipping name	:	PAINT RELATED MATERIAL
Class	:	3
Packing group	:	III
Labels	:	3

###### IATA-DGR

UN/ID No.	:	UN 1263
Proper shipping name	:	PAINT RELATED MATERIAL
Class	:	3
Packing group	:	III
Labels	:	Flammable Liquids
Packing instruction (cargo aircraft)	:	366

###### IMDG-Code

UN number	:	UN 1263
Proper shipping name	:	PAINT RELATED MATERIAL
Class	:	3
Packing group	:	III
Labels	:	3
EmS Code	:	F-E, <u>S-E</u>
Marine pollutant	:	no

##### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

##### National Regulations

###### 49 CFR

UN/ID/NA number	:	UN 1263
Proper shipping name	:	PAINT RELATED MATERIAL
Class	:	3
Packing group	:	III
Labels	:	FLAMMABLE LIQUID
ERG Code	:	128
Marine pollutant	:	no

##### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

---

#### SECTION 15. REGULATORY INFORMATION

##### EPCRA - Emergency Planning and Community Right-to-Know Act

# SAFETY DATA SHEET

## PRIAM PCE 211 PARTIE B

Version 1.7      Revision Date: 02/13/2020      SDS Number: 102000004072      Date of last issue: 02/08/2019  
 Date of first issue: 06/03/2017

### CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Xylene	1330-20-7	100	207
Xylene	1330-20-7	100	100 (F003)
1-Butanol	71-36-3	100	100 (F003)
Ethylbenzene	100-41-4	100	100 (F003)
Toluene	108-88-3	100	100 (F005)

### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

**SARA 311/312 Hazards** : Flammable (gases, aerosols, liquids, or solids)  
 Specific target organ toxicity (single or repeated exposure)  
 Skin corrosion or irritation  
 Serious eye damage or eye irritation

**SARA 313** : The following components are subject to reporting levels established by SARA Title III, Section 313:

1-Butanol	71-36-3	>= 10 - < 20 %
Ethylbenzene	100-41-4	>= 1 - < 5 %

### Clean Air Act

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 112 (40 CFR 61):

Xylene	1330-20-7	>= 30 - < 50 %
Ethylbenzene	100-41-4	>= 1 - < 5 %

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489):

Xylene	1330-20-7	>= 30 - < 50 %
1-Butanol	71-36-3	>= 10 - < 20 %
Ethylbenzene	100-41-4	>= 1 - < 5 %

### Clean Water Act

The following Hazardous Substances are listed under the U.S. CleanWater Act, Section 311, Table 116.4A:

Xylene	1330-20-7	>= 30 - < 50 %
Ethylbenzene	100-41-4	>= 1 - < 5 %
Toluene	108-88-3	>= 0 - < 0.1 %

The following Hazardous Chemicals are listed under the U.S. CleanWater Act, Section 311, Table 117.3:

Xylene	1330-20-7	>= 30 - < 50 %
Ethylbenzene	100-41-4	>= 1 - < 5 %
Toluene	108-88-3	>= 0 - < 0.1 %

## SAFETY DATA SHEET

### PRIAM PCE 211 PARTIE B

Version	Revision Date:	SDS Number:	Date of last issue: 02/08/2019
1.7	02/13/2020	102000004072	Date of first issue: 06/03/2017

This product contains the following toxic pollutants listed under the U.S. Clean Water Act Section 307

Ethylbenzene	100-41-4	>= 1 - < 5 %
--------------	----------	--------------

This product contains the following priority pollutants related to the U.S. Clean Water Act:

Ethylbenzene	100-41-4	>= 1 - < 5 %
--------------	----------	--------------

#### US State Regulations

##### Massachusetts Right To Know

Xylene	1330-20-7
1-Butanol	71-36-3
Ethylbenzene	100-41-4

##### Pennsylvania Right To Know

Xylene	1330-20-7
1-Butanol	71-36-3
Ethylbenzene	100-41-4
Toluene	108-88-3

##### Maine Chemicals of High Concern

Toluene	108-88-3
---------	----------

The following chemicals are listed as Maine Chemicals of High Concern:

##### Maine Chemicals of High Concern

Toluene	108-88-3
---------	----------

##### Vermont Chemicals of High Concern

Ethylbenzene	100-41-4
Toluene	108-88-3

##### Washington Chemicals of High Concern

Ethylbenzene	100-41-4
Toluene	108-88-3

##### California Prop. 65

WARNING: This product can expose you to chemicals including Ethylbenzene, which is/are known to the State of California to cause cancer, and Toluene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

##### California List of Hazardous Substances

Xylene	1330-20-7
1-Butanol	71-36-3
Ethylbenzene	100-41-4

##### California Permissible Exposure Limits for Chemical Contaminants

Xylene	1330-20-7
1-Butanol	71-36-3
Ethylbenzene	100-41-4

#### The components of this product are reported in the following inventories:

TSCA : All substances listed as active on the TSCA inventory

DSL : All components of this product are on the Canadian DSL

## SAFETY DATA SHEET

### PRIAM PCE 211 PARTIE B

Version 1.7      Revision Date: 02/13/2020      SDS Number: 102000004072      Date of last issue: 02/08/2019  
Date of first issue: 06/03/2017

#### TSCA list


No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

## SECTION 16. OTHER INFORMATION

#### Further information

##### NFPA 704:



##### HMIS® IV:

<b>HEALTH</b>	*	<b>3</b>
<b>FLAMMABILITY</b>	<b>3</b>	
<b>PHYSICAL HAZARD</b>	<b>0</b>	

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

#### Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	:	ACGIH - Biological Exposure Indices (BEI)
NIOSH REL	:	USA. NIOSH Recommended Exposure Limits
OSHA P0	:	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	:	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
NIOSH REL / C	:	Ceiling value not be exceeded at any time.
OSHA P0 / TWA	:	8-hour time weighted average
OSHA P0 / STEL	:	Short-term exposure limit
OSHA P0 / C	:	Ceiling limit
OSHA Z-1 / TWA	:	8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation,

## SAFETY DATA SHEET

### PRIAM PCE 211 PARTIE B

Version	Revision Date:	SDS Number:	Date of last issue: 02/08/2019
1.7	02/13/2020	102000004072	Date of first issue: 06/03/2017

and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 02/13/2020

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN