

ADDICAP 2 is an anti-evaporation additive which protects the active layer of non chlorinated remover.

- Maintenance product for baths of paint removers of the type **SOCOSTRIP A4310**. This product is neither toxic nor harmful.
- It is inert in contact with steel, aluminium and zinc.

DIRECTIONS FOR USE

When operating non chlorinated remover baths between 60 and 90°C (140 and 194°F), losses due to evaporation and product drag out have to be compensated for to maintain a high degree of efficiency.

During maintenance operations, after adjustment of the active layer, add ADDICAP 2 to obtain the following values:

- 10% of the bath minimum (in volume)
- If the tank is wide, always maintain a minimum thickness of 20 cm of ADDICAP 2. The absolute minimum is 12cm, even if the tank is narrow; below this the active layer evaporation rate will be too high.

TECHNICAL CHARACTERISTICS

Appearance clear liquid
Specific gravity (at 20°C) 0,9
Flash point (ISO 2592) 125°C (257°F)
Free of chlorinated or aromatic solvents

PRECAUTIONS FOR USE AND STORAGE

For more information regarding the danger of the product, please consult the product safety data sheet according to local regulation.

For professional use only.

This technical data sheet replaces and cancels the previous one.

The above details have been compiled to the best of our knowledge. They have, however, an indicative value only and we therefore make no warranties and assume no liability in connection with any use of this information, particularly if a third party's rights are affected by the use of our products. The above information has been compiled based upon tests carried out by SOCOMORE. All data is subject to change as Socomore deems appropriate. The data given is not intended to substitute for any testing you must conduct in order to determine the suitability of the product for your particular purposes. Please check your local legislation applicable to the use of this product. Should you need any further

information please contact us.