

Aeroglaze 9953 thinner is used to reduce the viscosity of Aeroglaze epoxy primers for spray applications. Aeroglaze 9953 thinner is not compatible with Aeroglaze or Chemglaze polyurethane coatings or wash primers.

### Features & Benefits

- **Improves Application:** when used in conjunction with Aeroglaze epoxy primers, Aeroglaze 9953 improves flow properties for spray application and provides control of application film thickness.
- **Multifunctional:** Aeroglaze 9953 is very effective when used to clean substrates prior to priming with an Aeroglaze epoxy primer and spray equipment contaminated with Aeroglaze epoxy primers.

### DIRECTIONS FOR USE

#### Mixing

Mix the required Aeroglaze epoxy primer prior to adding Aeroglaze 9953 thinner. Refer to the appropriate technical data sheet for primer mixing instructions.

Slowly add Aeroglaze 9953 thinner while stirring the mixed epoxy primer. The amount of thinner that should be added is dependent on the specific primer, as well as the spray system properties.

Aeroglaze 9953 thinner is not compatible with Aeroglaze or Chemglaze polyurethane coatings or wash primers.

### TECHNICAL CHARACTERISTICS

#### Typical Properties\*

Property	Value
Appearance	Clear or Straw Yellow Liquid
Density, kg/L (lb/gal) ASTM D 1475-85	0.81-0.84 (6.73-7.03)
Flash Point (Seta), °C (°F) ASTM D 3278-82, Closed Cup	2.2 (36)
Volatile Organic Content (VOC), g/L (lb/gal) ASTM D 3960-87	824 (6.88)

\*Data is typical and not to be used for specification purposes.

## ***PRECAUTIONS FOR USE AND STORAGE***

---

The shelf life is one year from date of shipment when stored in a dry, well-ventilated area at 0-32°C (32-90°F) in the original, unopened container. Do not store or use near heat, sparks, or open flames.

Before using this or any SOCOMORE product, refer to the Safety Data Sheet (SDS) and label for safe use and handling instructions.

For industrial/commercial use only. Must be applied by trained personnel only. Not to be used in household applications. Not for consumer use.

Manufactured for SOCOMORE by: LORD Corporation, Saegertown, PA

**This technical data sheet replaces and cancels the previous one.**

The above details have been compiled to the best of our knowledge. They have, however, an indicative value only and we therefore make no warranties and assume no liability in connection with any use of this information, particularly if a third party's rights are affected by the use of our products. The above information has been compiled based upon tests carried out by SOCOMORE. All data is subject to change as Socomore deems appropriate. The data given is not intended to substitute for any testing you must conduct in order to determine the suitability of the product for your particular purposes. Please check your local legislation applicable to the use of this product. Should you need any further information please contact us.