Technical Data Sheet

Approvals and conformities

 DEPT OF NAVY
 6237660

 HONEYWELL
 P8251333-7

 ITT, Space Systems
 400-3093-301

 L3 Communications
 B185239

 PRATT & WHITNEY
 PWA36510

Chemglaze 9951 thinner is used to reduce the viscosity of Chemglaze wash primers and polyurethane coatings for spray applications.

Features & Benefits

- Improves Application: when used in conjunction with Chemglaze wash primers and polyurethane coatings, Chemglaze 9951 thinner improves flow properties for spray application and provides better control of application film thickness.
- **Multifunctional:** Chemglaze 9951 is very effective when used to clean spray equipment and substrates with light contamination.

DIRECTIONS FOR USE

Mixing

Mix the required Chemglaze wash primer or polyurethane coating prior to adding Chemglaze 9951 thinner. Refer to the appropriate technical data sheet for coating mixing instructions.

Slowly add Chemglaze 9951 thinner while stirring the mixed coating. The amount of thinner that should be added is dependent on the coating, as well as the spray system properties.

TECHNICAL CHARACTERISTICS

Typical Properties*

Property	Value
Appearance	Clear Liquid
Density, kg/L (lb/gal) ASTM D 1475-85	0.89-0.91 (7.5-7.6)
Flash Point (Seta), °C (°F) ASTM D 3278-82, Closed Cup	32 (90)





Volatile Organic Content (VOC), g/L (lb/gal) ASTM D 3960-87	890 (7.43)
----------------------------------------------------------------	------------

^{*}Data is typical and not to be used for specification purposes.

PRECAUTIONS FOR USE AND STORAGE

The shelf life is one year from date of shipment when stored in a dry, well-ventilated area at 0-32°C (32-90°F) in the original, unopened container. Do not store or use near heat, sparks, or open flames.

Before using this or any SOCOMORE product, refer to the Safety Data Sheet (SDS) and label for safe use and handling instructions.

For industrial/commercial use only. Must be applied by trained personnel only. Not to be used in household applications. Not for consumer use.

Manufactured for SOCOMORE by: LORD Corporation, Saegertown, PA

This technical data sheet replaces and cancels the previous one.

The above details have been compiled to the best of our knowledge. They have, however, an indicative value only and we therefore make no warranties and assume no liability in connection with any use of this information, particularly if a third party's rights are affected by the use of our products. The above information has been compiled based upon tests carried out by SOCOMORE. All data is subject to change as Socomore deems appropriate. The data given is not intended to substitute for any testing you must conduct in order to determine the suitability of the product for your particular purposes. Please check your local legislation applicable to the use of this product. Should you need any further information please contact us.

