

### Approvals and conformities

AIR FRANCE	FITS 51095
AIRBUS	APII 09-01-002, I.P. DA -62.32 Annexe 1
AIRBUS HELICOPTERS	Marignane : IF-MA310
ATR	SRM : 11-003F
DASSAULT AVIATION	DGQT 22689
DGA (French Army)	Fiche identification n°3705 / AIR 0011
EADS CASA	Z23150 (liquid form) / Z24943 (presaturated wipes)
ROLLS-ROYCE	oMat 1/257AL
SAFRAN	Pr-1500
SAFRAN HELICOPTER ENGINES (formerly TURBOMECA)	CCT LA 729 - CCT LB 540

**DIESTONE D is a solvent composition with controlled volatility. It is free from halogenated hydrocarbons and used as a cleaning agent. The product provides maximum security, it is absolutely free from any aromatic component harmful to health. It does not contain any teratogenic or carcinogenic components.**

- Very high solvent power, which gives excellent cleaning and degreasing of metallic surfaces before painting.
- Non-corrosive on metals, including light alloys. Efficient reactivation and cleaning of epoxy and polyurethane primers.
- Pleasant odour.
- Compatible with epoxy, polyurethane, acrylic and nitrocellulose paints and lacquers.
- Absolutely free from toluene, xylene and glycol ethyl acetate.
- The flash point is stable in time and remains constant throughout the evaporation period.
- Available in liquid form, and in CONTEC presaturated wipes.

## USES

---

Painting and paint stripping shops, construction and assembly:

- Cleaning of paint application equipment (brushes, rollers, spray guns, spray booths, etc...).
- Subsidiary stripper of dry paint films (elimination of polyvinyl primers and nitrocellulose lacquers).
- Suitable for eliminating graffiti, felt-tip, inks, etc...
- Degreasing of epoxy/carbon composites before painting.
- Cleaning of jointing, sealant and glue application equipment
- Removal of excess, marks and runs of jointing products, sealants and glues.

## DIRECTIONS FOR USE

---

DIESTONE D is used as supplied without dilution at ambient temperature using the following methods:

- spraying
- brushing or swabbing,
- by circulation in paint equipment pipes.

## TECHNICAL CHARACTERISTICS

---

Appearance .....	clear liquid
Specific gravity .....	(at 20°C / 68°F) 0.92
Flammability point .....	(ISO 2592) 30°C / 86°F
Evaporation rate (NFT 30301) (n-Butyl acetate=1) .....	0.5
Halogenated hydrocarbon content .....	none

## PRECAUTIONS FOR USE AND STORAGE

---

It is recommended to wear suitable gloves because the strong degreasing action of DIESTONE D will de-fat the skin. Avoid breathing or swallowing the product. Wear suitable eye protection when handling or using the product. In the case of contact with skin or eyes, rinse immediately and abundantly with water. If work is continuous, it is recommended to install a vapour extraction system at the emission point.

DIESTONE D must be used and stored in a sufficiently ventilated place, away from flame and heat sources. The product must be protected and kept in the closed original containers.

For more information regarding the danger of the product, please consult the product safety data sheet according to local regulation.

For professional use only.

**This technical data sheet replaces and cancels the previous one.**

The above details have been compiled to the best of our knowledge. They have, however, an indicative value only and we therefore make no warranties and assume no liability in connection with any use of this information, particularly if a third party's rights are affected by the use of our products. The above information has been compiled based upon tests carried out by SOCOMORE. All data is subject to change as SOCOMORE deems appropriate. The data given is not intended to substitute for any testing you must conduct in order to determine the suitability of the product for your particular purposes. Pictures are not contractual. Please check your local legislation applicable to the use of this product. Should you need any further information please contact us.