DIESTONE DS88

Technical Data Sheet

DIESTONE DS88 thinner is a balanced blend of solvents designed to reduce the viscosity of high molecular weight adhesion promoters to make them applicable for spray application.

Key Characteristics

- Improves application
- Eliminates cobwebbing
- · Promotes fast dry times
- Provides excellent flow properties to enhance control of dry film thickness

DIESTONE DS88 can also be used as cleaner for spray guns and tools before and after application.

USES

Improves the spraying properties of high viscosity adhesion promoters. Also suitable for cleaning tools and spray guns pre and post application.

DIRECTIONS FOR USE

Mixing

Premix the adhesion promoter coating before adding the thinner. Refer to the appropriate data sheet for the coating mixing instructions.

Stir the adhesion promoter and slowly add Diestone DS88 thinner. Depending on the adhesion promoter, add the DS88 thinner 140-160% by volume. Consult the adhesion promoter data sheet for specific recommendations.

TECHNICAL CHARACTERISTICS

Appearance	Clear Colorless Liquid
	7.24 (0.872 kg/l) ASTM D 1475-85
Flash point	
VOC (US regulation)	887 g/L (7.4 lb./gal) ASTM D 3960-87



1/2

PRECAUTIONS FOR USE AND STORAGE

Shelf life is one year from date of shipment when stored in a dry, well ventilated area at 16°C (60°F) in original, unopened containers. Do not store or use near heat, sparks or open flame.

Cautionary information before using this or any SOCOMORE product: Refer to the Material Safety Data Sheet (MSDS) and label for safe use and handling instructions.

For industrial/commercial use only. Must be applied by trained personnel only. Not to be used in household applications. Not for consumer use.

This technical data sheet replaces and cancels the previous one.

The above details have been compiled to the best of our knowledge. They have, however, an indicative value only and we therefore make no warranties and assume no liability in connection with any use of this information, particularly if a third party's rights are affected by the use of our products. The above information has been compiled based upon tests carried out by SOCOMORE. All data is subject to change as Socomore deems appropriate. The data given is not intended to substitute for any testing you must conduct in order to determine the suitability of the product for your particular purposes. Please check your local legislation applicable to the use of this product. Should you need any further information please contact us.

