

Comant CI 420-221

ComDat GPS

COBHAM

2008 Data Sheet

The most important thing we build is trust

CI 420-221 ComDat GPS

Comant's ComDat® stand-alone GPS antenna with TNC connector. Matches the popular teardrop footprint found on many general aviation aircraft and business jets.

Meets RTCA DO 160D operating standards including direct effects lightning. Designed to operate with Garmin 17.0 dB panel mount GPS receivers.

Not compatible with most portable GPS receiver systems.

Applications

Most aircraft up to and including business jets. Consult your FBO or installation shop for best application information.

Frequencies Covered

GPS 1575.42 MHz - 17.0 dB Gain

Specifications

GPS Preamplifier Characteristics

Frequency	1575.42 +/-3 MHz
VSWR	1.5:1 Maximum
Polarization	RHCP
Radiation Pattern	Hemispherical
Output Impedance	50 Ohms
Gain @ 1575.42 MHz	17 +/-3 dB
DC Voltage	4 to 24 Volts
DC Current Min/Max	20mA Maximum
Noise Figure	3.8 dB
Selectivity	-35 dB Min. @ Satcom 1626.5 MHz

Mechanical / Environmental

Weight	4.2 Ounces
RTCA Env. / TSO	DO 160D / C 144
Connector	TNC (Female)



WARNING: Use factory supplied drawings and specifications for installation. Refer to FAA AC 43.13-2B for installation guidelines.

For further information please contact:

Cobham SATCOM Airborne Systems
577 Burning Tree Road
Fullerton, California 92833 USA
Tel: (01) 714-870-2420
Fax: (01) 714-870-5133
Email: comant@cobham.com