

Comant CI 105-6 & CI 105-7

DME/XPDR

COBHAM

The most important thing we build is trust

CI 105-6 & CI 105-7 DME/XPDR

Comant CI 105-3 DME/Transponder antenna. Identical to the CI 105 in operating characteristics. The antenna is designed for external applications using a four hole flange mounting. BNC female connector.

Applications

Single and twin engine piston aircraft for applications of this antenna design. Consult your FBO or installation shop for best application information.

Frequencies Covered

960-1220 MHz

Specifications

Electrical

Frequency	960-1220 MHz
VSWR	1.5:1 Max 960-1220 MHz 1.3:1 Max 1025-1150 MHz
Polarization	Vertical
Radiation Pattern	Equivalent to a 1/4 wave stub
Impedance RF	50 Ohms
Resistance DC	Open Circuit
Power RF	2.5 KW Peak

Mechanical

Weight	0.40 lbs
Height	3.31 inches
Finish	Polyurethane Enamel
Material	Molded Radome
Connector CI 105-6	BNC
Connector CI 105-7	C

Environmental

Temperature	-54 C to +55 C
Altitude	70,000 ft.

Federal Specifications

FAA TSO	C66b, C74c
RTCA Environmental	DO-160C

Gasket B10505



WARNING: Use factory supplied drawings and specifications for installation. Refer to FAA AC 43.13-2B for installation guidelines.

Order at:

Tel: 714-870-2420 Fax: 714-870-6294
Email: comantorders@cobham.com