

Comant CI 292-2

VHF Communication

COBHAM

The most important thing we build is trust

CI 292-2 VHF Communication

Identical to the CI 292-1 except thais it provides a stainless steel bent-whip radiator which makes it ideal for helicopters and bot-tom mounting underneath fixed wing aircraft.

The CI 292-2 has been re-tested and upgrad-ed to the new RTCA DO-160D environmental requirements and offers the 118 to 137 MHz frequency associated with DO 186 MOPS.

Applications

Single engine piston aircraft for applications of this antenna design. Consult your FBO or installation shop for best application information.

Frequencies Covered

118-137 MHz

Specifications

Electrical

Frequency 118-137 MHz

VSWR 3.0:1 Maximum

Polarization Vertical

Radiation Pattern Omnidirectional

Impedance RF 50 Ohms

Power RF 50 Watts

Mechanical

Weight 0.6 lbs Maximum

Height 8.5 inches / 23.5 inches total length

Material Cast Housing / Stainless steel whip

Finish Polyurethane Enamel

Connector BNC (female)

Environmental

Temperature -55 to +85 Celsius

Altitude 50,000 ft.

Federal Specifications

FAA TSO C37d, C38d

RTCA Environmental DO-160D

Gasket

C29205 Cork Neoprene



WARNING: Use factory supplied drawings and specifications for installation. Refer to FAA AC 43.13-2B for installation guidelines.

Order at:

Tel: 714-870-2420 Fax: 714-870-6294

Email: comantorders@cobham.com