

4MP Indoor Fixed-focal Wi-Fi Pan & Tilt Network Camera DH-H4C



Series Overview

The Hero Series, which is under the Dahua Wireless series, are cameras that are not only easy to install and operate, but also perform outstandingly and are cost-effective. These highly sensitive cameras deliver crystal clear images and offer 360-degree monitoring without blind spots. Their powerful functions, such as human detection and auto tracking, not only assist with the accurate detection and continuous tracking of targets, but also reduce the occurrence of false alarms. It also features two-way talk, which allows you to freely communicate with your scene anytime, anywhere. Information is synchronously sent to your phone to keep you up-to-date. These cameras are widely used in small scenes such as shops and restaurants.



| 9:41 | | .al 🗢 🖬 |
|-------------------------|-----------|---------|
| < | Live | 0 = |
| 00 | 0.0 | |
| | | |
| | | |
| Playback | \$ D | 0 88 |
| | 0 0 | \$ P |
| | ^ | |
| Alarm Messag | io | |
| 07/05/2023 | | |
| • ⊅ Human I 15:01:08 | Detection | 10.5 |
| • 弐 Human (15.01.05 | Detection | 10.5 |
| • 🕞 Vehicle E | Detection | 5. |

Upgrade Your Experience with DMSS

Dahua Mobile Security Surveillance (DMSS) is a professional remote surveillance management platform that offers remote monitoring, device migration, and sharing. When connected to the internet, the platform provides real-time alerts to improve surveillance efficiency and grant flexibility in security management.







Specifications

Camera

Image Sensor Max. Resolution Electronic Shutter Speed Illumination Distance Illuminator On/Off Control Illuminator Number Angle Adjustment Max. Aperture Field of View

Intelligence

Human Detection

Video & Audio

Video Compression

Resolution

Video Frame Rate

Video Bit Rate

Day/Night

WDR Motion Detection

Image Rotation Built-in MIC

2560 (H) × 1440 (V) Auto/Manual1/3s~1/100000s 15m(49.21 ft) Manual; Auto; Off 1 (IR light) Pan: 0° to 325° Tilt: -20° to +100° F1.6 H: 80.3°; V: 43.2; D: 94.3°

1/2.8" CMOS

Yes

Smart H.265+;H.265;Smart H.264+;H.264;H.264B;MJPEG 4M (2560×1440); 1080p (1920×1080); 960p (1280x960); 720p (1280×720) Main stream: 4M/1080p/1.3M/720p @(1–25/30 fps) Sub stream 1: D1/CIF@ (1–25/30 fps)" H.264: 256 Kbps-8192 Kbps H.265: 144 Kbps-8192 Kbps Auto(ICR)/Color/B/W DWDR Yes

Built-in Speaker

Audio Compression

Network

Network Port Wi-Fi Storage

Management Software

Mobile Client

General

| Certifications | CE |
|----------------------|---|
| Power Supply | 5 VDC, 1 A ± 10% (Type-C) |
| Power Consumption | Basic: 2 W Max: 5 W (illuminator +PTZ +speaker) |
| Operating Conditions | -10 °C to +40 °C (14 °F to +104 °F) |
| Operating Humidity | ≤ 95% |
| Casing Material | Plastic |
| Product Dimensions | 130.4mm×Ф95.5mm |
| Net Weight | 0.25 kg (0.55 lb) |
| | |

Yes

G722.1

DMSS

iOS;Android

RJ-45 (10/100 Base-T)

FTP; Micro SD card (512 GB)

PCM; G.711a; G.711Mu; G.726; MPEG2-Layer2;

IEEE 802.11b/g/n 2.412-2.472 GHz, 2.4 G

What's in the box

Tools:



Installation Position

180°

Yes

Map×1 Mounting Plate×1 Screw Package×1

Power:

Power Adapter×1 Power Cable×1



Documents:

QR Code×1

Quick Start Guide×1

Legal and regulation

information×1