

Accessories——One-Touch Fittings

One-touch fittings—tube-tube type

Ordering code

Same diameter type fittings

GPE 6 □

① ② ③

① Model				② Port size	③ Standard color		
GPM: Bulkhead union	GPE: Union tee	GPP: Plug	GPV: Union elbow	4 : Φ4mm 6 : Φ6mm 8 : Φ8mm 10 : Φ10mm 12 : Φ12mm	Standard color	Specification	Adaptable model
					Blank: Gray	Release button: Gray	GPM
						Release button: Gray Body: Gray	Others
GPLM: Bulkhead male elbow	GPY: Union "Y"	GPZ: Cross	GPU: Straight union		D: Black	Release button: Black	GPM
						Release button: Black Body: Black	Others

Different diameter type fittings

GPEG 6 - 4 □

① ② ③ ④

① Model					② Port size I	③ Port size II	④ Standard color	
GPG: Different diameter straight	GPZG: Different diameter cross	GPEW: Different diameter tee	GPYW: Different diameter union "Y"	GPGJ: Plug-in reducer	4: Φ4mm 6: Φ6mm 8: Φ8mm 10: Φ10mm 12: Φ12mm	4: Φ4mm 6: Φ6mm 8: Φ8mm 10: Φ10mm	Standard color	Specification
							Blank: Gray	Release button: Gray Body: Gray
GPEG: Different diameter tee	GPKG: Reducer triple branch union	GPHK: Universal reducer triple branch union	GPHD: Universal reducer four branch union					Release button: Black Body: Black
							D: Black	

Specification

Operating pressure range	0~10kgf/cm ² (0~1.0MPa)
Negative pressure	-750mmHg(10Torr)
Proof pressure	1.5MPa
Ambient and fluid temperature (°C)	-20~70
Applicable tubing	Soft nylon or polyurethane
Color	Gray/black

Product feature

1. Variable models can be widely used in every kind of pneumatic systems.
2. High circulation performance: bear the same flow with the volume of the tubing inside diameter.
3. Connect tubing easily and conveniently. The tubing connection portion is safe and durable.
4. The threaded portion is covered with sealant and the M5 thread is attached with a sealing gasket to prevent air leakage over the connection thread portion.

Inner structure

GPM Series		
	No.	Item
	1	Release button
	2	Guide
	3	Spring gasket
	4	Chuck
	5	O-ring
	6	Body
	7	Rubber washer
	8	Nut
		Material
		POM
		Aluminum alloy
		Stainless steel
		POM
		NBR
		Aluminum alloy
		NBR
		Aluminum alloy

Table for interface port and tube O.D.


Product series	Port size I	Port size II				
		Φ4	Φ6	Φ8	Φ10	
GPG GPGJ	Φ4					
	Φ6	●				
	Φ8	●	●			
	Φ10		●	●		
	Φ12			●	●	
GPEG GPEW GPYW	Φ4					
	Φ6	●				
	Φ8		●			
	Φ10			●		
	Φ12			●	●	
GPZG	Φ4					
	Φ6	●				
	Φ8		●			
	Φ10			●		
	Φ12				●	
GPKG	Φ4					
	Φ6	●				
	Φ8		●			
	Φ10			●		
	Φ12					
GPHK GPHD	Φ4					
	Φ6					
	Φ8		●			
	Φ10			●		
	Φ12					
Product series		Port size				
		Φ4	Φ6	Φ8	Φ10	Φ12
GPE, GPY, GPV, GPU		●	●	●	●	●
GPM, GPLM, GPP, GPZ		●	●	●	●	●

Accessories—One-Touch Fittings

One-touch fittings—tube-tube type


Dimensions

GPE Series




Model\Item	ΦD	ΦP	K	E	ΦJ	JB	JC	Weight(g)	PCS/bag
GPE4	4	9	14	17	3.2	6.5	13	3.1	10
GPE6	6	12.5	16.5	20	3.2	8	16	6.1	10
GPE8	8	15	18.5	23	4.3	9.5	19	8.8	10
GPE10	10	18	21	26.5	4.3	11	22	13.8	10
GPE12	12	21	23	30	4.3	13	26	21	10

GPU Series




Model\Item	ΦD	ΦP	K	A	Weight(g)	PCS/bag
GPU4	4	9	14	29.5	1.7	10
GPU6	6	12.5	16.5	34	3.6	10
GPU8	8	15	18.5	38.5	5	10
GPU10	10	18	21	43	8.1	10
GPU12	12	21	23	47	12	10

GPY Series




Model\Item	ΦD	ΦP	C	K	ΦJ	JA	DC	Weight(g)	PCS/bag
GPY4	4	9	31.5	14	3.2	13	10	3	10
GPY6	6	12.5	37	16.5	3.2	15.5	12	6	10
GPY8	8	15	42.5	18.5	3.2	17	14.5	8.6	10
GPY10	10	18	48.5	21	4.3	19.5	18	14	10
GPY12	12	21	54.5	23	4.3	21	20.5	21.2	10

GPM Series




Model\Item	ΦD	M	A	K	L	E	GA	G	Weight(g)	PCS/bag
GPM4	4	M12X1	29	14	10	7	4	14	6.2	10
GPM6	6	M14X1	34	16.5	10.5	11	4	17	9.5	10
GPM8	8	M16X1	38	18.5	11.5	13	4	19	15.7	10
GPM10	10	M20X1	43	21	12.5	16	5	24	22.5	10
GPM12	12	M22X1	46.5	23	13.5	17.5	6	27	29.5	10

GPV Series



Model\Item	ΦD	ΦP	K	E	ΦJ	JB	Weight(g)	PCS/bag
GPV4	4	9	14	17	3.2	6.5	1.9	10
GPV6	6	12.5	16.5	20	3.2	8	4.2	10
GPV8	8	15	18.5	23	4.3	9.5	6	10
GPV10	10	18	21	26.5	4.3	11	9.3	10
GPV12	12	21	23	30	4.3	13	14.6	10

GPLM Series




Model\Item	ΦD	ΦP	M	L	E	K	EA	EB	GA	G	H	Weight(g)	PCS/bag
GPLM4	4	9	M12X1	12	7.5	14	17	31	4	14	14	7.5	10
GPLM6	6	12.5	M14X1	12.5	8.5	17	20	35.5	4	17	17	12.1	10
GPLM8	8	15	M16X1	13.5	9	18.5	23	39	4	19	19	16.6	10
GPLM10	10	18	M20X1	14.5	11	21	25.5	44.5	5	24	22	26.2	10
GPLM12	12	21	M22X1	15.5	11	23	29.5	48	6	27	24	34	10

Accessories—One-Touch Fittings

AIRTAC


One-touch fittings—tube-tube type

GPYW Series




Model\Item	ΦDA	ΦDB	C	ΦP	KA	KB	ΦJ	JA	DC	Weight(g)	PCS/bag
GPYW6-4	6	4	36.5	12.5	16.5	14	3.2	15	12	5.8	10
GPYW8-6	8	6	42	15	18.5	16.5	3.2	16.5	14.5	9.1	10
GPYW10-8	10	8	48.5	18	21	18.5	4.3	19	18	14.1	10
GPYW12-8	12	8	54	21	23	18.5	4.3	20.5	20.5	22.3	10
GPYW12-10	12	10	54.5	21	23	21	4.3	21	20.5	21.7	10

GPEG Series




Model\Item	ΦDA	ΦDB	ΦP	KA	KB	EA	EB	ΦJ	JB	JC	Weight(g)	PCS/bag
GPEG6-4	6	4	12.5	16.5	14	20.0	19.5	3.2	8	16	7	10
GPEG8-6	8	6	15	18.5	16.5	22.5	22	4.3	9.5	19	22.8	10
GPEG10-8	10	8	18	21	18.5	25.5	25.5	4.3	11	22	15.1	10
GPEG12-8	12	8	21	23	18.5	29	28.5	4.3	13	26	22	10
GPEG12-10	12	10	21	23	21	29	29	4.3	13	26	21.5	10

GPZ Series




Model\Item	ΦD	A	ΦP	K	ΦJ	JB	JC	Weight(g)	PCS/bag
GPZ4	4	34	9	14	3.2	6.5	13	3.9	10
GPZ6	6	39.5	12.5	16.5	3.2	8	16	7.9	10
GPZ8	8	46	15	18.5	4.3	9.5	19	11.1	10
GPZ10	10	52.5	18	21	4.3	11	22	17.5	10
GPZ12	12	59.5	21	23	4.3	13	26	26.6	10

GPEW Series




Model\Item	ΦDA	ΦDB	ΦP	KA	KB	EA	EB	ΦJ	JB	JC	Weight(g)	PCS/bag
GPEW6-4	6	4	12.5	16.5	14	20	19.5	3.2	8	16	7	10
GPEW8-6	8	6	15	18.5	16.5	22.5	22	4.3	9.5	19	22.8	10
GPEW10-8	10	8	18	21	18.5	25.5	25.5	4.3	11	22	15.1	10
GPEW12-8	12	8	21	23	18.5	29	28.5	4.3	13	26	22	10
GPEW12-10	12	10	21	23	21	29	29	4.3	13	26	21.5	10

GPG Series



Model\Item	ΦDA	ΦDB	ΦPA	ΦPB	KA	KB	A	Weight(g)	PCS/bag
GPG6-4	6	4	12.5	9	16.5	14	33.5	2.7	10
GPG8-4	8	4	15	12.5	18.5	14	37.5	4.5	10
GPG8-6	8	6	15	12.5	18.5	16.5	38	4.5	10
GPG10-6	10	6	18	15	21	16.5	42	6.9	10
GPG10-8	10	8	18	15	21	18.5	42.5	6.7	10
GPG12-8	12	8	21	18	23	18.5	46.5	10.3	10
GPG12-10	12	10	21	18	23	21	47	10.2	10

GPP Series



Model\Item	ΦD	ΦPA	ΦPB	L	A	Weight(g)	PCS/bag
GPP4	4	5	3	15	27.5	0.7	10
GPP6	6	7	3	17	32	0.9	10
GPP8	8	9	4	18	36	1.6	10
GPP10	10	11	5	20	42	2.5	10
GPP12	12	13	6	23	44	4.3	10




Accessories——One-Touch Fittings

AirTAC


One-touch fittings—tube-tube type

GPGJ Series




Model\Item	ΦDA	ΦDB	ΦP	K	L	A	Weight(g)	PCS/bag
GPGJ6-4	6	4	9	14	21	35	1.5	10
GPGJ8-4	8	4	12.5	14	22	39	2.6	10
GPGJ8-6	8	6	12.5	16.5	22	39.5	3.2	10
GPGJ10-6	10	6	15	16.5	25	44	4.1	10
GPGJ10-8	10	8	15	18.5	25	44.5	3.9	10
GPGJ12-8	12	8	18	18.5	26	48.5	6.2	10
GPGJ12-10	12	10	18	21	26	49	6	10

GPZG Series




Model\Item	ΦDA	ΦDB	A	C	ΦP	KA	KB	ΦJ	JB	JC	Weight(g)	PCS/bag
GPZG6-4	6	4	39	39.5	12.5	16.5	14	3.2	8	16	8.2	10
GPZG8-6	8	6	45	46	15	18.5	16.5	4.3	9.5	19	12	10
GPZG10-8	10	8	52	52.5	18	21	18.5	4.3	11	22	18.1	10
GPZG12-10	12	10	59	59.5	21	23	21	4.3	13	26	29	10

GPHK Series




Model\Item	ΦDA	ΦDB	A	ΦPA	ΦPB	KA	KB	DC	E	Weight(g)	PCS/bag
GPHK8-6	8	6	75	14	12.5	18.5	16.5	15.5	25	28.4	2
GPHK10-8	10	8	85.5	17	15	21	18.5	16.5	29.5	45	2

GPHD Series



Model\Item	ΦDA	ΦDB	A	ΦPA	ΦPB	KA	KB	DC	E	Weight(g)	PCS/bag
GPHD8-6	8	6	90.5	14	12.5	18.5	16.5	15.5	25	18.7	2
GPHD10-8	10	8	102.5	17	15	21	18.5	16.5	29.5	52.7	2

GPKG Series



Model\Item	ΦDA	ΦDB	A	ΦPA	ΦPB	KA	KB	ΦJ	JB	JC	DC	E	Weight(g)	PCS/bag
GPKG6-4	6	4	58.5	12.5	9	16.5	14	3.2	8	34	10	17.5	8.6	5
GPKG8-6	8	6	69	15	12.5	18.5	16.5	3.2	9.5	40	12	21	13.5	5
GPKG10-8	10	8	80	18	15	21	18.5	4.3	11	48	14.5	24	20.7	5

