



MADE IN ITALY since 1972

T3-AS MAG

CB Mobile antenna
Ø7mm 0.27" Fiberglass whip
logarithmic loaded, with bottom coil

TECHNICAL DATA

Type: logarithmic loaded
Impedance: 50 Ω
Frequency range: 26.9 ... 27.5 MHz
Polarization: linear vertical
SWR @ res. freq.: ≤ 1.2
Max. power: ... 20 Watts (CW) continuous, 100 Watts (CW) short time
Bandwidth @ SWR ≤ 2: ≥ 700 kHz (65 channel)
Mounting: PM-125 PL magnetic mount
Cable Length / Type: 3.6m, 11.8 ft / RG58
Height (approx.): 620 mm, 2 ft
Weight (approx.): 400 gr, 0.9 lb

P/N 2206815.63 T3-AS MAG

AS series

CB & 10m base loaded mobile antennas
Tunable from 27 to 28.5 MHz
DC-Ground protection
17/7 PH tapered stainless steel whip

TECHNICAL DATA

Type: base loaded
Impedance: 50 Ω
Frequency range: 27 ... 28.5 MHz
Polarization: Linear vertical
SWR @ res. freq.: ≤ 1.2
Max. power:
AS 100: 100 Watts (CW) continuous, 300 Watts (CW) short time
AS 145: 150 Watts (CW) continuous, 450 Watts (CW) short time
AS 170: 200 Watts (CW) continuous, 600 Watts (CW) short time
Bandwidth @ SWR ≤ 2: AS 100 ≥ 580kHz (55 channel)
AS 145: ≥ 1240kHz (110 channel)
AS 170: ≥ 1940kHz (180 channel)
Mounting:
PL series: Whip only, connection UHF-male (PL 259)
N series: Whip + cable + N-PL mount, hole 12.5mm, 1/2in
AS-100 MAG: ... PM-100 PL, magnetic mount, 3.6 m / 11.8 ft RG58
Height (approx.) AS 100 1020 mm, 3.3 ft
AS 145 / AS 170 1400 mm, 4.6 ft / 1670 mm, 5.5 ft
Weight (approx.) 240 gr, 0.53 lb

P/N 2209005.05 AS 100 PL
P/N 2201405.05 AS 145 PL
P/N 2201605.05 AS 170 PL

P/N 2209005.23 AS 100 N
P/N 2201405.23 AS 145 N
P/N 2201605.23 AS 170 N

P/N 2209005.61 AS 100 MAG
P/N 2209006.61 AS 100 BLACK MAG



DIFFERENCE BETWEEN SERIES

PL-Series
(whip only)



To mount on
UHF female (like
magnet mount or
SO-239 connector)

(plastic cap)

N-Series
(supplied with
mount & cable)



+ N-PL mount



+ N cable



T3-AS MAG



AS-100 MAG