


LED BULB

Product&Family Code: 001 001 0006

FONIX-6




Technical Drawing



Technical Data

Voltage (V)	175-250V
Product Wattage (W)	6
Equivalence with incandescent lamp	48
Colour Render Index (Ra)	>Ra80
Colour Temperature (K)	3000K-4200K-6400K
Materials	Aluminium Housing with PMMA Diffuser
Protection Class	-
Dimmable	No
EEL	A F
Warm-up time up to 60 % of the full light output	Instant Full Light
Luminous Flux (lm)	440
Luminous Efficacy (lm/W)	73
Rated Life (hrs) Ⓢ	25,000
IP Rating	-
Power Factor	>0.5
Beam Angle ☆	110 °
Starting Time	<0.5
Number of ON-OFF cycling	x12,500

Photometric Diagram



Applications

- The luminaire is an excellent solutions for market, museum, restaurant, show room, and other spot lighting needed.



Features

- Low power consumption
- Efficient replacement for incandescent lamps
- Mercury free, no UV and IR radiation
- Instant on, 100% light output

///	12.500X ON / OFF	Start Up Time <0.5
NO UV / IR	mA 52	%85 ENERGY Saving
0,0mg	Optimally	110°
Ra >80	Warm Up %60 < 0.5 sc	PF >0.5

