

Haibike ALLTRAIL 3

MTB Fully

caramel/orange/black glossy

41

WINORA
GROUP

Bikes for Life.



Hit the trails with ease. Our ALLTRAIL 3 is the ideal eMTB for your first steps into trail riding. This touring full-suspension features a mullet setup, offering perfect traction on the climbs while remaining agile on the descents. The concept is simple yet brilliant: the 29" front wheel provides stability, while the 27.5" rear wheel lets you tackle tight corners with ease. With the Shimano 10-speed drivetrain, you'll always find the right gear, even on varied terrain. And the powerful Yamaha PW-S2 motor gives you that extra boost when you need it. Maximum comfort is provided by the SR Suntour fork, offering 140mm of travel to handle even the toughest downhills. We're confident that this eMTB will deliver maximum touring fun in any terrain, with a level of ease you've never experienced – even when things get bumpy.

€ 4299

Specification

Frame and more

Brand	Haibike
Frame	Haibike aluminium, 29"
Frame shape	MTB Fully
Model name	ALLTRAIL 3
Total perm. weight	120
Frame height	41
Fork	SR Suntour XCR34 Boost (2 Pos. Lever) 140 mm
Damper	RockShox Deluxe Select 205x57,5mm, Trunnion, DebonAir+
Head set	Acros Blocklock 164° ZS44/ZS56

Propulsion

Drive unit	Yamaha PW-S2, 250W, 25km/h, 75Nm
Charger	Yamaha Standard Charger 4A
Battery	Yamaha InTube 720Wh
Battery capacity	720
Display	Yamaha A2 Display
Engine manufacturer	Yamaha
Engine torque	75

Gear shift and brakes

Gear shift	Shimano Cues RD-U6000 10s, Shadow+, 10 gears, Cues U6000, rapidfire
Chain	Shimano CN-LG500 10s, Linkglide
Brakes	Shimano Deore BR-MT420, 4 pistons, PM, 203mm
Brake lever	Shimano BL-MT401, aluminium
Chain guide	Winning Nylon direct mount
Crank arm	Samox ISIS Alloy Crankarms

Handlebar and saddle

Saddle	Selle Royal Vivo
Handlebar	Haibike Components TheBar ++, 780 mm
Grips	Velo VLG-1751D2, MTB Grips

Wheels and wheel components

Rims	Rodi Tryp 30 Disc 32H with eyelets, eyeleted, Hollow section rim
------	--

Geometry

Seat tube length	410
Seat tube angle	74.7
Head tube length	120
Head tube angle	65.7
Chain stay length	460
Bottom bracket drop	-17
Reach	425
Seat tube offset	-23