



ARDON®
WORKWEAR
& OUTDOOR

ARDON® DIGGER O1

WORKING SHOES



DRY AIR



**DEFUSE
CONTROL**



**0%
METAL**



REFLECTIVE



ARDON®
WORKWEAR
& OUTDOOR

ARDON® DIGGER O1

WORKING SHOES

ARTICLE

G3239

MATERIAL

Upper

Lining

Sole

Toe cap

Plate

Insole

MICROFIBER / CANVAS type fabrics

MESH laminated breathable fabric

MD/rubber/TPU, glued technology

-

-

ANATOMIC FOAM anatomically shaped EVA foam

SIZE

UNIT

PACKAGE

Units in a carton

Units in a box

36-48

pair

10 pairs

1 pair

DIMENSIONS

Carton H x W x D

(cm)

Carton (cbm)

36-43

34 x 48.5 x 63

0,104

44-48

37 x 52.5 x 63

0,122

Size EUR

35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51

Insole length mm

- 238 244 251 258 264 271 278 284 291 298 304 311 318 - - -

Foot length cm

- 23,3 23,9 24,6 25,3 25,9 26,6 27,3 27,9 28,6 29,3 29,9 30,6 31,3 - - -

DESCRIPTION

Low shoes in sports design. Breathable upper is made of solid fabric and microfiber, the toe cap is reinforced with PU. Wearing comfort is increased by padding the tongue and the area around the heel and ankle, but mainly the shoes are equipped with an anatomically shaped insole, made of a material that effectively dampens the impact of the tread and ensures comfort even during long-term wear. The sole made of a combination of MD / rubber / TPU material ensures a soft tread and at the same time provides the highest level of anti-slip properties.

NORMS

(EU) 2016/425

EN ISO 20347:2012

Personal protective equipment – Occupational footwear

Category

O1 SRC

Categories

EN ISO 20347

E - energy absorption in the heel area

✓



FO - resistance to oils and fuels

✓



A - antistatic footwear

✓



SRC - resistance to slipping on ceramic floor tiles with SLS
and on steel floors with glycerin

✓



WR - upper resistant to water



Safety toe cap for toe protection



P - resistance to punctures (protective insole)



SRA - slip resistance ceramic floor tiles with SLS



HRO - resistance to contact heatup to 300 °C



HI-insulation of the bottom of the shoe against heat



CI-insulation of the bottom of the shoe against the cold



Splatters of molten metal



ESD – shoe protects against electrostatic discharge and can
be used on EPA premises



The shoes do not contain metal parts

✓



-

-

-



ARDON®
WORKWEAR
& **OUTDOOR**

CODE	EAN	CARTON WEIGHT (KG)	UNIT WEIGHT (KG)
G3239/36	8592390157331	9.70	0.970
G3239/37	8592390157348	9.80	0.980
G3239/38	8592390157355	10.10	1.101
G3239/39	8592390095077	10.20	1.020
G3239/40	8592390095084	10.50	1.050
G3239/41	8592390095091	10.80	1.080
G3239/42	8592390095107	11.20	1.120
G3239/43	8592390095114	11.40	1.140
G3239/44	8592390095121	11.75	1.175
G3239/45	8592390095138	12.10	1.210
G3239/46	8592390095145	12.30	1.230
G3239/47	8592390157362	12.80	1.280
G3239/48	8592390157379	13.30	1.330



ARDON®
WORKWEAR
& OUTDOOR





ARDON®

**WORKWEAR
& OUTDOOR**

