Fnirsi
Technology

Intelligent. Powerful. SimpleMINI

Body size is smaller than 2 fingers,
Easy to carry around.



Fnirsi-C1
PD3.0 105.00W
20.104
0.0163

2
QC/PD Detection & Trigger

Fnirsi-C1
9.10V MEM 1.0H 2.20A

3
Offline data storage

Fnirsi
Technology

Powerful PC software Driver-free installation

Data management * Protocol control * Firmware upgrade
Support monitoring and recording of voltage and current curves;
Protocol single trigger and smart trigger functions



Fnirsi
Technology

Bluetooth APP Control

By linking the Bluetooth APP,Can view voltage, current and curve in real time, and can be controlled by agreement,View 10 sets of capacity statistics and capacity calculations,At the same time, the overvoltage current alarm can be set in the APP.
NOTE: Currently only supports Android phones; Normal version without Bluetooth function.

FNIRSI-C1
VA
D+D-
STOP
CH1
CH2
Voltage
5.1899V
Current
1.8921A
Power
9.8184W
TRIGGER
BATTERY CAP
CLEAR
ALARM

Fnirsi
Technology

Comprehensive functions, Meet all your needs

All mainstream protocol detection triggers,Wave curve,
Internal resistance measurement of charging cable,
Low internal resistance,Free drive PC software, etc.

• • • **Fnirsi-C1**

- 1.3-inch high-definition TFT color screen
- Double Type-C (1 male & 1 female)
- Two-way charging
- Gravity sensor 360 degree screen rotation
- On-board temperature monitoring
- Four major mode curve detection
- V/A/W 6-bit high-precision detection
- 6.5A high current
- Apple 2.4A acceleration
- Rich fast charge protocol triggers
- PD E-Marker/DASH cable inspection
- Cable internal resistance detection
- 10 sets of output capacity & energy detection statistics
- Bluetooth APP
- PC software

Fnirsi
Technology

Technical Parameters

Accuracy: ± (a% (%) Reading + Number of words

Index	Range	Resolution	Precisio
Monitor voltage	4~24V	0.00001V	±(0.2%+2)
Monitor current	0~6.5A	0.00001A	±(0.5%+2)
Monitor power	0~130W	0.00001W	±(0.5%+2)
Load equivalent internal resistance	0~9999.9Ω	0.0001W	±(0.5%+2)
D+/D- voltage	0~3.3V	0.001V	±(1.0%+2)
Equipment temperature	°C	1°C	±(1.2%+3)
	°F	1°F	±(1.2%+4)
Capacity	0~9999.99Ah	0.00001Ah	
Energy used	0~9999.99Wh	0.00001Wh	
Internal resistance of the cable	0~9999.9Ω	0.0001Ω	
Equipment running time	99days23hours 59minute59second	1second	
Record time	999hours 59minute59second	1second	

Fnirsi
Technology

Real-time monitoring of charging voltage, current and power. Multi-interface display, Multi-data measurement

FNIRSI-C1 uses an external 16-bit ADC&PD protocol physical chip,Commonly used forthe detection and monitoring of various digital devices such as various chargers, power banks, data cables, mobile phones and laptops

• • • **Fnirsi-C1**

Charger

Data cable


Power Bank


Fast charge mobile phone


Various laptop computers

Type-C digital equipment

Automatic Detection/Triggering of multiplefast charging protocols

Protocol trigger: QC2.0, QC3.0, Huawei FCP, Huawei SCP, Samsung AFC, PD protocol
Protocol detection: APPLE2.4A, PD2.0, PD3.0, QC2.0, QC3.0,Huawei FCP, Huawei SCP, Samsung AFCMTK-PE and other fast charging protocols

Fnirsi-C1
Trigger and Detect
1 Detection
2 Qualcomm QC 2.0
3 Qualcomm QC 3.0
4 Huawei FCP
5 Huawei SCP
6 SAMSUNG AFC

🟨 Protocol detection in progress
🟩 Support the agreement
🟥 Does not support the protocol

In the "Quick Charge Trigger Interface", long press the "<< key" to enter the trigger menu,Press "OK" to enter "Quick Charge Detection Trigger Menu"After entering, you can see the automatic detection of various fast charging protocols.Do not connect any load during automatic detection,To prevent damage,After the detection is completed, "Detection Complete" will be displayed in the upper right corner.



```
V1.0              检测完成
APPLE->5V2.4A
BC1.2->DCP 5V 1.5A
QC2.0->5V 9V 12V 20V
QC3.0->20.86V Max
SAMSUNG AFC->9V 12V
HUAWEI DCP->
NONE
HUAWEI SCP->
NONE
```

Fast charge detection display diagram



```
PD3.0 105.00W
20.104V   D+2.719V
          D-2.705V
0.0163A   0.3295W
● Gear  5.00V  3.00A
    20  9.00V  3.00A
   100 12.00V  3.00A
  1000 15.00V  3.00A
Target 20.00V  5.00A
20.00V 3.3-21.0V 5.0A
```

Fast charge protocol Detection/ Trigger display diagram

Fnirsi
Technology

Mainstream protocol trigger function Interface

Meet your different needs



```
Qualcomm QC 2.0
19.981V   D+3.291V
          D-3.012V
0.0162A   0.3245W
[1] 5V    [2] 9V
[3] 12V   [4] 20V
```

Qualcomm QC2.0 trigger interface



```
Qualcomm QC 3.0
19.982V   D+0.597V
          D-3.010V
0.0163A   0.3261W
-200mV    +200mV
Now 20000mV
```

Qualcomm QC3.0 trigger interface



```
HUAWEI FCP
12.100V   D+0.593V
          D-0.008V
0.0209A   0.2536W
   [1] 5V
   [2] 9V
   [3] 12V
```

Huawei FCP trigger interface



```
HUAWEU SCP
5.4649V   D+0.593V
          D-0.008V
0.0312A   0.1706W
-20mV     +20mV
Now 05500mV
3.4-5.5V⎓5.0A 25W
```

Huawei SCP trigger interface



```
SAMSUNG AFC
12.102V   D+0.594V
          D-0.008V
0.0208A   0.2529W
[1] 9V    [2] 12V
```

Samsung AFC trigger interface



```
PD2.0 45.00W
15.056V   D+2.719V
          D-2.705V
0.0154A   0.2319W
● Gear  5.00V  3.00A
    20  9.00V  3.00A
   100 12.00V  3.00A
  1000 15.00V  3.00A
Target
15.00V
```

PD2.0 trigger interface



```
PD3.0 105.00W
20.104V   D+2.719V
          D-2.705V
0.0163A   0.3295W
● Gear  5.00V  3.00A
    20  9.00V  3.00A
   100 12.00V  3.00A
  1000 15.00V  3.00A
Target 20.00V  5.00A
20.00V 3.3-21.0V 5.0A
```

PD3.0 trigger interface