

		Key features
		★ 3MP IR bullet network camera ★ 2.8mm lens brings everything back to life ★ Efficient H.265+ compression technology ★ Clear day and night vision with 3D DNR and DWDR ★ Support PoE & DC12V
Model Number		I71EP
IP Camera		
Camera	Image Sensor	1/2.9" Progressive Scan CMOS
	Max resolution	2304*1296(3MP)
	Main Stream	50 Hz: 25 fps@(2304*1296, 1920*1080, 1280*720) 60 Hz: 25 fps@(2304*1296, 1920*1080, 1280*720)
	Substream	50 Hz: 25 fps (640*480, 640*360) 60 Hz: 25 fps (640*480, 640*360)
	Video Compression	Main stream: H.265+/H.265/H.264+/H.264 Sub-stream: H.265/H.264
	Video Bitrate	256 Kbps - 8 Mbps
	Lens	2.8 mm
	Min. Illumination	Color: 0.01 Lux @ (F2.2, AGC ON), B/W: 0 Lux with IR
	Angle of View	Horizontal FOV 94°, vertical FOV 51°, diagonal FOV 112°
	Supplement Light Type	IR
	Supplement Light Range	Up to 20 m
	Motion detection	Support
	Image Enhancement	BLC, HLC, 3D DNR
	Wide Dynamic Range	DWDR
	Protocols	TCP/IP, ICMP, DHCP, DNS, HTTP, RTP, RTSP, NTP, IGMP, IPv6, UDP, QoS
	API	Open Network Video Interface Version 18.12
	Privacy Mask	1 programmable polygon privacy masks
	General Function	Mirror, password protection, remote access
General	Ethernet	1 RJ45 10 M/100 M self-adaptive Ethernet port
	Housing	Plastic
	Color	White & Black
	Operating Power	DC 12 V± 25%, max. 5 W; PoE (802.3af), max. 6.5 W
	Operating Temperature	-22 °F – 140 °F/-30 °C – 60 °C
	Indoor/Outdoor Use	Indoor/Outdoor
	Dimension (L X W X H)	138.8 mm × 60.9 mm × 57.9 mm (5.5" × 2.4" × 2.3")
Packaging Contents	Weight	175 g (0.4 lb.)
	Camera	1
	Ethernet Cable	60 ft/18 m X2; 100 ft/30 m X2
	Mounting Screw Bag	1
	User Manual for Camera	1