

# AV1300 Gigabit Passthrough Powerline Starter Kit

Extend Reliable Gigabit Network Using Existing Electrical Wiring







4K HD video streaming and lag-free gaming



### Highlights

#### 1,300 Mbps Powerline with 2×2 MIMO<sup>+</sup>

Advanced HomePlug AV2 1,300 Mbps Powerline accompanied with 2×2 MIMO technology significantly improves data transfer rates, stability and coverage.

#### Gigabit Ethernet for Fast Connections

Gigabit Ethernet port provides reliable high-speed wired connections for game consoles, smart TVs, STB and more.





## Highlights

#### **Power Saving**

Automatically switches to "Power-Saving" mode when not in use, reducing its energy consumption by up to 85%.§



AV1300 Gigabit Passthrough Powerline Starter Kit brings internet to any area with a power outlet using your home's electrical wiring.<sup>†</sup>

• No need for new wires or drilling • Network passes through walls and floors







#### Get Reliable Gigabit Network from Any Outlet

### Features



- Ultra-fast Powerline Speed HomePlug AV2 standard compliant, high-speed data transfer rate of up to 1300 Mbps, ideal for Ultra HD streaming and online gaming
- Gigabit Ports The Gigabit Ethernet ports allow your TVs, game consoles or PCs to connect to the internet at high speeds



 300-meter Range – Up to 300 meters/1,000 feet over existing electrical wiring<sup>†</sup>



- Plug and play Plug and play, no configuration required
- No new wires No new wires, use existing electrical wiring to expand your home network
- Keep your outlet An integrated socket lets you power regular devices as normal, and a built-in noise filter prevents them from interrupting the powerline signal.
- TP-Link tpPLC Allows you to easily manage your network using the tpPLC Utility



 Pair Button – 128-bit AES encryption easily at a push of "Pair" button



• Mains Filter – Mains Filter inside the outlet reduces electrical noise interference and improves powerline communication performance



 Power Saving – Power Saving Mode helps reducing power consumption by up to 85%<sup>§</sup>

### **Specifications**

#### Hardware

- · Plug Type: EU
- Standards and Protocols: HomePlug AV2, HomePlug AV, IEEE 1901, IEEE 802.3, IEEE 802.3u, IEEE 802.3ab
- Power Consumption: Maximum: 4.9W
  - Typical: 4.6W Standby: 0.5W
- · Range: 300 meters over electrical circuit
- Interface: Gigabit Ethernet Port, Power Socket
- Button: Pair Button
- LED Indicator: Power, Powerline, Ethernet
- Dimensions (W x D x H):  $2.8 \times 1.7 \times 5.2$  in ( $72 \times 42 \times 131$  mm)





For more information, please visit

https://www.tp-link.com/home-networking/powerline/tl-pa8010p-kit/

or scan the QR code left

Specifications are subject to change without notice. TP-Link is a registered trademarks or registered trademarks of their respective holders. Copyright @2020 TP-Link Technologies Co., Ltd. All rights reserved. <sup>†</sup>Maximum Powerline signal rates are the physical rates derived from HomePlug AV/AV2 specifications. Actual Powerline data throughput and environmental factors, including electrical interference, volume of traffic and network overhead, AFCI circuit breaker, and Powerline being located in a separate circuit.

<sup>‡</sup>Compatible with all HomePlug AV and AV2 Standard Powerline adapters. This product may not be compatible with routers or gateways with firmware that has been altered, is based on open source programs, or are non-standard or outdated. <sup>§</sup>Actual power saving data will vary in different network conditions and environments.

#### Software

- Modulation Technology: OFDM (PLC)
- Encryption: Powerline Security: 128-bit AES

#### Others

- · Certification: CE, RoHS
- · Package Contents:
- 2 × TL-PA8010P
- 2 × Ethernet Cable
- Quick Installation Guide
- · System Requirements:
- System Requirements for tpPLC Utility:
- Environment:

Operating Temperature: 0°C~40°C (32°F ~104°F) Storage Temperature: -40°C~70°C (-40°F ~158°F) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing

AV1300 Gigabit Passthrough Powerline Adapter

Windows 2000/XP/2003/Vista, Windows 7/8/8,1/10, Mac, Linux

Windows XP/Vista/7/8/8.1/10 and Mac OS X (10.7 or later)

www.tp-link.com

TP-Link AV1300 Gigabit Passthrough Powerline Starter Kit TL-PA8010P KIT