

Eaton 216407

Catalog Number: 216407

Eaton Moeller® series M22 Coding part M22-XC-Y

General specifications



Product Name

Eaton Moeller® series M22 Accessory
Coding kit

Catalog Number

216407

EAN

4015081849741

Product Length/Depth

19 mm

Product Height

16 mm

Product Width

11 mm

Product Weight

0.002 kg

Certifications

UL/CSA certification not required

Catalog Notes

Not for key-operated button for master
key systems

Model Code

M22-XC-Y

Charakterytyka & Funkcje

Color

Yellow

Functions

For converting between stay-put and spring-return function

Parametry ogólne

Accessory/spare part type

Accessory

Klimatyczne warunki środowiskowe

Ambient operating temperature - min

-25 °C

Ambient operating temperature - max

70 °C

Komunikacja

Connection to SmartWire-DT

No

Styki

Force for positive opening - min

0 N

Weryfikacja projektu

Equipment heat dissipation, current-dependent P_{vid}

0 W

Heat dissipation capacity P_{diss}

0 W

Heat dissipation per pole, current-dependent P_{vid}

0 W

Rated operational current for specified heat dissipation (I_n)

0 A

Static heat dissipation, non-current-dependent P_{vs}

0 W

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

Do pobrania

Certyfikaty

[DA-DC-00004135.pdf](#)

[DA-DC-00004157.pdf](#)

DWG

[eaton-operating-m22-coding-kit-3d-drawing.eps](#)

[eaton-general-m22-coding-kit-symbol-002.eps](#)

Instrukcje montażu

[IL04716002Z](#)

mCAD model

[DA-CS-anschlag_gelb](#)

[DA-CD-anschlag_gelb](#)

Multimedia

[RMQ small E-Stop emergency-stop button](#)

System overview

[Pilot devices - selection aid](#)

10.2.4 Resistance to ultra-violet (UV) radiation

Please enquire

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

10.10 Temperature rise

Not applicable.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2023 Eaton. Wszelkie
prawa zastrzeżone.

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)