



Super Light 10W-40

SPECIFICATIONS

Engine:	gasoline, diesel
SAE:	10W-40
API:	SN / CF
ACEA:	A3/B4

APPROVALS AND CONFORMITY

MB 229.3 VW 501.01 VW 502.00 VW 505.00 BMW Longlife-01

CHARACTERISTICS

- Extrem wear protection;
- Excellent viscosity-temperature behavior;
- High oxydation- and thermo stability;
- Minimal frictional loss;
- Very high cleaning capability;
- Low volatilization loss.

EFFECTS

- Very good operating reliability;
- Excellent cold starting properties - rapid supply of all points of lubrication;
- Optimal high temperature viscosity;
- Constant operating properties;
- Maximum performance results;
- Reduced fuel consumption;
- Optimal engine cleanliness;
- Low oil consumption;
- All-year operation.

DISPOSAL

- Wolver Super Light SAE 10W-40 is assigned to category 2 of used oils and thus is free for disposal.

TYPICALS

Kinematic viscosity at 100 °C, mm²/s	14.1
Viscosity index	159
Pour point, °C	-33
Viscosity CCS at -25 °C, mPa·s	6400
TBN, mgKOH/g	8.2
Flash point, °C	212
Density at 15.6 °C, kg/m³	873

DESCRIPTION

Wolver Super Light SAE 10W-40 is a highly alloyed lightrun petrol and diesel engine oil enabling by its additives, selection of grand oils and its viscosity application an energy-saving operation of car diesel engines.

To guarantee the lowest viscosity of the SAE 10W-range as well as simultaneously a low volatilization loss.

Wolver Super Light SAE 10W-40 lightrun engine contains full synthetic components meeeting the demands of high-tech.

Utilization

- High-performance and normal four-stroke petrol engines;
- with multivalve technology;
- with turbocharging;
- with catalyst technology;
- Passenger car diesel engines;
- Suction diesel;
- CDI- HDI- and TDI-motors;
- with CDi-technology;
- Direct-injection.

Miscibility

Wolver Super Light SAE 10W-40 is fully compatible to comparable lubrications and can be mixed without any doubts. However, it is recommended to take Wolver Super Light SAE 10W-40 when refilling.

1L - Can	4105	4260360941054
4L - Can	4303	4260360940033
20L - Pail	4061	4260360940613
60L - Barrel	4191	4260360941917

208L - Barrel	4031	4260360940316
---------------	------	---------------
