

D COMPACT ENCLOSED SWITCH

Features

- High precision and long life.
- Suitable for applications demanding higher mechanical strength,
- Gasket diaphragm seal provides high environmental resistance.



Specifications

Item	Standard
Rating	10A, 125V or 250VAC
Contact Resistance	25mΩ max. (initial)
Insulation Resistance	100MΩ min. (at 500VDC)
Dielectric Strength	1,000VAC,50/60Hz for 1 minute
Service Life Mechanically:	1,000,000 operations min.
Service Life Electrically	100,000 operations min.

Product Selection


D ☐

1


1.HEAD AND ACTUATOR

- 5000:** Push plunger type
- 5020:** Roller plunger type
- 5040:** Cross Roller plunger type
- 1000:** Lever type
- 1020:** Short Lever type
- 2000:** Lever roller type
- 2020:** Short Lever roller type

Mounting Hole



Contact Configuration



HIGHLY

C9

Design, specifications are subject to change without notice.

D COMPACT ENCLOSED SWITCH


Operating Characteristics

Unit: mm

Item	Operating Characteristics	Dimensions
D5000		




OF max.	600g
RF min.	100g
PT max.	1.6 mm
OT min.	5 mm
MD max.	0.2 mm
OP	21.8± 1.2 mm
FP	--



D5020




OF max.	600g
RF min.	100g
PT max.	1.6 mm
OT min.	5 mm
MD max.	0.2 mm
OP	33.35± 1.2 mm
FP	--



D5040



OF max.	600g
RF min.	100g
PT max.	1.6 mm
OT min.	5 mm
MD max.	0.2 mm
OP	33.35± 1.2 mm
FP	--



D COMPACT ENCLOSED SWITCH

Operating Characteristics

Unit: mm

Item


Operating Characteristics

Dimensions

D2000




OF max.	195g
RF min.	28g
PT max.	8.5 mm
OT min.	3.2 mm
MD max.	2.6 mm
OP	40 ± 1 mm
FP	50 mm



D2020




OF max.	300g
RF min.	40g
PT max.	6 mm
OT min.	2 mm
MD max.	1.5 mm
OP	40 ± 1 mm
FP	46 mm



D1000



OF max.	170g
RF min.	25g
PT max.	10 mm
OT min.	4 mm
MD max.	3 mm
OP	25 ± 1 mm
FP	35 mm



D COMPACT ENCLOSED SWITCH


Operating Characteristics

Unit: mm

Item	Operating Characteristics	Dimensions
D1020		



OF max.	260g
RF min.	35g
PT max.	7 mm
OT min.	2.5 mm
MD max.	1.7 mm
OP	25±1 mm
FP	32 mm



NOTE: