

LED SURFACE LIGHT

Product&Family Code:

016 026 0018

ARINA-18




WHITE



BLACK

Technical Drawing



Technical Data


Voltage (V)	100-265V
Product Wattage (W)	18
Equivalence with incandescent lamp	144
Colour Render Index (Ra)	>Ra80
Colour Temperature (K)	3000K / 4200K / 6400K
Materials	Aluminium Die Casting Body
Protection Class	II
Dimmable	No
EEL	-
Warm-up time up to 60 % of the full light output	Instant Full Light
Luminous Flux (lm)	1300
Luminous Efficacy (lm/W)	72
Rated Life (hrs) ⌚	30.000
IP Rating	20
Power Factor	>0.5
Beam Angle	120°
Starting Time	<0.2s
Number of ON-OFF cycling	x15.000

Applications

Airport, Bathroom, Bedroom, Car Park, Cinema, Gallery, Hospital, Hotel, Kitchen, Museum etc.



Photometric Diagram



CF: C0 Plane beam angle(50%) CF: C90 Plane beam angle(50%)
C0 Plane beam angle(50%):116.7(DEG) C90 Plane beam angle(50%):116.1(DEG)

Features

- High Lumen and CRI, Good quality & Constant Current driver.
- High heat dissipation, low carbon and environmental protection.
- Innovative design of assembly structure.
- Extremely Long Life.

