



# Xitanium LED downlight and spotlight drivers

## Xitanium 36W/m 0.3-1.05A 54V S TD 230V

Xitanium LED drivers are leading the way in terms of reliability

### Product data

General Information	
Lighting Technology	LED
Operating and Electrical	
Output Current Ripple (Max)	4 %
Output Current (Max)	1050 mA
Open Circuit Voltage (DC) (Max)	60 V
Output Power (Max)	36 W
Output Power (Min)	11 W
Output Current (Min)	300 mA
Output Voltage (Max)	54 V
Output Voltage (Min)	24 V
System characteristics	
Central DC Operation	Yes
YellowDot ready	No
Temperature	
T-Case Lifetime (Max)	80 °C
T-Case Maximum (Max)	80 °C

Controls and Dimming	
Dimmable	DALI
Mechanical and Housing	
Product Length	97 mm
Overall length	97.2 mm
Overall width	43 mm
Overall height	30 mm
Dimensions (Height x Width x Depth)	30 x 43 x 97 mm
Approval and Application	
Ingress protection code	IP20 [Finger-protected]
Isolation Classification	Class I and Class II
Approval Marks	CE marking CB Certificate ENEC certificate CCC certificate RCM compliance
Output Current Set Options	DALI, NFC
Protection class IEC	Safety class I/II
Product Data	
Order product name	Xitanium 36W/m 0.3-1.05A 54V S TD 230V
Full product name	Xitanium 36W/m 0.3-1.05A 54V S TD 230V

Xitanium LED downlight and spotlight drivers

Full product code	871869976683200
Order code	929002182906
Material Nr. (12NC)	929002182906
Numerator - Quantity Per Pack	1
Net Weight (Piece)	0.088 kg

EAN/UPC - Product/Case	8718699766832
Numerator - Packs per outer box	20
EAN/UPC - Case	8718699766849

