

HWN-5216MH-16P

NVR for IP cameras

16Ch video / 16 PoE Port(s)

Max Resolution 8 Mpx / Compression

H.265+

Bandwidth 160 Mbps

Alarms / HDMI Output 4K and VGA

Space for 2 hard disks



Hikvision HiWatch Series

NVR for IP cameras

16 CH

160 Mbps bandwidth supported

Maximum resolution 8 Megapixel

16 PoE ports IEEE802.3af/at

Compression H.265+/H.265/H.264+/H.264

Outputs 4K HDMI & VGA

IP Dual Stream Access

Alarms

Mouse

Space for 2 HDD

WEB, CMS and Smartphone interface

ONVIF Compatible

Specifications

Brand	Hikvision
Range	HiWatch Series
Inputs for IP cameras	LAN port up to 16 channels
Power over Ethernet	16 port PoE Switch IEEE802.3af/at (max. 75 W)
IP compatible cameras	HIKVISION, ONVIF
Bidirectional audio	1 input / 1 RCA output
Video outputs	1 HDMI 4K, 1 VGA
Video compression format	H.265+ / H.265 / H.264+ / H.264
Display resolution	3840x2160, 2560x1440, 1920x1080, 1600x1200, 1280x1024, 1280x720, 1024x768
Decoding capacity	2CH @ 8 MP (25fps) / 4CH @ 4MP (30fps) / 8CH @ 1080p (30fps)
Total bandwidth	160 Mbps downstream / 160 Mbps upstream
Main Stream recording	8MP/6MP/5MP/4MP/3MP/1080P /UXGA /720P /VGA /4CIF /DCIF /2CIF /CIF /QCIF
Simultaneous multifunction	Pentaplex: Live, Recording, Playback, Backup and Remote Access
Alarms	4 inputs / 1 relay
Recording method	Manual, programmed, motion detection, alarm
External Backup	USB memory / HDD USB / CD-RW USB / DVR-RW USB
Internal memory	2 SATA HDD 3.5" of up to 6 TB (not included)
Communication	2 x USB 2.0 / 1 x RJ45 10/100/1000 (Ethernet)
Remote access	Web Browser, Smartphone App IVMS 4500 and PC Software IVMS 4200
Power	100-240 VAC, 50/60 Hz
Dimensions / Weight	52 (H) x 385 (W) x 315 (D) mm / 3.0 Kg (without HDD)