

PAN HEAD

Panelvit®
UNIVERSAL SCREW



Screw for fixing hardware elements for windows and doors (straps, espagnolettes, hinges and chains) and for furniture due to the **shape of the head**, capable of exerting a **strong tightening pressure**.



CASE HARDENING TREATMENT

This confers two properties to the screw:

- **very hard surface**, for biting into the fibres of the hardest wood;
- **tough, elastic core**, needed to avoid breakage of screws.

NEROPLUS® GALVANIC TREATMENT

The Neroplus® treatment has a **corrosion resistance of 1,000 hours (min.) in salt spray**, 15 times as high as that of standard black galvanizing. **Scratch-proof sealing** gives it exceptional **abrasion resistance** and **improves its aesthetics**. **Respects the environment** in compliance with the RoHS, Reach and 2000/53/EU standards.

LUBRICATION **LUBEX®**


MUSTAD antifriction treatment for **reducing fastening force by up to 50%**.



Panelvit® UNIVERSAL SCREW
NEROPLUS® - LUBRICATED
 Pan Head - PZ Recess



CE
 EN 14592:2012



	Cod. Mustad	D (mm)	L tot (mm)	L fil (mm)	Dt (mm)	Pcs. 	Pcs. 
PZ2 	PVACZC350160KNC	3,5	16	TOT	6,9	500	20000
	PVACZC350200KNC	3,5	20	TOT	6,9	500	15000
	PVACZC400200KNC	4	20	TOT	7,9	500	15000
	PVACZC400250KNC	4	25	TOT	7,9	500	15000
	PVACZC400300KNC	4	30	TOT	7,9	500	11000
	PVACZC400350KNC	4	35	TOT	7,9	500	11000
	PVACZC400400KNC	4	40	TOT	7,9	500	7500
	PVACZC500200KNC	5	20	TOT	9,8	500	7000
	PVACZC500250KNC	5	25	TOT	9,8	500	7000
	PVACZC500300KNC	5	30	TOT	9,8	500	7500
	PVACZC500350KNC	5	35	TOT	9,8	500	7000
	PVACZC500400KNC	5	40	TOT	9,8	500	7500
	PVACZC500500KNC	5	50	TOT	9,8	200	5200