

LED DOWNLIGHT

Product&Family Code:

016 092 0009

PAULA-9 3CCT



ADJUSTABLE
CUT HOLE

CCT ADJUSTABLE



CCT Selectable
by DIP Switch

3000K

4000K

6500K

Technical Data

| | |
|--|--------------------------|
| Voltage (V) | 160-265V |
| Product Wattage (W) | 9W |
| Equivalence with incandescent lamp | 72 |
| Colour Render Index (Ra) | >Ra70 |
| Colour Temperature (K) | 3CCT (3000K-4000K-6500K) |
| Materials | PS+Aluminium |
| Protection Class | II |
| Dimmable | No |
| EEI | - |
| Warm-up time up to 60 % of the full light output | Instant Full Light |
| Luminous Flux (lm) | 720 |
| Luminous Efficacy (lm/W) | 80 |
| Rated Life (hrs) ⌚ | 30.000 |
| IP Rating | 20 |
| Power Factor | >0.5 |
| Beam Angle | 120° |
| Starting Time | <0.2s |
| Number of ON-OFF cycling | x15.000 |

Applications

- Airport, Bathroom, Bedroom, Car Park, Cinema, Gallery, Hospital, Hotel, Kitchen, Museum etc.



Features

- High Lumen and CRI, Good quality & Constant Current driver.
- High heat dissipation, low carbon and environmental protection.
- SMD LED Lamp Base.

