


工艺：双面四色印刷
装订：骑马钉



工艺：双面四色印刷
装订：骑马钉

C20 M60 Y0 K0
C49 M41 Y40 K0

Growing up together with your kids

Retractable Safety Gate


Instruction Manual

Model:

SH20.006BB-140CD

SH20.006BB-180CD

SH20.006BB-280CD



**IMPORTANT! READ AND
FOLLOW THESE INSTRUCTIONS
CAREFULLY AND KEEP FOR
FUTURE REFERENCE.**

210.00 mm

145.00 mm

TABLE OF CONTENTS

SAFETY INFORMATION

Warning	03
Mountings	05

WHAT'S IN THE BOX

Parts	07
Assembly parts	08

INSTALLATION

Multiple installation methods	09
Specific assembly operations	10
Installation steps	11
Adjustable lower gate mount	13
To remove	14

FLOOR HOOK

Installation Steps	15
--------------------	----

OPERATION

How to Open and Lock	17
Cleaning Instruction	19

GENERAL

Read this instruction manual carefully and keep it in a safe place for future reference. The correct use and maintenance of this product is essential.

MAINTENANCE

Regularly check that the gate is functioning correctly, lubricate hinges and moving components with a suitable spray lubricant. Tighten and adjust mounts to ensure secure smooth operation. Inspect all components regularly and stop using if any component is damaged or missing.

WARNING

- To prevent serious injury or death, securely install gate or enclosure and use according to manufacturer's instructions.
- Incorrect installation can be **DANGEROUS**.
- DANGER** to older children if climbing over the product.
- DO NOT** use the safety barrier if any components are damaged or missing.
- The safety barrier must not be fitted across windows.
- NEVER** install this product on glass doors. Install this product against reliable doors or walls.
- If the safety barrier is used at the top of the stairs, it should not be positioned below the top level.
- If the safety barrier is used at the bottom of the stairs, it should be positioned at the front of the lowest tread possible.
- NEVER** use to keep child away from pool.
- This safety barrier is for domestic use only.
- This safety barrier has a manual closing system.
- NEVER LEAVE** the child unattended when using this product.
- Children have died or been seriously injured when gates/enclosures are not securely installed.
- DO NOT** put any goods which can be grabbed by children or pets near this product to prevent injury.
- Before using this product, carefully inspect for any loose parts and whether any parts need to be tightened.

WARNING

- This product is intended for use with children from 6 to 24 months or small to medium pets from 4.5kg(10 lbs) up to 18kg (40 lbs).
- ALWAYS check that safety barrier is correctly closed.
- Use only with the locking/latching mechanism securely engaged.
- Gate must be installed as close to the ground as possible, as per the installation guides.
- NEVER use with a child able to climb over or dislodge/open the gate or enclosure.
- **STOP USING** when a child can climb over or dislodge the gate.
- Install with this side away from child.
- Regularly check that the safety barrier is properly installed and secure.
- ALWAYS install and use as directed using all parts. Any additional or replacement parts should be obtained from after sales support.
- Barrier must be fitted between rigid surfaces such as plaster board, timber or hard wall.
- You **MUST** install wall cups to keep the gate in place. Without wall cups, child can push out and escape.
- The gate extends up from 55in to 197in wide and 34in tall, the minimum width of the opening is 27.6in, maximum width of opening is from 55in to 197in, the best width of opening is 35.4in.
- This product is a deterrent and not a substitute for adult supervision.


NEVER LEAVE children unattended. Check the gate regularly to ensure safe usage.

MOUNTINGS

Gate must be installed in a structurally sound opening. Ensure mounting surface (wall, door frame, stair posts, etc) is strong, rigid and has an even surface.

Note: If using gate on stairs, it must be placed either on the top step or on the lowest step at the bottom.

Select the appropriate fixing method from the following list.




Installation method of wooden wall:

Drill 5/64" (2mm) pilot holes and use the screws provided screwing directly into the wood.



For Installation

Screws




Installation method of Dry wall:

Drill 5mm (3/16") pilot holes, insert grey expansion rubber and secure with screws.



For Installation

Grey expansion rubber
Screws




Installation method of brick wall:

Drill 5mm (3/16") pilot holes, insert Iron Expansion and secure with screws.



For Installation

Iron Expansion
Screws



Installation method of concrete wall:

Drill 5mm (3/16") pilot holes, insert Iron Expansion and secure with screws.

This gate must only be fixed to a solid and secure surface. If unsure, check with a qualified builder or trades person that the installation you intend is suitable and safe within the chosen location.

TOOLS PREPARATION:



A. Philips head screw driver



B. Pencil




C. Power drill




D. Hammer


PLEASE SELECT THE PROPER ACCESSORIES AND A SUITABLE WALL.



Install on wooden material.



Install on a hard wall.




Do not install onto dry wood, or glass walls.

MEASUREMENT PREPARATION :


Measure the door width to ensure that the gate can be installed normally.

WHAT'S IN THE BOX

The dashed line represents the right side of the retractable safety gate, the users need to assemble it before using. Please according to the next page for specific assembly operations.







ASSEMBLY PARTS



Please according to the next page for specific assembly operations.

MULTIPLE INSTALLATION METHODS

CHOOSE THE INSTALLATION METHOD THAT SUITS YOU BEST



INSTALLATION STEPS

Note:

Thank you very much for purchasing this product. The whole installation process takes about 20 minutes. Please read the installation manual carefully, find the corresponding components and select the right location to be installed. Please prepare an electric drill, a mark pen and a screw driver.

Confirm fittings before installation.



THE RIGHT SIDE OF THE RETRACTABLE SAFETY GATE SPECIFIC ASSEMBLY OPERATIONS.




1.Insert the Iron tube into the base.



2.Drill the short screws into the iron tube with the phillips head screwdriver.




3.Insert the lower bracket into the iron tube.



4.Insert the upper fixing head into the iron tube.



5.Drill the short screws into the iron tube with the phillips head screwdriver.



6.This part is finish .


The product must be installed on the ground to better realize the separation function.



7. Install the two brackets on the gate.



8. Peel off the paper of adhesive tape from the two brackets.



9. Select the installation location, make sure the bottom of the main body door gate is on the ground.



10. Select the installation location, make sure the bottom of main body door gate is on ground. If there are baseboard on the wall. Pls slide lower bracket up to the suitable position until go around the baseboard.



11. Take out door gate from the two brackets according to the arrow.



12. Mark the holes position of the two brackets and then pull out the two brackets from wall.



13. Drill holes in the marked place with an electric drill.



14. Insert the expansion screw into the holes.



15. Drill the two brackets to wall as the holes.



16. Install gate to upper bracket as the arrow.



17. Install gate to lower bracket as the arrow, please make sure install gate to upper bracket at first then install gate to lower bracket .



18. Install the two brackets on the right side of the gate.



19. Peel off the paper of adhesive tape from the two brackets .



20. Select the installation location, make sure the bottom of the right side gate is on the ground.



20.1. If there are baseboard on the wall, pls slide lower bracket up to the suitable position until go around the baseboard.



21. Press the button according to the arrow and also put upward the gate from the two brackets at the same time.



22. Mark the holes position of the two brackets and then pull out the two brackets from wall .



23. Drill holes in the marked place with an electric drill.



24. Insert the expansion screw into the holes.



25. Drill the two brackets to wall as the holes.



26. Install the right side gate to upper bracket as the arrow.



27. Install the right side gate to lower bracket as the arrow, please make sure install gate to upper bracket at first then install gate to lower bracket finally Screw down Four screws .



28. Lift up Turn to "Unlock" position it shows green to unlock the gate



29. Pull the cloth horizontally to the opposite door frame and insert the lower end of the rod into the lower fixing heading.



30. Insert the upper end of the rod into the upper fixing head.





31. Turn to "Lock" position, it shows red to lock the gate .



32. The installation is complete, Enjoy your gate!

ADJUSTABLE LOWERGATE MOUNT

INSTALLATION



✓ Upgraded version:adjustable



✗ Others not upgraded

TO REMOVE



1. Press the button



2. When press the button and also put upward the gate from the bracket at the same time.

Installation steps for Mesh Gate Floor Hook

This is an optional accessory: You can install this accessory on the floor, if you think the mesh is loose. If it is to prevent children from passing under the safety gate, please be sure to use this product to protect the safety of children.

Confirm fittings and prepare scissors and towels before installation.



1. Choose a suitable position on the double-layer mesh, below the mesh gate, and use scissors or use a screwdriver to cut a small hole of about 0.35 inches.



2. Attach the white ring to the hole you just cut. Make sure the top and the bottom covers of the white ring closed tightly.



Note: Check that the top and bottom covers are tightly closed.



3. Put the metal ring over the white ring.

Method No.1 Punch



4. Mark the four holes of the cloth clip, drill holes of, with an electric drill as the marks.



5. Insert the expansion screw to all holes, drill the four screw to ground as the holes.



6. Done!

Method No.2 Punch-Free



4. Wipe the floor clean with a towel. Tear off the film on the surface of the double-sided tape and stick to the round transparent plastic part.



5. Tear off the other film on the surface of the tape and stick to the ground.



6. Done!

HOW TO LOCK THE GATE



Note: When gate is retracting always hold the handle and guide the gate evenly back into its original position in a horizontal direction. Never let go of handle when gate is retracting.

HOW TO GET THROUGH THE GATE



Note: When gate is retracting always hold the handle and guide the gate evenly back into its original position in a horizontal direction. Never let go of handle when gate is retracting.


CLEANING INSTRUCTIONS

Simply use a soft damp cloth to wipe gate, dry after cleaning.
Do not use chemical or abrasive cleaners.



Thank you very much for choosing our products. Please read instruction manuals carefully before using this retractable safety gate. Do not use if any part is Broken, Torn or Missing. Please retain the instruction manual for future reference.






04系列单手操作配件包说明书

INSTRUCTION MANUAL FOR ONE-HAND OPERATION

Note: Thank you very much for purchasing this product. Please read the installation manual carefully, confirm fittings before installation.



- ① Iron tube*1(Remove from the main body of the retractable safety gate)
- ② Upper fixing head*1
- ③ Lower fixing head*1
- ④ Lower bracket*1
- ⑤ Bracket*4
- ⑥ Screwdriver*1
- ⑦ Plugs*8+2 spare, Screws*8+2 spare
- ⑧ Short screws*4+1 spare screws
- ⑨ Sticker*4

INSTALLATION STEPS



1.Insert the Iron tube into the base.



2.Drill the short screws into the iron tube with the philips head screwdriver.



3.Insert the lower bracket into the iron tube.



4.Insert the upper fixing head into the iron tube.



5.Drill the short screws into the iron tube with the philips head screwdriver.




6.This part is finish .

210.00 mm

85.00 mm

工艺：双面四色印刷
装订：骑马钉



工艺：双面四色印刷
装订：骑马钉

C20M60
YOKO C49M41
Y40KO

Growing up together with your kids

Retractable Safety Gate

Instruction Manual

Modell
: SH20.006BB-
140CD SH20.006BB
-180CD
SH20.006BB-280CD



**IMPORTANT! READ AND
FOLLOW THESE INSTRUCTIONS
CAREFULLY AND KEEP FOR
FUTURE REFERENCE.**

210.00 mm

145.00 mm

TABELL AV INNEHÅLL

SÄKERHETSINFORMATION

warning	03
Mountings	05

WHAT'S IN THE BOX

parts	07
Assembly parts	08

INSTALLATION

Multipel installation metoder	09
specifika	10
monteringsoperationer	11
installation steg	13
Justerbar lägre gate	14
montera till ta bort	

GOLVKROK

installationssteg	15
-------------------	----

DRIFT

Hur att öppna och	17
Låsa	19
rengöringsinstruktion	

ALLMÄN

Läs denna bruksanvisning noggrant och förvara den på en säker plats framtiden referens . De rätta använda och underhåll av detta produkt är väsentligt .

UNDERHÅLL

Kontrollera regelbundet att porten fungerar korrekt y, smörja gångjärn och rörliga komponenter med ett lämpligt spraysmörjmedel. Dra åt och justera fästena till säkerställa säkra jämna operation . Inspektera alla komponenter regelbundet och stopp använder ifany komponent är skadad eller saknas .

WARNING

- To prevent serious injury or death, securely install gate or enclosure and use according to manufacturer's instructions.
- Incorrect installation can be **DANGEROUS**.
- DANGER** to older children if climbing over the product.
- DO NOT** use the safety barrier if any components are damaged or missing.
- The safety barrier must not be fitted across windows.
- NEVER** install this product on glass doors. Install this product against reliable doors or walls.
- If the safety barrier is used at the top of the stairs, it should not be positioned below the top level.
- If the safety barrier is used at the bottom of the stairs, it should be positioned at the front of the lowest tread possible.
- NEVER** use to keep child away from pool.
- This safety barrier is for domestic use only.
- This safety barrier has a manual closing system.
- NEVER LEAVE** the child unattended when using this product.
- Children have died or been seriously injured when gates/enclosures are not securely installed.
- DO NOT** put any goods which can be grabbed by children or pets near this product to prevent injury.
- Before using this product, carefully inspect for any loose parts and whether any parts need to be tightened.

WARNING

- This product is intended for use with children from 6 to 24 months or small to medium pets from 4.5kg(10 lbs) up to 18kg (40 lbs).
- **ALWAYS** check that safety barrier is correctly closed.
- Use only with the locking/latching mechanism securely engaged.
- Gate must be installed as close to the ground as possible, as per the installation guides.
- **NEVER** use with a child able to climb over or dislodge/open the gate or enclosure.
- **STOP USING** when a child can climb over or dislodge the gate.
- **Install** with this side away from child.
- Regularly check that the safety barrier is properly installed and secure.
- **ALWAYS** install and use as directed using **all** parts. Any additional or replacement parts should be obtained from after sales support.
- Barrier must be fitted between rigid surfaces such as plaster board, timber or hard wall.
- You **MUST** install wall cups to keep the gate in place. Without wall cups, child can push out and escape.
- The gate extends up from 55in to 197in wide and 34in tall, the minimum width of the opening is 27.6in, maximum width of opening is from 55in to 197in, the best width of opening is 35.4in.
- This product is a deterrent and not a substitute for adult supervision.

NEVER LEAVE children unattended. Check the gate regularly to ensure safe usage.

MOUNTINGS

Gate måste vara installerat i en strukturellt sund öppning . Se till monteringsytan (vägg , dörr frame , trappsteg inlägg , etc) är stark , stel och har en jämn yta .

Notera: Om du använder grind på trappor , den måste placeras antingen på bästa steg eller på de lägsta steget vid botten .

välj lämplig fixering metod från följande lista.




Installationsmetod för w ooden vägg:

Borra 5/64" (2 mm) styrhål en use the screws
nd förutsatt skruvnidirectly into the wood .



För installation
skruvar




Installationsmetod av Gipsskivor

Borra 5 mm (3/16) pilothål , infoga grå exponering gummi
och säkra med skruvar .



För installation
Gråexpansion gummi
skruvar




Installation method of brick wall:

Drill 5mm (3/16") pilot holes ,
insert Iron Expansion
and secure with screws .



For Installation
Iron Expansion
screws



Installation method of concrete wall:

Drill 5mm (3/16") pilot holes ,
insert Iron Expansion
and secure with screws .

This gate must only be fixed to a solid and secure surface. If unsure, kontrollera med en kvalificerad byggare eller trader person att installationen du avser är lämplig och säker inom valt plats.

VERKTYG FÖRBEREDELSE:




A. philips huvud
mig skruva förare


B. pencil C. elektrisk bormaskin

D. Skinka

BEHAGA VÄLJA DE RÄTT TILLBEHÖR OCH EN LÄMPLIG VÄGG,



Installera på trämaterial . Installera på a hård vägg .




Installera inte till
torka trä , eller
glasväggar.

MEASUREMENT PREPARATION :

Measure the door width to ensure that the gate can be installed normally.

WHAT'S IN THE BOX

Den streckade linje representerar höger sida av t han infällbar säkerhet gate, de användare måste monteras innan användning. snälla enligt nästa sida för specifik montering operationer.




MONTERING DELAR



snälla enligt nästa sida för specifik montering operationer.

MULTIPLE INSTALLATION METHODS

CHOOSE THE INSTALLATION METHOD THAT SUITS YOU BEST



INSTALLERA ION STEG

Notera:

Tack så mycket för att du köpte denna produkt. Helheten installation behandla tar cirka 20 minuter. behaga läs installation manuell noggrant, hitta motsvarande komponenter och välj de rätt plats till vara installerat. behaga förbereda en elektrisk borra、 a märke penna och a skruvmejsel .

bekräfta beslag före installation .



DE RÄTT SIDA AV DE INFÄLLBAR SÄKERHET PORT SPECIFIKA MONTERING OPERATIONER.




1.Insert the Iron tube into the base.



2.Drill the short screws into the iron tube with the philips head skruvmejsel.



jämrör.



4.Insert the upper fixing head till de jäm rör.



5.Drill the short screws into the iron tube with the philips head skruvmejsel.



6. Den här delen är färdig .

Produkten måste installeras på marken för att bättre förverkliga separationsfunktionen.



7. Install the two brackets on the gate.



8. skala av papperet av lim tejsa från de två fastena.



9. Select the installation location, make sure the bottom of the main body door gate is on the ground.



10. Select the installation location, make sure the bottom of main body dörrport is on jord. Om det är baseboard on the wall. Pis slide lower bracket up to the suitable position until go around the fotlist.



11. Take out door gate from the two brackets according to the arrow.



12. Mark the holes position of the two brackets and then pull out the two brackets from wall.



13. Drill holes in the marked place with an electric drill.



14. Insert the expansion screw in i hålen.



15. Drill the two brackets to wall as the holes.



16. Install gate to upper bracket as the arrow.



17. Install gate to lower bracket as pilen, se till att den är hög gate to upper bracket at first then install gate to lower bracket .



18. Install the two brackets on the right side of the gate.



19. Peel off the paper of adhesive tape from the two brackets .



20. Select the installation location, make sure the bottom of the right side gate is on the ground.



20.1. If there are baseboard on the wall, pls slide lower bracket up to the suitable position until go around the baseboard.



21. Press the button according to the arrow and also put upward the gate from the two brackets at the same time.



22. Mark the holes position of the two brackets and then pull out the two brackets from wall .



23. Drill holes in the marked place with an electric drill.



24. Insert the expansion screw into the holes.



25. Drill the two brackets to wall as the holes.



26. Install the right side gate to upper bracket as the arrow.



27. Install the right side gate to —, please make sure install gate to upper bracket at first then install gate to lower bracket finally Screw down Four screws .



28. Lift up Turn to "unlock" position it shows green to unlock the gate



29. Pull the cloth horizontally to the opposite door frame and insert the lower end of the rod into the lower fixing heading.



30. Insert the upper end of the rod into the upper fixing head.





31. Turn to "Lock" position, it shows red to lock the gate .



32. The installation is complete, Enjoy your gate!

JUSTERBAR LOWERGATE MONTERING

INSTALLATION



ATT TA BORT



1. Press the button



2. när du trycker på knapp och även sätta uppåt porten från fästet vid samtidigt.

Installation steps for Mesh Gate Floor Hook

Detta är ett valfritt tillbehör: Du kan installera detta tillbehör på de våningen, jag känner dig thinkthemesh är lös . Om det är till förhindra barn från godkänd under säkerhetsgrind , tack vara säker till använda detta produktto skydda säkerhet av barn .

bekräfta beslag och förbereda sax och handdukar före installation



1 . välja lämpligt placera på de dubbel - lager maska , under nätporten och använd scisso rs eller använd en skruvmejsel för att skära ett litet hål på ca 0,35 tum .

2 . Attach the white ring to the hole you just cut. Make sure the top and the bottom covers of the white ring closed tightly.



Obs : kontrollera att bästa och botten täcker är tätt stängd.

3 . put the metal ring over the white ring.

Method No.1 Punch



4. Mark the four holes of the cloth clip, drill holes of, with an electric drill as the marks.



5. Insert the expansion screw to all holes, drill the four screw to ground as the holes.



6. Done!

Method No.2 Punch-Free



4. Wipe the floor clean with a towel. Tear off the film on the surface of the double-sided tape and stick to the round transparent plastic part.



5. Tear off the other film on the surface of the tape and stick to the ground.



6. Done!

HUR TILL LÅSA DE GATE



Note: When gate is retracting always hold the handle and guide the gate evenly back into its original position in a horizontal direction. Never let go of handle when gate is retracting.

HUR MAN FÅR GENOM DE GATE



Note: When gate is retracting always hold the handle and guide the gate evenly back into its original position in a horizontal direction. Never let go of handle when gate is retracting.

RENGÖRING INSTRUKTIONER


använd helt enkelt en mjuk fuktig trasa till torka av grinden, torka efter rengöring. DO inte använd kemikalier eller slipmedel renare .



Tack så mycket mycket för att välja vår produkter. snälla läs instruktion handböcker försiktigt före använder detta infällbar säkerhet grind . Do inte använda om några del är Trasig , Trasig eller Saknas .
vänligen spara bruksanvisningen för framtida referens .



GJORD I KINA



04系列单手操作配件包说明书

INSTRUKTION MANUELL FÖR ENHAND DRIFT

Notera: Tack så mycket för att du köpte detta produkt. behaga läsa de installation manuell försiktigt, bekräfta beslag innan installation .

DELAR



- ① Iron tube* 1 (Ta bort från de huvud kroppen av r urtagbar säkerhet gate)
- ② övre fixering
- huvud* 1 ③ Nedre
- fixering huvud * 1 ④
- Lägre fäste * 1
- ⑤ Fäste*4
- ⑥ skruvmejsel* 1
- ⑦ pluggar *8+2 reserv, skruvar *8+2
- reserv ⑧ korta skruvar*4+1 extra fm
- varv
- ⑨ klistermärke *4

INSTALLATION O N STEG



1.Insert the iron tube into the base.



2.Drill the short screws into the iron tube with the philips head skruvmejsel.




3 Sätt in nedre fästet i järn rör.



4.Insert the upper fixing head till de järn rör.



5.Drill the short screws into the iron tube with the philips head skruvmejsel.




6. Den här delen är färdig .

210.00 mm

85.00 mm

工艺：双面四色印刷

装订：骑马钉



工艺：双面四色印刷
装订：骑马钉

C20M60
YOKO C49M41
Y40KO

Growing up together with your kids

Retractable Safety Gate

Instruction Manual

Model
o: SH20.006BB-
140CD SH20.006BB
-180CD
SH20.006BB-280CD



**IMPORTANT! READ AND
FOLLOW THESE INSTRUCTIONS
CAREFULLY AND KEEP FOR
FUTURE REFERENCE.**

210.00 mm

145.00 mm

MESA DE CONTENID O

INFORMACIÓN DE SEGURIDAD

warning	03
Mountings	05

WHAT'S IN THE BOX

parts	07
Assembly parts	08

INSTALLATION

Múltiple instalación métodos	09
operaciones de montaje	10
específicas Instalación	11
pasos	13
Ajustable más bajo puerta	14
montar a eliminar	

GANCHO DE PISO

Pasos de instalación	15
----------------------	----

OPERACIÓN

Cómo abrir y Cerrar	17
Instrucciones de limpieza	19

GENERAL

Lea este manual de instrucciones con atención y Guárdalo en un lugar seguro para el futuro referencia . El correcto usar y mantenimiento de esto producto es básico .

MANTENIMIENTO

Revisar regularmente que la puerta esté funcionando correctamente y, Lubricar las bisagras y

Componentes móviles con un lubricante en aerosol adecuado. Apriete y ajuste los soportes a asegurar seguro liso operación . Inspeccionar todo componentes regularmente y detener

usando si alguno componente es dañado o desaparecido .

WARNING

- To prevent serious injury or death, securely install gate or enclosure and use according to manufacturer's instructions.
- Incorrect installation can be **DANGEROUS**.
- DANGER** to older children if climbing over the product.
- DO NOT** use the safety barrier if any components are damaged or missing.
- The safety barrier must not be fitted across windows.
- NEVER** install this product on glass doors. Install this product against reliable doors or walls.
- If the safety barrier is used at the top of the stairs, it should not be positioned below the top level.
- If the safety barrier is used at the bottom of the stairs, it should be positioned at the front of the lowest tread possible.
- NEVER** use to keep child away from pool.
- This safety barrier is for domestic use only.
- This safety barrier has a manual closing system.
- NEVER LEAVE** the child unattended when using this product.
- Children have died or been seriously injured when gates/enclosures are not securely installed.
- DO NOT** put any goods which can be grabbed by children or pets near this product to prevent injury.
- Before using this product, carefully inspect for any loose parts and whether any parts need to be tightened.

WARNING

- This product is intended for use with children from 6 to 24 months or small to medium pets from 4.5kg(10 lbs) up to 18kg (40 lbs).
- **ALWAYS** check that safety barrier is correctly closed.
- Use only with the locking/latching mechanism securely engaged.
- Gate must be installed as close to the ground as possible, as per the installation guides.
- **NEVER** use with a child able to climb over or dislodge/open the gate or enclosure.
- **STOP USING** when a child can climb over or dislodge the gate.
- **Install** with this side away from child.
- Regularly check that the safety barrier is properly installed and secure.
- **ALWAYS** install and use as directed using **all** parts. Any additional or replacement parts should be obtained from after sales support.
- Barrier must be fitted between rigid surfaces such as plaster board, timber or hard wall.
- You **MUST** install wall cups to keep the gate in place. Without wall cups, child can push out and escape.
- The gate extends up from 55in to 197in wide and 34in tall, the minimum width of the opening is 27.6in, maximum width of opening is from 55in to 197in, the best width of opening is 35.4in.
- This product is a deterrent and not a substitute for adult supervision.

NEVER LEAVE children unattended. Check the gate regularly to ensure safe usage.

MOUNTINGS

Puerta debe ser instalado en una abertura estructuralmente sólida . Asegúrese de que la superficie de montaje (pared) , desde la puerta , escalera publicaciones , etc) es fuerte , rígido y tiene un par superficie .

Nota: Si se utiliza la puerta en las escaleras , debe colocarse ya sea en el arriba paso o en el escalón más bajo en el abajo .

Seleccione la fijación adecuada método del siguiente lista.




Método de instalación de de madera muro:

Perforar Orificios piloto de 5/64" (2 mm) y use the screws directly into the wood .



Para la instalación
tornillos




Método de instalación de Paneles de yeso

Taladro de 5 mm (3/16) agujeros piloto , insertar gris gasto goma con tornillos .




Para la instalación
Expansión gris goma
tornillos




Installation method of brick wall:

Drill 5mm (3/16") pilot holes ,
insert Iron Expansion
and secure with screws .



For Installation
Iron Expansion
screws



Installation method of concrete wall:

Drill 5mm (3/16") pilot holes ,
insert Iron Expansion
and secure with screws .

This gate must only be fixed to a solid and secure surface. If unsure, controlar con un profesional cualificado constructor o persona de oficios que la instalación tú pretender es adecuado y seguro dentro de la preferido ubicación.

HERRAMIENTAS PREPARACIÓN:





A. cabeza de philips
a mif tornillo conductor


B. lápiz il C . taladro eléctrico

D . Jamón

POR FAVOR SELECCIONAR EL ADECUADO ACCESORIOS Y UNA PARED ADECUADA



Instalar sobre material de madera . Instalar en a pared dura .




No instalar sobre
seco madera , o
paredes de cristal.

MEASUREMENT PREPARATION :


Measure the door width to ensure that the gate can be installed normally.

WHAT'S IN THE BOX

El punteado La línea representa la lado derecho de el retráctil seguridad puerta, el usuarios Es necesario ensamblarlo antes de usarlo. Por favor de acuerdo a la próximo página para conjunto específico operaciones.




ASAMBLEA REGIONES



Por favor según el siguiente página para conjunto específico operaciones.

MULTIPLE INSTALLATION METHODS

CHOOSE THE INSTALLATION METHOD THAT SUITS YOU BEST



INSTALACIÓN ION PASOS

Nota:

Muchas gracias por comprar este producto. Todo el... instalación proceso acepta alrededor de 20 minutos. por favor leer el instalación manual Con cuidado, encuentra los componentes correspondientes y seleccione el bien ubicación a ser instalado . por favor preparar un eléctrico perforar , a marca bolígrafo y a destornillador .

Confirme los accesorios antes de la instalación .



EL BIEN LADO DE EL RETRÁCTIL SEGURIDAD OPERACIONES DE MONTAJE ESPECÍFICAS DE LA PUERTA .




1.Insert the Iron tube into the base.



2.Drill the short screws into the iron tube with the philips head destornillador.



tubo de hierro.



4.Insert the upper fixing head en el hierro tubo.



5.Drill the short screws into the iron tube with the philips head destornillador.



6. Esta parte esta terminada .

El producto debe instalarse en el suelo para realizar mejor la función de separación.



7. Install the two brackets on the gate.



8. despegar el papel de adhesivo cinta de los dos soportes.



9. Select the installation location, make sure the bottom of the main body door gate is on the ground.



10. Select the installation location, make sure the bottom of main body

puerta portón is on the ground. Si allá son baseboard on the wall. Pis slide lower bracket up to the suitable position until go around the zócalo.



11. Take out door gate from the two brackets according to the arrow.



12. Mark the holes position of the two brackets and then pull out the two brackets from wall.



13. Drill holes in the marked place with an electric drill.



14. Insert the expansion screw En los agujeros.



15. Drill the two brackets to wall as the holes.



16. Install gate to upper bracket as the arrow.



17. Install gate to lower bracket as the arrow, por favor asegúrese de instalar la parte superior de la puerta a la parte superior del soporte primero, luego instale la puerta en el soporte inferior.



18. Install the two brackets on the wall.



19. Peel off the paper of adhesive tape from the two brackets .



20. Select the installation location, make sure the bottom of the right side gate is on the ground.



20.1. If there are baseboard on the wall, pls slide lower bracket up to the suitable position until go around the baseboard.



21. Press the button according to the arrow and also put upward the gate from the two brackets at the same time.



22. Mark the holes position of the two brackets and then pull out the two brackets from wall .



23. Drill holes in the marked place with an electric drill.



24. Insert the expansion screw into the holes.



25. Drill the two brackets to wall as the holes.



26. Install the right side gate to upper bracket as the arrow.



27. Install the right side gate to —, please make sure install gate to upper bracket at first then install gate to lower bracket finally Screw down Four screws .



28. Lift up Turn to "unlock" position it shows green to unlock the gate



29. Pull the cloth horizontally to the opposite door frame and insert the lower end of the rod into the lower fixing heading.



30. Insert the upper end of the rod into the upper fixing head.





31. Turn to "Lock" position, it shows red to lock the gate .



32. The installation is complete, Enjoy your gate!

AJUSTABLE MONTAJE DE PUERTA IN **INSTALLATION**



PARA QUITAR



1. Press the button



2. Al presionar el botón y también poner hacia arriba la puerta de el soporte al mismo tiempo.

Installation steps for Mesh Gate Floor Hook

Este es un accesorio opcional: puedes instalar este accesorio en el piso, te lo agradezco thinkthemesh es suelto . Si él es a prevenir niños de paso debajo de puerta de seguridad , por favor ser seguro a usar este producto a proteger seguridad de niños .

confirmar guarniciones y preparar tijeras v toallas antes Instalación .



1 . elige no adecuado posición en el doble capa malla , debajo de la puerta de malla , y utilizar tijeras o Utilice un destornillador para cortar un pequeño orificio de aproximadamente 0,35 mm . pulgadas

2 . Attach the white ring to the hole you just cut. Make sure the top and the bottom covers of the white ring closed tightly.



Nota : compruebe que arriba y abajo cubiertas son herméticamente cerrado.

3 . put the metal ring over the white ring.

Method No.1 Punch



4. Mark the four holes of the cloth clip, drill holes of, with an electric drill as the marks.



5. Insert the expansion screw to all holes, drill the four screw to ground as the holes.



6. Done!

Method No.2 Punch-Free



4. Wipe the floor clean with a towel. Tear off the film on the surface of the double-sided tape and stick to the round transparent plastic part.



5. Tear off the other film on the surface of the tape and stick to the ground.



6. Done!

CÓMO A CERRAR EL PUERTA



Note: When gate is retracting always hold the handle and guide the gate evenly back into its original position in a horizontal direction. Never let go of handle when gate is retracting.

CÓMO LLEGAR A TRAVÉS DE EL PUERTA



Note: When gate is retracting always hold the handle and guide the gate evenly back into its original position in a horizontal direction. Never let go of handle when gate is retracting.

LIMPIEZA INSTRUCCIONES

simplemente use un suave paño húmedo para Limpiar la puerta y secarla después limpieza. HACER no utilizar productos químicos o abrasivos limpiadores .




Muchas gracias Muchísimas gracias por elegirnos productos. por favor lea instrucción manuales con cuidado antes usando este retráctil seguridad puerta . Hacer no usar si cualquier parte es Roto , Rasgado o Desaparecido .

Conserve el manual de instrucciones para referencia futura .



HECHO EN
PORCELANA



04系列单手操作配件包说明书

210.00 mm

INSTRUCCIÓN MANUAL
PARA UNA MANO
OPERACIÓN

Nota: Muchas gracias por comprar esto. producto. por favor leer el instalación manual con cuidado, Confirmar los ajustes antes Instalación .

REGIONES

①



① Itubo de ron* 1(Quitar de el principal cuerpo de la seguridad retráctil puerta)

2 fijación superior
cabeza* 1 ③ Fijación
inferior cabeza * 1 ④
Más bajo soporte * 1
⑤ Soporte*4
⑥ destornillador* 1
⑦ enchufes *8+2 de repuesto, tornillos
*8+2 de repuesto ⑧ tornillos
cortos*4+1 tornillos de repuesto
⑨ pegatina *4

INSTALACIÓN PASOS



1.Insert the iron tube into the base.



2.Drill the short screws into the iron tube with the philips head destornillador.



3 Insertar el soporte inferior en el hierro tubo.



4.Insert the upper fixing head en el hierro tubo.



5.Drill the short screws into the iron tube with the philips head destornillador.




6. Esta parte esta terminada .

85 .00 mm

工艺：双面四色印刷

装订：骑马钉



工艺：双面四色印刷
装订：骑马钉

C20M60
YOKO C49M41
Y40KO

Growing up together with your kids

Retractable Safety Gate

Instruction Manual

Modell
o: SH20.006BB-
140CD SH20.006BB
-180CD
SH20.006BB-280CD



**IMPORTANT! READ AND
FOLLOW THESE INSTRUCTIONS
CAREFULLY AND KEEP FOR
FUTURE REFERENCE.**

210.00 mm

145.00 mm

TAVOLO DI CONTENU TO

INFORMAZIONI SULLA SICUREZZA

warning	03
Mountings	05

WHAT'S IN THE BOX

parts	07
Assembly parts	08

INSTALLATION

Multiplo installazione metodi	09
operazioni di assemblaggio	10
specifiche I installazione	11
passi	13
Regolabile inferiore cancello	14
montare a rimuovere	

GANCIO DA PAVIMENTO

Ifasi di installazione	15
------------------------	----

OPERAZIONE

Come per aprire e	17
Serratura Istruzioni	19
per la pulizia	

GENERALE

attentamente questo manuale di istruzioni e conservalo in un posto sicuro per il futuro riferimento . Il corretto utilizzo E manutenzione di questo prodotto È essenziale .

MANUTENZIONE

Controllare regolarmente che il cancello funzioni correttamente e, lubrificare le cerniere e componenti mobili con un lubrificante spray adatto. Serrare e regolare i supporti per garantire sicuro liscio operazione . Ispezionare Tutto componenti regolarmente E fermare usando se qualsiasi componente È danneggiato O mancante .

WARNING

- To prevent serious injury or death, securely install gate or enclosure and use according to manufacturer's instructions.
- Incorrect installation can be **DANGEROUS**.
- DANGER** to older children if climbing over the product.
- DO NOT** use the safety barrier if any components are damaged or missing.
- The safety barrier must not be fitted across windows.
- NEVER** install this product on glass doors. Install this product against reliable doors or walls.
- If the safety barrier is used at the top of the stairs, it should not be positioned below the top level.
- If the safety barrier is used at the bottom of the stairs, it should be positioned at the front of the lowest tread possible.
- NEVER** use to keep child away from pool.
- This safety barrier is for domestic use only.
- This safety barrier has a manual closing system.
- NEVER LEAVE** the child unattended when using this product.
- Children have died or been seriously injured when gates/enclosures are not securely installed.
- DO NOT** put any goods which can be grabbed by children or pets near this product to prevent injury.
- Before using this product, carefully inspect for any loose parts and whether any parts need to be tightened.

WARNING

- This product is intended for use with children from 6 to 24 months or small to medium pets from 4.5kg(10 lbs) up to 18kg (40 lbs).
- **ALWAYS** check that safety barrier is correctly closed.
- Use only with the locking/latching mechanism securely engaged.
- Gate must be installed as close to the ground as possible, as per the installation guides.
- **NEVER** use with a child able to climb over or dislodge/open the gate or enclosure.
- **STOP USING** when a child can climb over or dislodge the gate.
- **Install** with this side away from child.
- Regularly check that the safety barrier is properly installed and secure.
- **ALWAYS** install and use as directed using **all** parts. Any additional or replacement parts should be obtained from after sales support.
- Barrier must be fitted between rigid surfaces such as plaster board, timber or hard wall.
- You **MUST** install wall cups to keep the gate in place. Without wall cups, child can push out and escape.
- The gate extends up from 55in to 197in wide and 34in tall, the minimum width of the opening is 27.6in, maximum width of opening is from 55in to 197in, the best width of opening is 35.4in.
- This product is a deterrent and not a substitute for adult supervision.

NEVER LEAVE children unattended. Check the gate regularly to ensure safe usage.

MOUNT INGLESE

Cancello deve essere installato In un'apertura strutturalmente solida . Assicurare la superficie di montaggio (parete , telaio della porta , scala post , ecc.) è forte , rigido E ha un pari superficie .

Nota: Se si utilizza il cancelletto sulle scale , deve essere posizionato sia sul superiore fare un passo o su IL gradino più basso al metter il fondo a .

selezionare il fissaggio appropriato metodo dal seguente lista.

Metodo di installazione di di legno parete:




Trapano Fori pilota da 5/64" (2 mm) E fornito avvitatore directly into the wood .



Per l'installazione
viti

Metodo di installazione Di cartongesso



Trapano da 5 mm (3/16) fori pilota , inserisci grigio espansione gomma e sicuro con viti .




Per l'installazione
Espansione grigia gomma
viti


Installation method of brick wall:



Drill 5mm (3/16") pilot holes , insert Iron Expansion and secure with screws .



For Installation
Iron Expansion
screws



Installation method of concrete wall:

Drill 5mm (3/16") pilot holes , insert Iron Expansion and secure with screws .

This gate must only be fixed to a solid and secure surface. If unsure, controllo con una qualificata costruttore o persona che si occupa dell'installazione Voi intendere è adatto e sicuro all'interno del scelto posizione.

UTENSILI PREPARAZIONE:




UN. testa di Philips
Prosciutto MeF vite autista


B. matita il C. trapano elettrico

D.

PER FAVORE SELEZIONARE IL CORRETTO ACCESSORI E UN MURO ADATTO



Installare su materiale in legno . Installa su UN muro duro .



Non installare su
Asciutto legna o pareti
di vetro.


MEASUREMENT PREPARATION :

Measure the door width to ensure that the gate can be installed normally.


WHAT'S IN THE BOX

Il tratteggiato la linea rappresenta il lato destro di il retrattile sicurezza cancello, IL utenti è necessario montarlo prima dell'uso. per favore secondo il

Prossimo pagina per assemblaggio specifico operazioni.




ASSEMBLEA PARTI



per favore secondo il prossimo pagina per assemblaggio specifico operazioni.

MULTIPLE INSTALLATION METHODS

CHOOSE THE INSTALLATION METHOD THAT SUITS YOU BEST



INSTALLAZIONE IOE FASI

Nota:

Grazie mille per aver acquistato questo prodotto. L'intero installazione processo prende circa 20 minuti. Per favore leggere il installazione manuale con attenzione, trova i componenti corrispondenti e seleziona IL Giusto posizione A Essere installato. Per favore preparare UN elettrico trapano, UN segno penna E UN cacciavite.

verificare i raccordi prima dell'installazione.



IL GIUSTO LATO DI IL RETRATTILE SICUREZZA OPERAZIONI DI MONTAGGIO SPECIFICHE DEL CANCELLO.




1. Insert the Iron tube into the base.



2. Drill the short screws into the iron tube with the philips head cacciavite.



tubo di ferro.



4. Insert the upper fixing head in IL ferro tubo.



5. Drill the short screws into the iron tube with the philips head cacciavite.



6. Questa parte è finita.

Per realizzare al meglio la funzione di separazione, il prodotto deve essere installato a terra.



7. Install the two brackets on the gate.



8. staccare la carta di adesivo nastro dalle due parentesi.



9. Select the installation location, make sure the bottom of the main body door gate is on the ground.



10. Select the installation location, make sure the bottom of main body porta cancello is on terra. Se L'è Sono baseboard on the wall. Pis slide lower bracket up to the suitable position until go around the battiscopa.



11. Take out door gate from the two brackets according to the arrow.



12. Mark the holes position of the two brackets and then pull out the two brackets from wall.



13. Drill holes in the marked place with an electric drill.



14. Insert the expansion screw nei buchi.



15. Drill the two brackets to wall as the holes.



16. Install gate to upper bracket as the arrow.



17. Install gate to lower bracket as la freccia, assicurati che sia alta gate to upper bracket at first then install gate to lower bracket .



18. Install the two brackets on the right side of the gate.



19. Peel off the paper of adhesive tape from the two brackets .



20. Select the installation location, make sure the bottom of the right side gate is on the ground.



20.1. If there are baseboard on the wall, pls slide lower bracket up to the suitable position until go around the baseboard.



21. Press the button according to the arrow and also put upward the gate from the two brackets at the same time.



22. Mark the holes position of the two brackets and then pull out the two brackets from wall .



23. Drill holes in the marked place with an electric drill.



24. Insert the expansion screw into the holes.



25. Drill the two brackets to wall as the holes.



26. Install the right side gate to upper bracket as the arrow.



27. Install the right side gate to lower bracket, please make sure install gate to upper bracket at first then install gate to lower bracket finally Screw down Four screws .



28. Lift up Turn to "unlock" position it shows green to unlock the gate



29. Pull the cloth horizontally to the opposite door frame and insert the lower end of the rod into the lower fixing heading.




30. Insert the upper end of the rod into the upper fixing head.



31. Turn to "Lock" position, it shows red to lock the gate .



32. The installation is complete, Enjoy your gate!



PER RIMUOVERE



1. Press the button



2. quando si preme il tasto
pulsante e anche Mettere
verso l'alto il
cancello da la staffa
al
allo stesso tempo.

Installation steps for Mesh Gate Floor Hook

Questo è un accessorio opzionale: puoi installare questo accessorio su IL pavimento, io fyou pensatemi È sciolto . Se Esso È A impedire bambini da passando sotto il cancelletto di sicurezza , per favore Essere Sicuro A utilizzo Questo prodotto proteggere il sicurezza dei bambini .

confermare raccordi E preparare forbici E asciugamani Prima installazione .



1 . scegliere adatto posizione SU IL doppio strato maglia , sotto il cancello a maglie , e utilizzare sicisso rs o utilizzare un cacciavite per tagliare un piccolo foro di circa 0,35 pollici .

2 . Attach the white ring to the hole you just cut. Make sure the top and the bottom covers of the white ring closed tightly.



Nota : verificare che superiore E metter il fondo a coperture Sono ben chiuso.

3 . put the metal ring over the white ring.

Method No.1 Punch



4. Mark the four holes of the cloth clip, drill holes of, with an electric drill as the marks.



5. Insert the expansion screw to all holes, drill the four screw to ground as the holes.



6. Done!

Method No.2 Punch-Free



4. Wipe the floor clean with a towel. Tear off the film on the surface of the double-sided tape and stick to the round transparent plastic part.



5. Tear off the other film on the surface of the tape and stick to the ground.



6. Done!

OPERATION

COME A SERRATURA IL CANCELLO



Note: When gate is retracting always hold the handle and guide the gate evenly back into its original position in a horizontal direction. Never let go of handle when gate is retracting.

COME ARRIVARE ATTRAVERSO IL CANCELLO



Note: When gate is retracting always hold the handle and guide the gate evenly back into its original position in a horizontal direction. Never let go of handle when gate is retracting.

PULIZIA ISTRUZIONI


usa semplicemente un morbido panno umido per pulire il cancello, asciugare Dopo pulizia. FARE non utilizzare prodotti chimici o abrasivi pulitori .



Grazie mille molto per aver scelto il nostro prodotti. si prega di leggere istruzione manuali accuratamente Prima usando Questo retrattile sicurezza cancello . Fare non utilizzo Se Qualunque parte È Rotto , Strappato O Mancante .
si prega di conservare il manuale di istruzioni per riferimento futuro .



FATTO IN CINA



04系列单手操作配件包说明书

ISTRUZIONI MANUALE PER CON UNA MANO OPERAZIONE

Nota: Grazie mille per aver acquistato questo prodotto. Per favore Leggere IL installazione manuale accuratamente, confermare i raccordi prima installazione .

PARTI



① Itubo di ferro* 1(Rimuovi da IL principale corpo del sicurezza retrattile cancello)

② fissaggio superiore

Testa* 1 3. Fissaggio

inferiore Testa * 1 ④

Inferiore parentesi * 1

⑤ Staffa*4

⑥ cacciavite* 1

⑦ spine *8+2 di riserva, viti *8+2 di

scorta ⑧ viti corte*4+1 sc di riserva

⑨ adesivo *4

INSTALLAZIONE PASSAGGI



1.Insert the Iron tube into the base.



2.Drill the short screws into the iron tube with the philips head cacciavite.



3 Inserisci il staffa inferiore nella ferro tubo.



4.Insert the upper fixing head in IL ferro tubo.



5.Drill the short screws into the iron tube with the philips head cacciavite.




6. Questa parte è finita .

210.00 mm

85.00 mm

工艺：双面四色印刷

Tłumaczenie polskie：骑马钉



工艺：双面四色印刷
装订：骑马钉

C20M60
YOK C49M41
Y40KO

Growing up together with your kids

Retractable Safety Gate

Instruction Manual

Model:

SH20.006BB-140CD
SH20.006BB-180CD
SH20.006BB-280CD



**IMPORTANT! READ AND
FOLLOW THESE INSTRUCTIONS
CAREFULLY AND KEEP FOR
FUTURE REFERENCE.**

210.00 mm

145.00 mm

TABELA Z ZAWARTO ŚĆ

INFORMACJE DOTYCZĄCE BEZPIECZEŃSTWA

warning	03
Mountings	05

WHAT'S IN THE BOX

parts	07
Assembly parts	08

INSTALLATION

Wiele instalacja metody	09
konkretne operacje	10
montażowe I instalacja	11
kroki	13
Nastawny niżej brama	14
zamontować do usunąć	

HAK PODŁOGOWY

11kroki instalacji	15
--------------------	----

DZIAŁANIE

Jak otworzyć i Zamek	17
Instrukcja czyszczenia	19

OGÓLNY

Przeczytaj uważnie tę instrukcję obsługi i przechowuj w bezpiecznym miejscu na przyszłość odniesienie . prawidłowy używać I konserwacja tego produkt Jest niezbędny .

KONSERWACJA

Regularnie sprawdzaj że brama działa prawidłowo tak, nasmarować zawiasy i ruchome elementy za pomocą odpowiedniego smaru w sprayu. Dokręć i wyreguluj mocowania, aby zapewnić bezpieczny gładki operacja . Sprawdzaj Wszystko składniki regularnie I zatrzymywać się używając jeśliły część Jest uszkodzony Lub zaginiony .

WARNING

- To prevent serious injury or death, securely install gate or enclosure and use according to manufacturer's instructions.
- Incorrect installation can be **DANGEROUS**.
- DANGER** to older children if climbing over the product.
- DO NOT** use the safety barrier if any components are damaged or missing.
- The safety barrier must not be fitted across windows.
- NEVER** install this product on glass doors. Install this product against reliable doors or walls.
- If the safety barrier is used at the top of the stairs, it should not be positioned below the top level.
- If the safety barrier is used at the bottom of the stairs, it should be positioned at the front of the lowest tread possible.
- NEVER** use to keep child away from pool.
- This safety barrier is for domestic use only.
- This safety barrier has a manual closing system.
- NEVER LEAVE** the child unattended when using this product.
- Children have died or been seriously injured when gates/enclosures are not securely installed.
- DO NOT** put any goods which can be grabbed by children or pets near this product to prevent injury.
- Before using this product, carefully inspect for any loose parts and whether any parts need to be tightened.

WARNING

- This product is intended for use with children from 6 to 24 months or small to medium pets from 4.5kg(10 lbs) up to 18kg (40 lbs).
- **ALWAYS** check that safety barrier is correctly closed.
- Use only with the locking/latching mechanism securely engaged.
- Gate must be installed as close to the ground as possible, as per the installation guides.
- **NEVER** use with a child able to climb over or dislodge/open the gate or enclosure.
- **STOP USING** when a child can climb over or dislodge the gate.
- **Install** with this side away from child.
- Regularly check that the safety barrier is properly installed and secure.
- **ALWAYS** install and use as directed using **all** parts. Any additional or replacement parts should be obtained from after sales support.
- Barrier must be fitted between rigid surfaces such as plaster board, timber or hard wall.
- You **MUST** install wall cups to keep the gate in place. Without wall cups, child can push out and escape.
- The gate extends up from 55in to 197in wide and 34in tall, the minimum width of the opening is 27.6in, maximum width of opening is from 55in to 197in, the best width of opening is 35.4in.
- This product is a deterrent and not a substitute for adult supervision.

NEVER LEAVE children unattended. Check the gate regularly to ensure safe usage.

MOUNTING

Brama musi być zainstalowany W otwór o solidnej konstrukcji . Zapewnij powierzchnię montażową (ściana) , rama drzwi , schodek posty , itp) jest silny , sztywny I ma nawet powierzchnia .

Notatka: Jeśli używasz bramki na schodach , musi być umieszczony albo na szczycet krok lub na ten najniższy stopień na spód .

wybierz odpowiednie mocowanie metoda z poniższego lista.




Metoda instalacji drewno ściana:

Wiertarka Otwory pilotażowe use the screws
5/64"(2mm) I zapewnić into the wood .
śrubowanie



Do instalacji
śruby



Metoda instalacji z Płyta gipsowo-kartonowa

Wiertło 5mm (3/16) otwory pilotażowe , wstaw szary
rozszerzenie guma i zabezpiecz z śruby .




Do instalacji

Szara ekspansja guma
śruby




Installation method of brick wall:

Drill 5mm (3/16") pilot holes ,
insert Iron Expansion
and secure with screws .



For Installation

Iron Expansion
screws



Installation method of concrete wall:

Drill 5mm (3/16") pilot holes ,
insert Iron Expansion
and secure with screws .

This gate must only be fixed to a solid and secure surface. If unsure, sprawdzać z kwalifikacją budowniczy lub osoba handlująca , że instalacja Ty zamierzać jest odpowiedni i bezpieczny w ramach wybrany lokalizacja.

NARZEDZIA PRZYGOTOWANIE:




A. głowica philips
Szylnka Ja


B. ołówek il C . wiertarka elektryczna
śruba kierowca

D .

PROSZĘ WYBIERAĆ TO WŁAŚCIWY AKCESORIA I
ODPOWIEDNIA ŚCIANA ,



Montaż na materiale drewnianym . Zainstaluj na A twarda ściana .




Nie instaluj na suchy
drewno lub szklane
ściany.

MEASUREMENT PREPARATION :


Measure the door width to ensure that the gate can be installed normally.

WHAT'S IN THE BOX

Przerywana linia przedstawia prawa strona chowany
 bezpieczeństwo brama, ten użytkownicy Przed użyciem należy go
 złożyć. proszę zgodnie z
 Następny strona dla konkretny zestaw operacje.




MONTAŻ STRONY



proszę zgodnie z następnym strona dla montaż specjalny operacje.

MULTIPLE INSTALLATION METHODS

CHOOSE THE INSTALLATION METHOD THAT SUITS YOU BEST



KROKI INSTALACJI

Notatka:

Dziękuję bardzo za zakup tego produktu. Całość instalacji proces bierze około 20 minut. Proszę przeczytać instrukcję podrecznik ostrożnie, znaleźć odpowiednie komponenty i wybrać ten prawidłowy lokalizacja do być zainstalowany. Proszę przygotować jakiś elektryczny wiertarka, a ocena pióro i śrubokręt.

Przed montażem należy sprawdzić poprawność montażu.



TO PRAWIDŁOWY STRONA Z TO WYSUWANY
BEZPIECZEŃSTWO OPERACJE MONTAŻOWE
DOTYCZĄCE BRAMY.




1. Insert the Iron tube into the base.



2. Drill the short screws into the iron tube with the philips head screwdriver.



rura żelazna.



4. Insert the upper fixing head do ten żelazo rura.



5. Drill the short screws into the iron tube with the philips head screwdriver.



6. Ta część jest skończona.

Aby lepiej zrealizować funkcję separacji, produkt musi zostać zainstalowany na podłożu.



7. Install the two brackets on the gate.



8. tracić korę papier klejący taśmą z dwóch nawiasów.



9. Select the installation location, make sure the bottom of the main body door gate is on the ground.



10. Select the installation location, make sure the bottom of main body brama drzwiowa is on ground. Jeśli Tam Czy baseboard on the wall. Pis slide lower bracket up to the suitable position until go around the listwa przypodłogowa.



11. Take out door gate from the two brackets according to the arrow.



12. Mark the holes position of the two brackets and then pull out the two brackets from wall.



13. Drill holes in the marked place with an electric drill.



14. Insert the expansion screw do dziur.



15. Drill the two brackets to wall as the holes.



16. Install gate to upper bracket as the arrow.



17. Install gate to lower bracket as strzałka, proszę upewnij się, że jest występną side of the gate. install gate to upper bracket at first then install gate to lower bracket .



18. Install the two brackets on the gate.



19. Peel off the paper of adhesive tape from the two brackets .



20. Select the installation location, make sure the bottom of the right side gate is on the ground.



20.1. If there are baseboard on the wall, pls slide lower bracket up to the suitable position until go around the baseboard.



21. Press the button according to the arrow and also put upward the gate from the two brackets at the same time.



22. Mark the holes position of the two brackets and then pull out the two brackets from wall .



23. Drill holes in the marked place with an electric drill.



24. Insert the expansion screw into the holes.



25. Drill the two brackets to wall as the holes.



26. Install the right side gate to upper bracket as the arrow.



27. Install the right side gate to —, please make sure install gate to upper bracket at first then install gate to lower bracket finally Screw down Four screws .



28. Lift up Turn to "unlock" position it shows green to unlock the gate



29. Pull the cloth horizontally to the opposite door frame and insert the lower end of the rod into the lower fixing heading.




30. Insert the upper end of the rod into the upper fixing head.



31. Turn to "Lock" position, it shows red to lock the gate .



32. The installation is complete, Enjoy your gate!



USUNĄĆ



1. Press the button



2. po naciśnięciu przycisk i również umieść w górę brama z wspornik w tym samym czasie.

Installation steps for Mesh Gate Floor Hook


Jest to opcjonalne akcesorium: Możesz zainstalować to akcesorium na ten podłoga, gdybyś pomyślnie Jest luźny . Jeśli To Jest Do zapobiegać dzieci z przechodzący pod proszę o bramkę bezpieczeństwa Być Jasne Do używać Ten produkt do chronić bezpieczeństwo dzieci .

potwierdzać armatura I przygotowywać nożyczki I ręczniki zanim instalacja .



1. Wybierz odpowiednią pozycję NA ten dwuwarstwowy oczko , poniżej bramki siatkowej i użyj nożyc lub użyj śrubokręta, aby wyciąć mały otwór o średnicy około 0,35 cala .

2 . Attach the white ring to the hole you just cut. Make sure the top and the bottom covers of the white ring closed tightly.



Uwaga : sprawdź, czy szczyt I spód okładki Czy szczelnie zamknięte.

3 . put the metal ring over the white ring.

Method No.1 Punch



4. Mark the four holes of the cloth clip, drill holes of, with an electric drill as the marks.



5. Insert the expansion screw to all holes, drill the four screws to ground as the holes.



6. Done!

Method No.2 Punch-Free



4. Wipe the floor clean with a towel. Tear off the film on the surface of the double-sided tape and stick to the round transparent plastic part.



5. Tear off the other film on the surface of the tape and stick to the ground.



6. Done!

JAK DO ZAMEK TO BRAMA



Note: When gate is retracting always hold the handle and guide the gate evenly back into its original position in a horizontal direction. Never let go of handle when gate is retracting.

JAK DOJŚĆ POPRZEZ TO BRAMA



Note: When gate is retracting always hold the handle and guide the gate evenly back into its original position in a horizontal direction. Never let go of handle when gate is retracting.

CZYSZCZENIE INSTRUKCJE


po prostu użyj miękkiego wilgotna szmatka do wytrzeć
bramę, osuszyć Po czyszczenie. DO nie stosować środki
chemiczne lub ściernie sprzątacze .



Dziękuję bardzo wiele za wybranie naszego produkty. proszę przeczytać
instrukcja instrukcje ostrożnie zanim używając Ten chowany
bezpieczeństwo brama . Zrób nie używać Jeśli każdy część Jest
Złamany , Rozdarty Lub Zaginiony .
proszę zachować instrukcję obsługi odniesienie do przyszłości .



ZROBIONY W CHINY



04系列单手操作配件包说明书

INSTRUKCJA PODRĘCZNIK DLA JEDNORĘCZNY DZIAŁANIE

Notatka: Dziękuję bardzo za zakup tego produktu. Proszę Czytać ten instalacja podręcznik ostrożnie, potwierdź dopasowanie przed instalacja .



① Irura ronowa* 1(Usuń z ten główny ciało chowany bezpiecznik brama)

② mocowanie górne

głowa* 1 ③

Mocowanie dolne

głowa* 1 ④ Niżej

nawias* 1

⑤ Uchwyt*4

⑥ śrubokręt* 1

⑦ wtyczki*8+2 zapasowe, śruby*8+2

zapasowe ⑧ krótkie śruby*4+1

zapasowe śruby

⑨ naklejka*4

INSTALACJA KROKI



1.Insert the iron tube into the base.



2.Drill the short screws into the iron tube with the philips head śrubokręt.



3 Włóż dolny wspornik do żelazo rura.



4.Insert the upper fixing head do ten żelazo rura.



5.Drill the short screws into the iron tube with the philips head śrubokręt.




6. Ta część jest skończona .

210.00 mm

85.00 mm

工艺：双面四色印刷

装订：骑马钉



工艺：双面四色印刷
装订：骑马钉

C20M60
YOKO C49M41
Y40KO

Growing up together with your kids

Retractable Safety Gate

Instruction Manual

Modell
: SH20.006BB-
140CD SH20.006BB
-180CD
SH20.006BB-280CD



**IMPORTANT! READ AND
FOLLOW THESE INSTRUCTIONS
CAREFULLY AND KEEP FOR
FUTURE REFERENCE.**

210.00 mm

145.00 mm

TISCH VON INHALT

SICHERHEITSHINWEISE

warning	03
Mountings	05

WHAT'S IN THE BOX

parts	07
Assembly parts	08

INSTALLATION

Mehrere Installation	09
Methoden spezifische	10
Montagevorgänge	11
Installation Schritte	13
Einstellbar untere Tor montieren an entfernen	14

BODENHAKEN

Installationsschritte	15
-----------------------	----

BETRIEB

Wie zu öffnen und Sperren	17
Reinigungsanleitung	19

ALLGEMEIN

Lesen Sie diese Bedienungsanleitung sorgfältig durch und Bewahren Sie es an einem sicheren Ort auf für die Zukunft Referenz . Die richtig verwenden Und Wartung davon Produkt Ist essentiell .

WARTUNG

Regelmäßig prüfen dass das Tor ordnungsgemäß funktioniert ja, Scharniere schmieren und beweglichen Komponenten mit einem geeigneten Sprühschmiermittel.
Festziehen und justieren Sie die Halterungen sicherstellen sicher glatt Betrieb .
Überprüfen alle Komponenten regelmäßig Und stoppen mit wenn überhaupt Komponente Ist beschädigt oder fehlen .

WARNING

- To prevent serious injury or death, securely install gate or enclosure and use according to manufacturer's instructions.
- Incorrect installation can be **DANGEROUS**.
- **DANGER** to older children if climbing over the product.
- **DO NOT** use the safety barrier if any components are damaged or missing.
- The safety barrier must not be fitted across windows.
- **NEVER** install this product on glass doors. Install this product against reliable doors or walls.
- If the safety barrier is used at the top of the stairs, it should not be positioned below the top level.
- If the safety barrier is used at the bottom of the stairs, it should be positioned at the front of the lowest tread possible.
- **NEVER** use to keep child away from pool.
- This safety barrier is for domestic use only.
- This safety barrier has a manual closing system.
- **NEVER LEAVE** the child unattended when using this product.
- Children have died or been seriously injured when gates/enclosures are not securely installed.
- **DO NOT** put any goods which can be grabbed by children or pets near this product to prevent injury.
- Before using this product, carefully inspect for any loose parts and whether any parts need to be tightened.

WARNING

- This product is intended for use with children from 6 to 24 months or small to medium pets from 4.5kg(10 lbs) up to 18kg (40 lbs).
- **ALWAYS** check that safety barrier is correctly closed.
- Use only with the locking/latching mechanism securely engaged.
- Gate must be installed as close to the ground as possible, as per the installation guides.
- **NEVER** use with a child able to climb over or dislodge/open the gate or enclosure.
- **STOP USING** when a child can climb over or dislodge the gate.
- **Install** with this side away from child.
- Regularly check that the safety barrier is properly installed and secure.
- **ALWAYS** install and use as directed using **all** parts. Any additional or replacement parts should be obtained from after sales support.
- Barrier must be fitted between rigid surfaces such as plaster board, timber or hard wall.
- You **MUST** install wall cups to keep the gate in place. Without wall cups, child can push out and escape.
- The gate extends up from 55in to 197in wide and 34in tall, the minimum width of the opening is 27.6in, maximum width of opening is from 55in to 197in, the best width of opening is 35.4in.
- This product is a deterrent and not a substitute for adult supervision.

NEVER LEAVE children unattended. Check the gate regularly to ensure safe usage.

MOUNTINGS

Tor muss sein installiert In eine strukturell solide Öffnung . Stellen Sie sicher, dass die Montagefläche (Wand , Türrahmen , Treppe Beiträge , usw) ist stark , starr Und hat eine noch Oberfläche .

Notiz: Bei Verwendung eines Tors auf Treppen , es muss platziert werden entweder auf der Spitze Schritt oder auf Die unterste Stufe am unten .

Wählen Sie die passende Befestigung Methode aus dem folgenden Liste.




Installationsmethode von Holz Wand:

Bohren 5/64"(2 mm) Pilotlöcher use the screws Und mitgeliefert directly into the wood .
Verschraubung



Zur Installation
Schrauben




Installationsmethode von Trockenbau

Bohrer 5mm (3/16) Vorbohrungen , Einsatz grau Erweiterung Gummi und sichern Sie mit Schrauben .



Zur Installation

Graue Expansion Gummi
Schrauben




Installation method of brick wall:

Drill 5mm (3/16") pilot holes , insert Iron Expansion and secure with screws .



For Installation

Iron Expansion
screws



Installation method of concrete wall:

Drill 5mm (3/16") pilot holes , insert Iron Expansion and secure with screws .

This gate must only be fixed to a solid and secure surface. If unsure, überprüfen mit einem qualifizierten Baumeister oder Handwerker, dass die Installation Du beabsichtigen ist geeignet und sicher innerhalb der gewählt Standort.

WERKZEUGE VORBEREITUNG:




A. Philips Kopf
Mischschraubendreher


B. Bleistift C. Bohrmaschine

D. Schinken

BITTE WÄHLEN DER RICHTIG ZUBEHÖR UND EINE GEEIGNETE WAND,



Auf Holzmaterial installieren Installieren auf A harte Wand .




Nicht installieren auf trocken Holz , oder Glaswände.

MEASUREMENT PREPARATION :

Measure the door width to ensure that the gate can be installed normally.

WHAT'S IN THE BOX

Die gestrichelte Linie stellt die rechte Seite von der einziehbare Sicherheit Tor, Die Benutzer muss vor der Verwendung zusammengebaut werden. bitte entsprechend der nächste Seite für spezifische Montage Operationen.




MONTAGE TEILE



bitte nach dem nächsten Seite für spezifische Montage Operationen.

MULTIPLE INSTALLATION METHODS

CHOOSE THE INSTALLATION METHOD THAT SUITS YOU BEST



INSTALLATION IOIN SCHRITTEN

Notiz:

Vielen Dank für den Kauf dieses Produkts. Das Ganze Installation Verfahren dauert etwa 20 Minuten. Bitte Lesen Sie die Installation Handbuch sorgfältig, finden Sie die entsprechenden Komponenten und wählen Sie Die Rechts Standort Zu Sei installiert. Bitte vorbereiten ein elektrisch bohren, A markieren Stift Und A Schraubenzieher .

Bestätigen Sie die Anschlüsse vor der Installation .



DER RECHTS SEITE VON DER EINZIEHBAR SICHERHEIT TORSPEZIFISCHE MONTAGEVORGÄNGE .




1.Insert the Iron tube into the base.



2.Drill the short screws into the iron tube with the philips head Schraubendreher.



Eisenrohr.



4.Insert the upper fixing head hinein Die Eisen Rohr.



5.Drill the short screws into the iron tube with the philips head Schraubendreher.



6. Dieser Teil ist fertig .

Um die Trennfunktion besser zu realisieren, muss das Produkt auf dem Boden installiert werden .



7. Install the two brackets on the gate.



8. abziehen das Papier von Klebstoff Band aus den beiden Klammern.



9. Select the installation location, make sure the bottom of the main body door gate is on the ground.



10. Select the installation location, make sure the bottom of main body

Tür Tor Ison Boden. Wenn Dort Sind baseboard on the wall. Pis slide lower bracket up to the suitable position until go around the Fußleiste.



11. Take out door gate from the two brackets according to the arrow.



12. Mark the holes position of the two brackets and then pull out the two brackets from wall.



13. Drill holes in the marked place with an electric drill.



14. Insert the expansion screw in die Löcher.




15. Drill the two brackets to wall

as the holes.



16. Install gate to upper bracket as

the arrow.



17. Install gate to lower bracket as der Pfeil, bitte stellen Sie sicher, dass inghgreide of the gate. gate to upper bracket at first then install gate to lower bracket .



18. Install the two brackets on the



19. Peel off the paper of adhesive tape from the two brackets .



20. Select the installation location, make sure the bottom of the right side gate is on the ground.



20.1. If there are baseboard on the wall, pls slide lower bracket up to the suitable position until go around the baseboard.



21. Press the button according to the arrow and also put upward the gate from the two brackets at the same time.



22. Mark the holes position of the two brackets and then pull out the two brackets from wall .



23. Drill holes in the marked place with an electric drill.



24. Insert the expansion screw into the holes.



25. Drill the two brackets to wall as the holes.



26. Install the right side gate to upper bracket as the arrow.



27. Install the right side gate to lower bracket, please make sure install gate to upper bracket at first then install gate to lower bracket finally Screw down Four screws .



28. Lift up Turn to "unlock" position it shows green to unlock the gate



29. Pull the cloth horizontally to the opposite door frame and insert the lower end of the rod into the lower fixing heading.



30. Insert the upper end of the rod into the upper fixing head.




31. Turn to "Lock" position, it shows red to lock the gate .



32. The installation is complete, Enjoy your gate!

EINSTELLBAR LOWERGATE-MONTAGE **INSTALLATION**



ENTFERNEN



1. Press the button



2. Wenn Sie die Taste
Knopf und auch setzen
nach oben das Tor
von die Halterung am
gleichzeitig.

Installation steps for Mesh Gate Floor Hook

Dies ist ein optionales Zubehör: Sie können dieses Zubehör installieren auf Die Boden, ich fick dich Denkhema Ist lose . Wenn Es Ist Zu verhindern Kinder aus vorbeigehen unter dem Sicherheitstor , bitte Sei Sicher Zu verwenden Das Produkt zu schützen Sicherheit von Kindern .

bestätigen Armaturen Und vorbereiten Schere Und Handtücher vor Installation .



1. wählen geeignet Position An Die Doppelschicht Maschenware , unterhalb des Maschentors, und Verwenden Sie Scheren oder Verwenden Sie einen Schraubendreher, um ein kleines Loch von etwa 0,35 Zoll.

2. Attach the white ring to the hole you just cut. Make sure the top and the bottom covers of the white ring closed tightly.



Hinweis : Überprüfen Sie, ob die Spitze Und unten Abdeckungen Sind fest verschlossen.

3. put the metal ring over the white ring.

Method No.1 Punch



4. Mark the four holes of the cloth clip, drill holes of, with an electric drill as the marks.



5. Insert the expansion screw to all holes, drill the four screws to ground as the holes.



6. Done!

Method No.2 Punch-Free



4. Wipe the floor clean with a towel. Tear off the film on the surface of the double-sided tape and stick to the round transparent plastic part.



5. Tear off the other film on the surface of the tape and stick to the ground.



6. Done!

WIE ZU SPERREN DER TOR



Note: When gate is retracting always hold the handle and guide the gate evenly back into its original position in a horizontal direction. Never let go of handle when gate is retracting.

WIE MAN HINKOMMT DURCH DER TOR



Note: When gate is retracting always hold the handle and guide the gate evenly back into its original position in a horizontal direction. Never let go of handle when gate is retracting.

REINIGUNG ANWEISUNGEN


Verwenden Sie dazu einfach ein weiches feuchten Tuch zu Tor abwischen, trocknen nach Reinigung. TUN nicht Verwenden Sie keine Chemikalien oder Schleifmittel Reiniger .



Vielen Dank vielen Dank für die Wahl unseres Produkte. Bitte lesen Sie Anweisung Handbücher sorgfältig vor mit Das einziehbar Sicherheit Tor . Tun nicht verwenden Wenn beliebig Teil Ist Gebrochen , Zerrissen oder Fehlen . Bitte bewahren Sie die Bedienungsanleitung für für zukünftige Referenzzwecke



GEMACHT IN CHINA



04系列单手操作配件包说明书

ANWEISUNG HANDBUCH FÜR EINHÄNDIG BETRIEB

Notiz: Vielen Dank für den Kauf dieses Produkt. Bitte lesen Die Installation Handbuch sorgfältig, Bestätigen Sie die Ausstattung vor Installation .



- ① Eisenrohr* 1(Entfernen von Die hauptsächlich Körper des einziehbare Sicherheit Tor)
- ② obere Befestigung Kopf* 1 ③ Untere Befestigung Kopf* 1
- ④ Untere Klammer* 1
- ⑤ Halterung*4
- ⑥ Schraubendreher* 1
- ⑦ Stecker*8+2 Ersatz, Schrauben*8+2 Ersatz ⑧ kurze Schrauben*4+1 Ersatzschrauben
- ⑨ Aufkleber*4

INSTALLATION SCHRITTE



1.Insert the Iron tube into the base.



2.Drill the short screws into the iron tube with the philips head Schraubendreher.



3 Legen Sie die untere Halterung in die Eisen Rohr.



4.Insert the upper fixing head hinein Die Eisen Rohr.



5.Drill the short screws into the iron tube with the philips head Schraubendreher.




6. Dieser Teil ist fertig .

210.00 mm

85.00 mm

工艺：双面四色印刷

装订：骑马钉



工艺：双面四色印刷
装订：骑马钉

C20M60
YOKO C49M41
Y40KO

Growing up together with your kids

Retractable Safety Gate

Instruction Manual

Modè
e: SH20.006BB-
140CD SH20.006BB
-180CD
SH20.006BB-280CD



**IMPORTANT! READ AND
FOLLOW THESE INSTRUCTIONS
CAREFULLY AND KEEP FOR
FUTURE REFERENCE.**

210.00 mm

145.00 mm

TABLEAU DE CONTENU

INFORMATIONS DE SÉCURITÉ

warning	03
Mountings	05

WHAT'S IN THE BOX

parts	07
Assembly parts	08

INSTALLATION

Multiple installation	09
méthodes opérations	10
d'assemblage spécifiques	11
installation mesures	13
Réglable inférieur grille	14
monter à retirer	

CROCHET DE SOL

l'étapes d'installation	15
-------------------------	----

OPÉRATION

Comment pour ouvrir	17
et Verrouillage	19
Instructions de nettoyage	

GÉNÉRAL

Lisez attentivement ce manuel d'instructions et gardez-le dans un endroit sûr pour l'avenir référence . Le correct utiliser et entretien de ceci produit est essentiel .

ENTRETIEN

Vérifiez régulièrement que la porte fonctionne correctement et, lubrifier les charnières et composants mobiles avec un lubrifiant en aérosol approprié. Serrez et ajustez les supports pour assurer sécurisé lisse opération . Inspecter tous composants régulièrement et arrêt en utilisant si composant est endommagé ou manquant .

WARNING

- To prevent serious injury or death, securely install gate or enclosure and use according to manufacturer's instructions.
- Incorrect installation can be **DANGEROUS**.
- DANGER** to older children if climbing over the product.
- DO NOT** use the safety barrier if any components are damaged or missing.
- The safety barrier must not be fitted across windows.
- NEVER** install this product on glass doors. Install this product against reliable doors or walls.
- If the safety barrier is used at the top of the stairs, it should not be positioned below the top level.
- If the safety barrier is used at the bottom of the stairs, it should be positioned at the front of the lowest tread possible.
- NEVER** use to keep child away from pool.
- This safety barrier is for domestic use only.
- This safety barrier has a manual closing system.
- NEVER LEAVE** the child unattended when using this product.
- Children have died or been seriously injured when gates/enclosures are not securely installed.
- DO NOT** put any goods which can be grabbed by children or pets near this product to prevent injury.
- Before using this product, carefully inspect for any loose parts and whether any parts need to be tightened.

WARNING

- This product is intended for use with children from 6 to 24 months or small to medium pets from 4.5kg(10 lbs) up to 18kg (40 lbs).
- **ALWAYS** check that safety barrier is correctly closed.
- Use **only** with the locking/latching mechanism **securely** engaged.
- Gate must be installed as close to the ground as possible, as per the installation guides.
- **NEVER** use with a child able to climb over or dislodge/open the gate or enclosure.
- **STOP USING** when a child can climb over or dislodge the gate.
- **Install** with this side away from child.
- **Regularly** check that the safety barrier is properly installed and secure.
- **ALWAYS** install and use as directed using **all** parts. Any additional or replacement parts should be obtained from after sales support.
- Barrier must be fitted between rigid surfaces such as plaster board, timber or hard wall.
- You **MUST** install wall cups to keep the gate in place. Without wall cups, child can push out and escape.
- The gate extends up from 55in to 197in wide and 34in tall, the minimum width of the opening is 27.6in, maximum width of opening is from 55in to 197in, the best width of opening is 35.4in.
- This product is a deterrent and not a substitute for adult supervision.

NEVER LEAVE children unattended. Check the gate regularly to ensure safe usage.

MOUNTINGS

Grille doit être installée dans une ouverture structurellement saine. Assurez-vous que la surface de montage (mur), cadre de porte, marche articles, etc) est fort, rigide et a un pair surface.

Note: Si vous utilisez une barrière dans les escaliers, il doit être placé soit sur le haut étape ou sur le marche la plus basse au bas.

sélectionnez la fixation appropriée méthode parmi les suivantes liste.




Méthode d'installation de bois mur:

Percer trous pilotes de 5/64" (2 use the screws mm) et vissage directement into the wood.



Pour l'installation

vis



Méthode d'installation de Cloison sèche

Foret 5 mm (3/16) trous pilotes, insérer gris extension caoutchouc et sécurisé avec vis.




Pour l'installation

Greyexpansion caoutchouc
vis




Installation method of brick wall:

Drill 5mm (3/16") pilot holes, insert Iron Expansion and secure with screws.



For Installation

Iron Expansion
screws



Installation method of concrete wall:

Drill 5mm (3/16") pilot holes, insert Iron Expansion and secure with screws.

This gate must only be fixed to a solid and secure surface. If unsure, vérifier avec un qualifié constructeur ou personne de métier que l'installation toi avoir l'intention est adapté et sûr dans le choisi emplacement.

OUTILS PRÉPARATION:




UN. tête Philips
Jambon moi


B. crayon il C. perceuse électrique
vis conducteur

D.

S'IL TE PLAÎT SÉLECTIONNER LE APPROPRIÉ ACCESSOIRES ET UN MUR ADAPTÉ



Installer sur un matériau en bois . Installer sur un mur dur .




Ne pas installer sur
sec bois , ou des murs
en verre.

MEASUREMENT PREPARATION :


Measure the door width to ensure that the gate can be installed normally.

WHAT'S IN THE BOX

Le pointillé la ligne représente le côté droit de le rétractable sécurité grille, le utilisateurs il faut l'assembler avant de l'utiliser. s'il vous plaît selon le suivant page pour assemblage spécifique opérations.




ASSEMBLÉE PARTIES



s'il vous plaît selon la prochaine page pour assemblage spécifique opérations.

MULTIPLE INSTALLATION METHODS

CHOOSE THE INSTALLATION METHOD THAT SUITS YOU BEST



INSTALLATION IOEN ÉTAPES

Note:

Merci beaucoup d'avoir acheté ce produit. L'ensemble installation processus prend environ 20 minutes. s'il te plaît lire le installation manuel soigneusement, trouvez les composants correspondants et sélectionnez le droite emplacement à être installé . s'il te plaît préparer un électrique percer, un marque stylo et un tournevis .

confirmer les raccords avant l' installation.



LE DROITE CÔTÉ DE LE RÉTRACTABLE SÉCURITÉ OPÉRATIONS D'ASSEMBLAGE SPÉCIFIQUES AU PORTAIL .




1.Insert the Iron tube into the base.



2.Drill the short screws into the iron tube with the philips head tournevis.



tube de fer.



4.Insert the upper fixing head dans le fer tube.



5.Drill the short screws into the iron tube with the philips head tournevis.



6. Cette partie est terminée .

Le produit doit être installé au sol pour mieux réaliser la fonction de séparation.



7. Install the two brackets on the gate.



8. se détacher le papier d'adhésif ruban adhésif des deux supports.



9. Select the installation location, make sure the bottom of the main body door gate is on the ground.



10. Select the installation location, make sure the bottom of main body

porte portail is on sol. Si là sont baseboard on the wall. PIs slide lower bracket up to the suitable position until go around the plinthe.



11. Take out door gate from the two brackets according to the arrow.



12. Mark the holes position of the two brackets and then pull out the two brackets from wall.



13. Drill holes in the marked place with an electric drill.



14. Insert the expansion screw dans les trous.



15. Drill the two brackets to wall as the holes.



16. Install gate to upper bracket as the arrow.



17. Install gate to lower bracket as la flèche, assurez-vous qu'elle est bien right side of the gate. gate to upper bracket at first then install gate to lower bracket .



18. Install the two brackets on the



19. Peel off the paper of adhesive tape from the two brackets .



20. Select the installation location, make sure the bottom of the right side gate is on the ground.



20.1. If there are baseboard on the wall, pls slide lower bracket up to the suitable position until go around the baseboard.



21. Press the button according to the arrow and also put upward the gate from the two brackets at the same time.



22. Mark the holes position of the two brackets and then pull out the two brackets from wall .



23. Drill holes in the marked place with an electric drill.



24. Insert the expansion screw into the holes.



25. Drill the two brackets to wall as the holes.



26. Install the right side gate to upper bracket as the arrow.



27. Install the right side gate to —, please make sure install gate to upper bracket at first then install gate to lower bracket finally Screw down Four screws .



28. Lift up Turn to "unlock" position it shows green to unlock the gate



29. Pull the cloth horizontally to the opposite door frame and insert the lower end of the rod into the lower fixing heading.



30. Insert the upper end of the rod into the upper fixing head.




31. Turn to "Lock" position, it shows red to lock the gate .



32. The installation is complete, Enjoy your gate!

RÉGLABLE SUPPORT DE PORTE INF

INSTALLATION



À SUPPRIMER



1. Press the button



2. lorsque vous appuyez
le bouton et aussi mettre
la porte de la porte
de support au
en même temps.

Installation steps for Mesh Gate Floor Hook

Il s'agit d'un accessoire optionnel : vous pouvez installer cet accessoire sur le sol, je te le dis pense à mes mailles est lâche . Si il est à prévenir enfants depuis passage sous le barrière de sécurité , s'il vous plaît être bien sûr à utiliser ce produitto protéger sécurité des enfants .

confirmer accessoires et préparer ciseaux et serviettes avant installation .



1. choisir convenable position sur le double couche engrener , sous la porte maillée, et utiliser des ciseaux ou utilisez un tournevis pour percer un petit trou d'environ 0,35 pouces .

2 . Attach the white ring to the hole you just cut. Make sure the top and the bottom covers of the white ring closed tightly.



Remarque : vérifiez que le haut et bas couvertures sont hermétiquement fermé.

3. put the metal ring over the white ring.

Method No.1 Punch



4. Mark the four holes of the cloth clip, drill holes of, with an electric drill as the marks.



5. Insert the expansion screw to all holes, drill the four screw to ground as the holes.



6. Done!

Method No.2 Punch-Free



4. Wipe the floor clean with a towel. Tear off the film on the surface of the double-sided tape and stick to the round transparent plastic part.



5. Tear off the other film on the surface of the tape and stick to the ground.



6. Done!

OPERATION

COMMENT À VERROUILLAGE LE GRILLE



Note: When gate is retracting always hold the handle and guide the gate evenly back into its original position in a horizontal direction. Never let go of handle when gate is retracting.

COMMENT OBTENIR À TRAVERS LE GRILLE



Note: When gate is retracting always hold the handle and guide the gate evenly back into its original position in a horizontal direction. Never let go of handle when gate is retracting.

NETTOYAGE INSTRUCTIONS


utilisez simplement un chiffon doux chiffon humide pour essuyer la porte, sécher après nettoyage. FAIRE pas utiliser des produits chimiques ou abrasifs nettoyeurs .



Merci beaucoup beaucoup pour avoir choisi notre produits. Veuillez lire instruction manuels soigneusement avant en utilisant ce rétractable sécurité porte . Faire pas utiliser si n'importe lequel partie est Cassé , Déchiré ou Manquant .
veuillez conserver le manuel d'instructions pour référence future .



FAIT DANS CHINE



04系列单手操作配件包说明书

210.00 mm

INSTRUCTION MANUEL
POUR UNE MAIN
OPÉRATION

Note: Merci beaucoup d'avoir acheté ceci produit. s'il te plaît lire le installation manuel soigneusement, confirmer les raccords avant installation .

PARTIES

1



②

③

④

S ⑥

1

⑧

9

1 Itube de fer* 1(Supprimer de le principal corps de la sécurité rétractable grille)

② fixation supérieure
tête* 1 ③ Fixation
inférieure tête * 1 ④
Inférieur support * 1
⑤ Support*4
⑥ tournevis* 1
⑦ fiches *8+2 de rechange, vis *8+2
de rechange ⑧ vis courtes*4+1 vis de
rechange
⑨ autocollant *4

INSTALLATION

MESURES



1.Insert the Iron tube into the base.



2.Drill the short screws into the iron tube with the philips head tournevis.



3 Insérez le support inférieur dans le fer tube.



4.Insert the upper fixing head dans le fer tube.



5.Drill the short screws into the iron tube with the philips head tournevis.



6. Cette partie est terminée .

85 .00 mm

工艺：双面四色印刷

装订：骑马钉



工艺：双面四色印刷
装订：骑马钉

C20M60
YOKO C49M41
Y40KO

Growing up together with your kids

Retractable Safety Gate

Instruction Manual

Model:

SH20.006BB-140CD
SH20.006BB-180CD
SH20.006BB-280CD



**IMPORTANT! READ AND
FOLLOW THESE INSTRUCTIONS
CAREFULLY AND KEEP FOR
FUTURE REFERENCE.**

210.00 mm

145.00 mm

TAFEL VAN INHOUD

VEILIGHEIDSGEINFORMATIE

warning	03
Mountings	05

WHAT'S IN THE BOX

parts	07
Assembly parts	08

INSTALLATION

Meervoudig installatie	09
methoden specifieke	10
montagebewerkingen	11
installatie stappen	13
Verstelbaar lager hek berg	14
naar verwijderen	

VLOERHAAK

installatiestappen	15
--------------------	----

WERKING

Hoe om te openen en	17
Slot	19
reinigingsinstructie	

ALGEMEEN

Lees deze gebruiksaanwijzing zorgvuldig door en bewaar het op een veilige plaats voor de toekomst referentie . De juist gebruik En onderhoud hiervan product is essentieel .

ONDERHOUD

Regelmatig controleren dat de poort correct functioneert ja, scharnieren smeren en Bewegende onderdelen met een geschikte spray -smeermiddel. Bevestigingen vastdraaien en afstellen. ervoor zorgen zeker zacht operatie . Inspecteren alle componenten regelmatig En stop gebruik makend van als er onderdeel is beschadigd of vermist .

WARNING

- To prevent serious injury or death, securely install gate or enclosure and use according to manufacturer's instructions.
- Incorrect installation can be **DANGEROUS**.
- DANGER** to older children if climbing over the product.
- DO NOT** use the safety barrier if any components are damaged or missing.
- The safety barrier must not be fitted across windows.
- NEVER** install this product on glass doors. Install this product against reliable doors or walls.
- If the safety barrier is used at the top of the stairs, it should not be positioned below the top level.
- If the safety barrier is used at the bottom of the stairs, it should be positioned at the front of the lowest tread possible.
- NEVER** use to keep child away from pool.
- This safety barrier is for domestic use only.
- This safety barrier has a manual closing system.
- NEVER LEAVE** the child unattended when using this product.
- Children have died or been seriously injured when gates/enclosures are not securely installed.
- DO NOT** put any goods which can be grabbed by children or pets near this product to prevent injury.
- Before using this product, carefully inspect for any loose parts and whether any parts need to be tightened.

WARNING

- This product is intended for use with children from 6 to 24 months or small to medium pets from 4.5kg(10 lbs) up to 18kg (40 lbs).
- **ALWAYS** check that safety barrier is correctly closed.
- Use only with the locking/latching mechanism securely engaged.
- Gate must be installed as close to the ground as possible, as per the installation guides.
- **NEVER** use with a child able to climb over or dislodge/open the gate or enclosure.
- **STOP USING** when a child can climb over or dislodge the gate.
- **Install** with this side away from child.
- Regularly check that the safety barrier is properly installed and secure.
- **ALWAYS** install and use as directed using **all** parts. Any additional or replacement parts should be obtained from after sales support.
- Barrier must be fitted between rigid surfaces such as plaster board, timber or hard wall.
- You **MUST** install wall cups to keep the gate in place. Without wall cups, child can push out and escape.
- The gate extends up from 55in to 197in wide and 34in tall, the minimum width of the opening is 27.6in, maximum width of opening is from 55in to 197in, the best width of opening is 35.4in.
- This product is a deterrent and not a substitute for adult supervision.

NEVER LEAVE children unattended. Check the gate regularly to ensure safe usage.

MOUNTINGS

Hek moet zijn geïnstalleerd in een structureel gezonde opening . Zorg voor een montageoppervlak (muur) , deurkozijn , trap berichten , enz) is sterk , onbuigzaam En heeft een gelijke oppervlak .

Opmerking: Bij gebruik van een poort op een trap , het moet geplaatst worden ofwel op de bovenkant stap of op de laagste trede bij de onderkant .

Selecteer de juiste bevestiging methode uit de volgende lijst.




Installatiemethode van houten muur:

Oefening 5/64"(2mm) geleidegaten En use the screws
schroeven



Voor installatie
schroeven



Installatiemethode van Gipsplaat

Boor 5mm (3/16) proefgaten , grijs invoegen uitbreiding
rubber en veilig met schroeven .




Voor installatie

Grijze expansie rubber
schroeven




Installation method of brick wall:

Drill 5mm (3/16") pilot holes ,
insert Iron Expansion
and secure with screws .



For Installation

Iron Expansion
screws



Installation method of concrete wall:

Drill 5mm (3/16") pilot holes ,
insert Iron Expansion
and secure with screws .

This gate must only be fixed to a solid and secure surface. If unsure, rekening met een gekwalificeerde bouwer of vakmensen die de installatie uitvoeren Jij van plan zijn is geschikt en veilig binnen de gekozen locatie.

HULPMIDDELEN VOORBEREIDING:




A. philips hoofd
schroef bestuurder


B. potlood C. boormachine

D. Ham mijl

ALSJEBLIEFT SELECT DE JUIST ACCESSOIRES EN EEN GESCHIKTE MUUR,



Installeren op houten materiaal . Installeren op A harde muur .




Niet installeren op
droog hout , of glazen
wanden.

MEASUREMENT PREPARATION :

Measure the door width to ensure that the gate can be installed normally.

WHAT'S IN THE BOX

De gestippelde lijn vertegenwoordigt de rechterkant van de intrekbare veiligheid hek, de gebruikers moet je het eerst in elkaar zetten voordat je het kunt gebruiken. alstublieft volgens de volgende pagina voor specifieke assemblage operaties.




MONTAGE ONDERDELEN



alstublieft volgens de volgende pagina voor specifieke montage operaties.

MULTIPLE INSTALLATION METHODS

CHOOSE THE INSTALLATION METHOD THAT SUITS YOU BEST



INSTALLATIESTAPPENIO

Opmerking:

Hartelijk dank voor de aankoop van dit product. Het geheel installatie proces neemt ongeveer 20 notulen. Alsjeblieft lees de installatie handmatig Zoek zorgvuldig de bijbehorende componenten en selecteer de rechts locatie naar zijn geïnstalleerd . Alsjeblieft voorbereiden een elektrisch oefening, A markering pen En A schroevendraaier .

Controleer de fittingen vóór de installatie .



DE RECHTS KANT VAN DE INTREKBAAR VEILIGHEID POORTSPECIFIEKE MONTAGEWERKINGEN .




1.Insert the Iron tube into the base.



2.Drill the short screws into the iron tube with the philips head schroevendraaier .



ijzeren buis.



4.Insert the upper fixing head naar binnen de ijzer buis.



5.Drill the short screws into the iron tube with the philips head schroevendraaier .



6. Dit onderdeel is af .

Het product moet op de grond worden geïnstalleerd om de scheidingsfunctie beter te kunnen realiseren.



7. Install the two brackets on the gate.



8. afpellen het papier van lijm plakband van de twee haakjes.



9. Select the installation location, make sure the bottom of the main body door gate is on the ground.



10. Select the installation location, make sure the bottom of main body

deur poort is on grond. Als daar zijn baseboard on the wall. Pis slide lower bracket up to the suitable position until go around the plint.



11. Take out door gate from the two brackets according to the arrow.



12. Mark the holes position of the two brackets and then pull out the two brackets from wall.



13. Drill holes in the marked place with an electric drill.



14. Insert the expansion screw in de gaten.



15. Drill the two brackets to wall as the holes.



16. Install gate to upper bracket as the arrow.



17. Install gate to lower bracket as de pijl, zorg ervoor dat hij hoog is gate to upper bracket at first then install gate to lower bracket .



18. Install the two brackets on the right side of the gate.



19. Peel off the paper of adhesive tape from the two brackets .



20. Select the installation location, make sure the bottom of the right side gate is on the ground.



20.1. If there are baseboard on the wall, pls slide lower bracket up to the suitable position until go around the baseboard.



21. Press the button according to the arrow and also put upward the gate from the two brackets at the same time.



22. Mark the holes position of the two brackets and then pull out the two brackets from wall .



23. Drill holes in the marked place with an electric drill.



24. Insert the expansion screw into the holes.



25. Drill the two brackets to wall as the holes.



26. Install the right side gate to upper bracket as the arrow.



27. Install the right side gate to —, please make sure install gate to upper bracket at first then install gate to lower bracket finally Screw down Four screws .



28. Lift up Turn to "unlock" position it shows green to unlock the gate



29. Pull the cloth horizontally to the opposite door frame and insert the lower end of the rod into the lower fixing heading.




30. Insert the upper end of the rod into the upper fixing head.



31. Turn to "Lock" position, it shows red to lock the gate .



32. The installation is complete, Enjoy your gate!



VERWIJDEREN



1. Press the button



2. wanneer u op de knop en ook neerzetten omhoog de poort van de beugel bij de tegelijkertijd.

Installation steps for Mesh Gate Floor Hook

Dit is een optionele accessoire: U kunt deze accessoire installeren op de vloer, ik weet het denkmash is los . Als Het is naar voorkomen kinderen van voorbijgaan onder de veiligheidshekje , alstublieft zijn Zeker naar gebruik dit productto beschermen de veiligheid van kinderen .

bevestigen uitrusting En voorbereiden schaar En handdoeken voor installatie .



1. kiezen geschikt positie op de dubbellaags gaas , onder de gaaspoort, en gebruik een schaar of Gebruik een schroevendraaier om een klein gaatje van ongeveer 0,35 te maken inches

2 . Attach the white ring to the hole you just cut. Make sure the top and the bottom covers of the white ring closed tightly.



op : controleer of de bovenkant En onderkant dekt Zijn goed gesloten.

3. put the metal ring over the white ring.

Method No.1 Punch



4. Mark the four holes of the cloth clip, drill holes of, with an electric drill as the marks.



5. Insert the expansion screw to all holes, drill the four screw to ground as the holes.



6. Done!

Method No.2 Punch-Free



4. Wipe the floor clean with a towel. Tear off the film on the surface of the double-sided tape and stick to the round transparent plastic part.



5. Tear off the other film on the surface of the tape and stick to the ground.



6. Done!

HOE NAAR SLOT DE HEK



Note: When gate is retracting always hold the handle and guide the gate evenly back into its original position in a horizontal direction. Never let go of handle when gate is retracting.

HOE ER TE KOMEN DOOR DE HEK



Note: When gate is retracting always hold the handle and guide the gate evenly back into its original position in a horizontal direction. Never let go of handle when gate is retracting.

SCHOONMAAK INSTRUCTIES

gebruik gewoon een zachte vochtige doek om poort afvegen, droog na schoonmaak. DOEN niet gebruik chemicaliën of schuurmiddelen schoonmakers .




Hartelijk dank veel voor het kiezen van onze producten. Lees alstublieft instructie handleidingen voorzichtig voor gebruik makend van dit intrekbaar veiligheid poort . Doen niet gebruik als elk deel is Gebroken , Stuk of Vermist .

Bewaar de gebruiksaanwijzing voor toekomstige referentie .



GEMAAKT IN CHINA




04系列单手操作配件包说明书

INSTRUCTIE HANDMATIG VOOR ÉÉN HAND WERKING

Opmerking: Hartelijk dank voor de aankoop hiervan product. Alsjeblieft lezen de installatie handmatig voorzichtig, bevestig de fittingen voordat installatie .

ONDERDELEN



- ① Iron buis* 1(Verwijderen uit de voornaamst lichaam van de intrekbare veiligheid hek)
- ② bovenste bevestiging hoofd* 1
- ③ Onderste bevestiging hoofd * 1
- ④ Lager haakje * 1
- ⑤ Beugel*4
- ⑥ schroevendraaier* 1
- ⑦ stekkers *8+2 reserve, schroeven
- *8+2 reserve ⑧ korte schroeven*4+1 reserveschroeven
- ⑨ sticker *4

INSTALLATIE STAPPEN



1.Insert the Iron tube into the base.



2.Drill the short screws into the iron tube with the philips head schroevendraaier.



3 Plaats de onderste beugel in de ijzer buis.



4.Insert the upper fixing head naar binnen de ijzer buis.



5.Drill the short screws into the iron tube with the philips head schroevendraaier.



6. Dit onderdeel is af .

210.00 mm

85.00 mm