

Air-operated double diaphragm pumps have long been recognized as the most flexible pumps for handling difficult liquids at relatively low pressures and flows. The range of applications is virtually limitless. MECLUBE AODD pumps come in many sizes and choices of construction materials. Suitable for water, antifreeze, windscreen and AdBlue® transfer.



**Art. 028-P035-AB2 Air-operated double diaphragm pump**  
**Meclube model P35**

Made in polypropylene

Compression ratio: 1:1  
Max flow rate: 35 l/min  
Fluid connection: 1/2" BSP  
Air connection: 6 mm  
Max air pressure: 8 bar  
Max delivery height: 70 m  
Max suction lift dry: 5,0 m  
Max suction lift wet: 9,8 m

**EX II 3/3 GD h IIB T4 135°C ATEX zone2**



**Art. 028-P055-AB2 Air-operated double diaphragm pump**  
**Meclube model P55**

Made in polypropylene

Compression ratio: 1:1  
Max flow rate: 55 l/min  
Fluid connection: 1/2" BSP  
Air connection: 1/4" BSP  
Max air pressure: 8 bar  
Max delivery height: 80 m  
Max suction lift dry: 5,0 m  
Max suction lift wet: 9,8 m

**EX II 3/3 GD h IIB T4 135°C ATEX zone2**

Ref.	Casing	Diaphragm	Balls	Gasket	Fluids
------	--------	-----------	-------	--------	--------

<b>028-P035-AB2</b>	Polypropylene	Hytrel+Ptfe	Ptfe	Viton	Water-Anti-freeze-Windscreen- AdBlue®
<b>028-P055-AB2</b>	Polypropylene	Hytrel+Ptfe	Ptfe	Viton	Water-Anti-freeze-Windscreen- AdBlue®

Ref.	Flow rate	Max viscosity	Max.Temp.	Inlet-outlet	Weight	Packaging
	l/min	CPS	°C	BSPG	Kg	mm

<b>028-P035-AB2</b>	<b>35</b>	15000	65	1/2"	2	250X180X260
<b>028-P055-AB2</b>	<b>55</b>	20000	65	1/2"	4	310X195X290