ACTUATOR SERIES ARA500 3-POINT

ESBE Actuator Series ARA500 for operating ESBE mixing valves DN 15-50. The actuators have an operating range of 90° and can easily be manually operated.

OPERATION

The ESBE series ARA500 is a compact actuator designed for operating rotary mixing valves DN 15-50. The actuator is controlled by 3-point signal, and are recommended for mixing applications. The actuator has an operating range of 90° and the valve can easily be manually operated by the pull-and-turn knob on the front of the actuator.

VERSIONS

The ARA500 actuators are available for 230 V AC 50 Hz or 24 V AC 50 Hz. The actuator is supplied either with an attached 1.5 m connection cable or with a plug in contact (Molex). Running time is 120 seconds.

An auxiliary switch fixed to 45° is available as an option. (Mainly for VRB valve applications).





3-point, auxiliary switch



3-point, molex contact

SUITABLE MIXING VALVES

Thanks to the special interface between the actuator series ARA500 and the ESBE valve series VRG100, VRG200, VRG300 and VRB100, the unit as a whole has a unique stability and precision when regulating.

- Series VRG100
- Series VRG200 Series VRG300
- Series VRH100
- Series VRB100
- Series HG

ADAPTOR KITS

The actuator is delivered either mounted together with valve from ESBE factory or otherwise supplied complete with an adaptor kit for easily fitting onto an ESBE rotary mixing valve series VRG / VRB.

DELIVERY

Serie deliveries are as a multi-package-solution since the ESBE series ARA500 is targeted specific towards OEM customer segment.


TECHNICAL DATA Ambient temperature: max. +55°C _min. -5°C _with fixed cable: IP41 Enclosure rating:_ with plug-in contact, type Molex: IP20 Protection class: 230 ± 10%V AC, 50 Hz Power supply: 24 ± 10%V AC, 50 Hz Power consumption: _230V AC: 5 VA 24V AC: 2 VA Rating auxiliary switch: _ _6(3) A 250V AC Weight: _ 0,4 kg

(€ LVD 2014/35/EU EMC 2014/30/EU RoHS 2011/65/EU

EAC

WIRING


The actuator should be preceded by a multi-pole contact breaker in the fixed installation.



Actuator 3-point, with fixed cable

Option, Auxiliary switch


The actuators are fitted with two separate cables, one cable for actuator regulation and one for the auxiliary switch.




Actuator 3-point. with plug-in contact

ACTUATOR

SERIES ARA500 3-POINT





Installation dimensions for Actuator Series ARA500 with ESBE VRG100, VRG200, VRG300 and VRB100 mixing valves.

PRODUCT ASSORTMENT

SERIES ARA500, 3-POINT - With cable

Art. No.	Reference	Voltage [V AC]	Running time 90° [s]	Control signal*	Torque [Nm]	Note
12141310	ARA561	230	120	3-point SPDT	6	1)
12140310	ARA563	24	120	3-point SPDT	6	1]

^{* 3-}point SPDT = Single Pole Double Throw Note 1) This art.no. describes a neutral single pack version. There will be an other art.no. for multi-package-solution.

SERIES ARA500, 3-POINT - With plug-in contact (Molex)

Art. No.	Reference	Voltage [V AC]	Running time 90° [s]	Control signal*	Torque [Nm]	Note
12146310	ARA565	230	120	3-point SPDT	6	1)
12145310	ARA567	24	120	3-point SPDT	6	11

^{* 3-}point SPDT = Single Pole Double Throw Note 1) This art.no. describes a neutral single pack version. There will be an other art.no. for multi-package-solution.

SERIES ARA500, OPTION - Auxiliary switch

Art. No.	Reference	Note	
16200700	ESBE ARA801, Auxiliary switch kit ARA600/ARA500	For versions with connected cable	
16201700	ESBE ARA801, Auxiliary switch kit ARA500	For versions with plug-in contact (Molex)	

SERIES ARA500, OPTION - Cable with molex connector (for plug-in-contact versions)

Art. No.	Reference	Note	
46050300	ESBE ALZ801, 3-wire IP20, cable length 1.6m	For versions with plug-in contact (Molex)	
46050400	ESBE ALZ801, 6-wire IP20, cable length 1.6m	For versions with plug-in contact (Molex)	

