

Tabela doboru kompletów elektrycznych

długość zanurzeniowa [mm]	370	310	360	370	305	360	410	480	450	500	450	450	500	500	500	500	650	650	400	500	680	750								
mocowanie	korek 5/4"			korek 6/4"					flansza Ø 180							flansza Ø 280				korek 6/4"										
numer katalogowy	41-020001	41-020002	41-030001	41-020011	41-020015	41-030011	41-045015	41-060015	41-020021	41-030021	41-045021	41-060021	41-090021	41-120021	41-090020	41-120020	41-180020	41-240020	41-045011	41-060011	41-090016	41-120011								
napięcie [V]	230			230					230							400							400				400			
moc [kW]	2,0	2,0	3,0	2,0	2,0	3,0	4,5	6,0	2,0	3,0	4,5	6,0	9,0	12,0	9,0	12,0	18,0	24,0	4,5	6,0	9,0	12,0								
SGW(L)x2, SGW(L)P	•	•	•																											
SGW(S) Rondo Premium 120-140	•	•	•																											
SG(S) Fusion 100	•	•	•																											
SGW(S) Vulcan Kombi 100-140 (stojący)		•																												
SGW(S) Vulcan Kombi 200 (stojący)				•	•	•	•												•											
SGW(S) Mini Tower 100-140	•	•	•																											
SGW(S) Tower 200-300				•	•	•	•	•	•	•	•	•	•	•					•	•										
SGW(S) Tower 400-500				•	•	•	•	•	•	•	•	•	•	•					•	•										
SGW(S) Tower 700							•	•							•	•	•	•	•	•	•									
SGW(S) Tower 1000-1500							•	•							•	•	•	•	•	•	•	•								
SGW(S)B Tower Biwał 200-300				•	•	•	•	•	•	•	•	•	•	•					•	•	•	•								
SGW(S)B Tower Biwał 400-500				•	•	•	•	•	•	•	•	•	•	•					•	•										
SGW(S)B Tower Biwał 700							•	•							•	•	•	•	•	•	•	•								
SGW(S)B Tower Biwał 1000-1500							•	•							•	•	•	•	•	•	•	•								
SG(S) Tower Acu 100-140	•	•	•																											
SG(S) Tower Acu 200-300				•	•	•	•	•	•	•	•	•	•	•					•	•										
SG(S) Tower Acu 400-500				•	•	•	•	•	•	•	•	•	•	•					•	•										
SG(S) Tower Acu 700				•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•								
SG(S) Tower Acu 1000-1500				•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•								
SG(S) Tower Acu 2000-3000															•	•	•	•	•	•	•	•								
SGW(S) Maxi 250-300				•	•	•	•	•	•	•	•	•	•						•	•										
SGW(S) Maxi 400-500				•	•	•		•	•	•	•	•	•	•					•	•										
SGW(S) Maxi 700								•							•	•	•	•	•	•	•	•								
SGW(S) Maxi 1000								•							•	•	•	•	•	•	•	•								
SGW(S) Maxi 800-1000 z węz 9 i 12 m²															•	•	•	•												
SGW(S)B Maxi Plus 300				•	•	•	•	•	•	•	•	•	•	•					•	•										
SGW(S)B Maxi Plus 400-500				•	•	•	•	•	•	•	•	•	•	•					•	•										
SGW(S)B Maxi Plus 800-1000								•					•	•	•				•	•	•	•								
SGW(S) Tower Grand 160-500				•	•	•	•	•	•	•	•	•	•	•					•	•										
SG(K) Kumulo 300/80-380/120				•	•	•	•	•											•	•										
SG(K) Kumulo 500/160-600/200				•	•	•	•	•											•	•	•									
SG(K) Kumulo 800/200-1000/200				•	•	•	•	•											•	•	•	•								
SG(K) Complete 250/110				•	•	•	•	•	•	•	•	•							•	•										
SG(K)M Multi-Inox 600				•	•	•	•	•											•	•										
SG(K)M Multi-Inox 800-2000				•	•	•	•	•											•	•	•	•								
SG(B) 60-100				•	•	•	•												•	•										
SG(B) 120-140				•	•	•		•											•	•										
SG(B) 200-300							•	•											•	•										
SG(B) 400-500							•	•											•	•										
SG(B) 800-2000								•											•	•	•	•								
SG(B) 3000-5000															•	•	•	•	•	•	•	•								
SG(B) z węz. spiralną 200-500															•	•	•	•	•	•										
SG(B) z węz. spiralną 800-2000															•	•	•	•	•	•	•	•								
SG(B) z maksymalnie dużą wężownicą spiralną 200-300				•	•	•	•	•											•	•										
SG(B) z maksymalnie dużą wężownicą spiralną 400-500				•	•	•	•	•											•	•										
SG(B) z maksymalnie dużą wężownicą spiralną 800-1000															•	•	•	•												
SG(B) z dwiema maksymalnie dużymi węz. spiralnymi 800-1000												•	•	•																