## **LogiLink**<sub>®</sub>



### DisplayPort™ to HDMI™ Adapter

Art. No.: CV0100

The DisplayPort to HDMI adapter receives both video and audio streams from an upstream DisplayPort source link and converts to a HDMI output.

#### **Features:**

- » Compliant with DisplayPort 1.2 specification
- » Supports video resolutions up to 4 K@30 Hz
- » Supports RBR, HBR, HBR2, DPCP, HDCP 1.4, 3D
- » Supports Dolby Digital, Dolby Digital Plus, DTS, dts-HD, DVD audio, SACD, True HD audio data
- » Low power operation, powered from DisplayPort source
- » DisplayPort connector with latches provides a secure connection with a release button that must be depressed before unplugging
- » Portable adapter connects a DisplayPort (DP, DP++, DisplayPort++) equipped laptop or desktop to an HDTV, monitor, or projector with HDMI port



### **Specification:**

Input Connector	DisplayPort 20pin, male
Output Connector	HDMI-A 20pin, female
HDMI Version	1.4
DisplayPort Version	1.2
HDCP Version	1.4
Video Resolution	Up to 4Kx2K@30 Hz
Video Bandwidth	8,91 Gbps
Video Amplifier Bandwidth	10,2 Gbps
EDID Management	Pass-through
DDC (Display Data Channel)	Pass-through
TMDS (Transition Minimized Differential Signaling)	Yes







# LogiLink<sub>®</sub>



## DisplayPort™ to HDMI™ Adapter

Art. No.: CV0100

Umcompressed Audio (such as LPCM)	Yes
Compressed Audio (such as Dolby TrueHD™)	Yes
Color Depth	RGB, YCbCr 4:4:4, YCbCr 4:2:2, 8, 10, 12 and 16-bit
8bit/10bit Data Transmission	Yes
Operating Temperature	0°C–45°C
Operating Humidity	10%-85 % RH (no condensation)
Storage Temperature	-10°C-80°C
Storage Humidity	5%–90 % RH (no condensation)
Material	ABS
Color	White
Dimensions	4,8x2,1x1,2 cm
Weight	10 g

### **Package Contents:**

- » 1x DisplayPort to HDMI Adapter
- » 1x User Manual

### **Package Information:**

» Packing Dimension: 150x137x12 mm

» Packing Weight: 0,02kg

» Carton Dimension: 500x320x210 mm

» Carton Q'ty: 350 pcs» Carton Weight: 7,8 kg







