



Econova 5W-20 | Fully synthetic engine oil

Property

- proven fuel saving and reduced emissions thanks to lowered HTHS viscosity
- keeps the engine clean and protects against wear and corrosion
- excellent cold starting characteristics
- Low SAPS technology with reduced content of sulphated ash, phosphorus and sulphur
- increases the service life of exhaust aftertreatment systems such as catalytic converters (SCR) and particulate filters (GPF/DPF) in gasoline and diesel engines

Application area

- especially suitable for Ford
- only to be used in vehicles in which an engine oil viscosity of 5W-20 is recommended
- suitable for gasoline and diesel engines
- suitable for passenger cars and light commercial vehicles

Note

- Technical data subject to change without notice. Please observe the vehicle or machine manufacturer's directions. Please refer to the safety data sheet for further information.

Typical properties

Property	Unit	Value
Viscosity SAE	-	5W-20
Color	-	brown
Viscosity @ 40°C	mm ² /s	45
Viscosity @ 100°C	mm ² /s	8.3
Viscosity index	-	162
Density @ 15°C	kg/l	0.855
Viscosity CCS @ -30°C	mPa·s	4100
Viscosity HTHS @ 150°C	mPa·s	2.6
Zinc content	ppm	880
Sulphated ash	g/100g	0.8
Pour Point	°C	-39
Flash Point	°C	220

Available packaging

1 L bottle	Case 12 x 1 L bottles
50 kg drum (approx. 58 L)	175 kg drum (approx. 205 L)

Specifications

ACEA C5
API SJ*, SL*, SL/CF*, SM*, SN/CF
Chrysler MS 6395
Fiat 9.55535-CR1
Ford M2C948-B
Jaguar Land Rover STJLR.03.5004

* Additional Specifications