



SIRIO

antenne

MOBILE ANTENNAS

MADE IN ITALY since 1972

TITANIUM series

FEATURES

- # CB & 10m Mobile antennas
- # Tunable from 27 to 28.5 MHz
- # 180° adjustable whip
- # Detachable for car-wash
- # Suitable for magnetic mount

TECHNICAL DATA

Type:	base loaded
Impedance:	50 Ω
Frequency range:	27... 28.5 MHz
Polarization:	linear vertical
SWR @ res. freq.:	≤ 1.2
Max. Power	
TITANIUM 800, TITANIUM 1000	15 Watts (CW) continuous
	150 Watts (CW) short time
TITANIUM 1200	20 Watts (CW) continuous
	100 Watts (CW) short time
TITANIUM 1500 Black	35 Watts (CW) continuous
	250 Watts (CW) short time
Bandwidth @ SWR ≤ 2 :	
TITANIUM 800	≥ 1100 kHz (100 channel)
TITANIUM 1000	≥ 1200 kHz (110 channel)
TITANIUM 1200	≥ 1400 kHz (125 channel)
TITANIUM 1500 Black	≥ 1600 kHz (140 channel)
Height (approx.):	
TITANIUM 800	790 mm, 2.6 ft
TITANIUM 1000	975 mm, 3.2 ft
TITANIUM 1200	1215 mm, 4.0 ft
TITANIUM 1500 Black	1420 mm, 4.6 ft
Weight (approx.):	400 gr, 0.88 lb
Mount type:	"N" mount, hole $\varnothing 12.5$ mm, $\varnothing 1/2$ in
Cable length / type:	4m, 13 ft / RG58

P/N 2200605.01 or .07	TITANIUM 800 N or NE
P/N 2204505.01 or .07	TITANIUM 1000 N or NE
P/N 2204505.01/S or .07/S	TITANIUM 1200 N or NE
P/N 2204506.02 or .08	TITANIUM 1500 Black N or NE

P/N 2200605.61	TITANIUM 800 MAG
P/N 2204505.61	TITANIUM 1000 MAG
P/N 2204505.61/S	TITANIUM 1200 MAG

Low profile



NE mount chrome
2500202.01



N mount chrome
2500102.01

STAINLESS
STEEL SPRING
WITH NYLON
REINFORCE

TAPERED
STAINLESS
STEEL

BLACK
CHROMED
TAPERED
STAINLESS
STEEL

TITANIUM 800

TITANIUM 1000
TITANIUM 1200

TITANIUM 1500
Black

TITANIUM MAG