

## Technical Data Sheet

Revised: 2022/05/06 (version 1.0)

# PETRONAS Urania DAILY TEK PLUS 0W-30



### Description and Applications

PETRONAS Urania DAILY TEK PLUS 0W-30 is a synthetic based formulation engine oil developed in co-engineering with IVECO and FPT to offer high performance and exceptional protection for the engine. Its particular formulation is obtained as a result of thousands of hours of laboratory, bench and road tests.

PETRONAS Urania DAILY TEK PLUS 0W-30 is recommended for the IVECO Daily (Euro 6 and Euro VI Model Year 2016 and later), providing extended oil drain interval (up to 50.000 km), outstanding Fuel Economy, improved wear protection and reduced oil consumption, to reduce the TCO (Total Cost of Ownership).

### Approvals, Specifications and Recommendations

#### Approvals:

- IVECO 18-1811 SC1 LV 21 C.T.R. Nr I169.L21

Note: Always consult your owner's manual to check recommended viscosity grade and specifications for your specific vehicle

### Typical Physical Data

Parameters	Method	Unit	Typical Value
Appearance	--	--	B&C
Density @ 15°C	ASTM D 4052	g/cm <sup>3</sup>	0.841
Kinematic Viscosity @ 100°C	ASTM D 445	mm <sup>2</sup> /s (cSt)	12.2
Viscosity Index	ASTM D 2270	--	180
CCS Viscosity @ -35°C	ASTM D 5293	mPa.s (cP)	5000
Flash Point COC	ASTM D 92	°C	228
TBN	ASTM D 2896	mg KOH/g	7.2

All technical data is provided for reference only. These characteristics are typical of current production. Whilst future production will conform to PLI's specification, variations in these characteristics may occur.

#### Health, Safety and Environment

This product is unlikely to present any significant health and safety hazards when used in the recommended application. Avoid contact with skin. Wash immediately with soap and water after skin contact. Do not discharge into drains, soil or water.

For further detail regarding storage, safe handling, and disposal of product, please refer to product SDS or contact us at: [www.pli-petronas.com](http://www.pli-petronas.com)

#### Important Note

The word PETRONAS, the PETRONAS logo and such other related trademarks and/or marks used herein are trademarks or registered trademarks of PETRONAS Lubricants International Sdn. Bhd. ("PLISB"), or its subsidiaries or related Holding Corporation under license unless indicated otherwise. The PLI Documents and the information contained herein is believed to be accurate as of the date of printing. PLISB makes no express or implied representation or warranties as to its accuracy or completeness or information in or any transaction performed. The PLI Documents information provided is based on standard tests under laboratory conditions and is given only as a guide. Users are advised to ensure that they refer to the latest version of these PLI Documents. It is the responsibility of the users to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations imposed by the respective local authorities.

Safety Data Sheets are available for all our products and should be only be consulted for appropriate information regarding storage, safe handling and disposal of the product. No responsibility shall be taken by either PLISB or its subsidiaries and related holding corporation for any loss or injury or any direct, indirect, special, exemplary, consequential damages or any damages whatsoever, whether in action of contract, negligence or other tortious action, in connection or resulting from abnormal use of the materials and/or information, from any failure to adhere to recommendations, or from hazards inherent in the nature of the materials and/or information. All products, services and information supplied are under our standard conditions of sale. Please consult with any of our local representative in the event you require any further information.

Code: 81100